

4 Technical data

4.1 Planning drawing WOLFF 6031.8 *clear*




Fig. 4.1: Planning drawing WOLFF 6031.8 *clear*

[X] Max. hook height, see tower combination

Data WOLFF 6031.8 *clear*

Item	Data
Crane type	BGL-GRUPPE C.0.10.0224
Design	Tower crane with slewing trolley jib on top, climbing possible
Type of placement	Stationary or Travelling
Calculation basis	EN
Load moment	Max. 2592 kNm
Hoist winch	Hw 845FU / Hw 875FU

Tab. 4.1: Data WOLFF 6031.8 *clear*

4.2 Planning drawing WOLFF 6031.12 *clear*




Fig. 4.2: Planning drawing WOLFF 6031.12 *clear*

[X] Max. hook height, see tower combination

Data WOLFF 6031.12 *clear*

Item	Data
Crane type	BGL-GRUPPE C.0.10.0224
Design	Tower crane with slewing trolley jib on top, climbing possible
Type of placement	Stationary or Travelling
Calculation basis	EN
Load moment	Max. 2580 kNm
Hoist winch	Hw 845FU / Hw 875FU

Tab. 4.2: Data WOLFF 6031.12 *clear*

4.3 Load capacity tables and counterweight arrangement

4.3.1 Load capacity table WOLFF 6031.8 clear (8.5 t)

8.5 t	Radius [m]	25	30	32.5	35	37.5	40	42.5	45	47.5	50	52.5	55	57.5	60	62.5	65	
Jib length [m]	65	2.75- 21.7	7.3	5.9	5.4	5.0	4.6	4.2	3.9	3.7	3.4	3.2	3.0	2.9	2.7	2.6	2.4	2.3
	62.5	2.75- 23.5	8.0	6.5	5.9	5.5	5.0	4.7	4.3	4.1	3.8	3.6	3.4	3.2	3.0	2.8	2.7	
	60	2.75- 25.2	8.5	7.0	6.4	5.9	5.4	5.1	4.7	4.4	4.1	3.9	3.7	3.5	3.3	3.1		
	57.5	2.75- 26.0	8.5	7.3	6.6	6.1	5.6	5.2	4.9	4.6	4.3	4.0	3.8	3.6	3.4			
	55	2.75- 26.6	8.5	7.5	6.8	6.3	5.8	5.4	5.0	4.7	4.4	4.2	3.9	3.7				
	52.5	2.75- 27.1	8.5	7.6	7.0	6.4	5.9	5.5	5.1	4.8	4.5	4.2	4.0					
	50	2.75- 28.0	8.5	7.9	7.2	6.6	6.1	5.7	5.3	5.0	4.7	4.4						
	47.5	2.75- 28.6	8.5	8.1	7.4	6.8	6.3	5.9	5.5	5.1	4.8							
	45	2.75- 29.0	8.5	8.2	7.5	6.9	6.4	6.0	5.6	5.2								
	42.5	2.75- 29.7	8.5	8.4	7.7	7.1	6.6	6.1	5.7									
	40	2.75- 30.1	8.5	8.5	7.8	7.2	6.7	6.2										
	37.5	2.75- 30.2	8.5	8.5	7.9	7.2	6.7											
	35	2.75- 30.5	8.5	8.5	7.9	7.3												
	32.5	2.75- 30.4	8.5	8.5	7.9													
	30	2.75- 30.0	8.5	8.5														

Tab. 4.3: Load capacity table WOLFF 6031.8 clear (8.5 t)

The load capacity figures relate to 42.0 m hook travel. At larger hook travels, the permissible load capacity is reduced by the weight of the additional hoist rope (for double rope operation = 2.5 kg per metre hook travel).

4.3.2 Load capacity table WOLFF 6031.12 clear (8.3 t)

8.3 t	Radius [m]	25	30	32.5	35	37.5	40	42.5	45	47.5	50	52.5	55	57.5	60	62.5	65	
Jib length [m]	65	2.75- 21.4	7.0	5.6	5.1	4.7	4.3	3.9	3.6	3.4	3.1	2.9	2.7	2.6	2.4	2.3	2.1	2.0
	62.5	2.75- 23.3	7.7	6.2	5.6	5.2	4.7	4.4	4.0	3.8	3.5	3.3	3.1	2.9	2.7	2.5	2.4	
	60	2.75- 24.9	8.3	6.7	6.1	5.6	5.1	4.8	4.4	4.1	3.8	3.6	3.4	3.2	3.0	2.8		
	57.5	2.75- 25.7	8.3	7.0	6.3	5.8	5.3	4.9	4.6	4.3	4.0	3.7	3.5	3.3	3.1			
	55	2.75- 26.3	8.3	7.2	6.5	6.0	5.5	5.1	4.7	4.4	4.1	3.9	3.6	3.4				
	52.5	2.75- 26.8	8.3	7.3	6.7	6.1	5.6	5.2	4.8	4.5	4.2	3.9	3.7					
	50	2.75- 27.7	8.3	7.6	6.9	6.3	5.8	5.4	5.0	4.7	4.4	4.1						
	47.5	2.75- 28.3	8.3	7.8	7.1	6.5	6.0	5.6	5.2	4.8	4.5							
	45	2.75- 28.7	8.3	7.9	7.2	6.6	6.1	5.7	5.3	4.9								
	42.5	2.75- 29.4	8.3	8.1	7.4	6.8	6.3	5.8	5.4									
	40	2.75- 29.8	8.3	8.2	7.5	6.9	6.4	5.9										
	37.5	2.75- 29.9	8.3	8.3	7.6	6.9	6.4											
	35	2.75- 30.2	8.3	8.3	7.6	7.0												
	32.5	2.75- 30.1	8.3	8.3	7.6													
	30	2.75- 30.0	8.3	8.3														

Tab. 4.4: Load capacity table WOLFF 6031.12 clear (8.3 t)

The load capacity figures relate to 42.0 m hook travel. At larger hook travels, the permissible load capacity is reduced by the weight of the additional hoist rope (for double rope operation = 2.5 kg per metre hook travel).

4.3.3 Load capacity table WOLFF 6031.12 clear (12 t)

 12 t	Radius [m]	20	25	30	32.5	35	37.5	40	42.5	45	47.5	50	52.5	55	57.5	60	62.5	65	
65	2.75- 15.3	8.9	6.9	5.5	5.0	4.6	4.2	3.8	3.5	3.3	3.0	2.8	2.6	2.5	2.3	2.2	2.0	1.9	
62.5	2.75- 16.6	9.7	7.6	6.1	5.5	5.1	4.6	4.3	3.9	3.7	3.4	3.2	3.0	2.8	2.6	2.4	2.3		
60	2.75- 17.7	10.5	8.2	6.6	6.0	5.5	5.0	4.7	4.3	4.0	3.7	3.5	3.3	3.1	2.9	2.7			
57.5	2.75- 18.3	10.9	8.5	6.9	6.2	5.7	5.2	4.8	4.5	4.2	3.9	3.6	3.4	3.2	3.0				
55	2.75 - 18.8	11.2	8.7	7.1	6.4	5.9	5.4	5.0	4.6	4.3	4.0	3.8	3.5	3.3					
52.5	2.75- 19.1	11.4	8.9	7.2	6.6	6.0	5.5	5.1	4.7	4.4	4.1	3.8	3.6						
50	2.75- 19.7	11.8	9.2	7.5	6.8	6.2	5.7	5.3	4.9	4.6	4.3	4.0							
47.5	2.75- 20.2	12.0	9.4	7.7	7.0	6.4	5.9	5.5	5.1	4.7	4.4								
45	2.75- 20.5	12.0	9.6	7.8	7.1	6.5	6.0	5.6	5.2	4.8									
42.5	2.75- 20.9	12.0	9.9	8.0	7.3	6.7	6.2	5.7	5.3										
40	2.75- 21.2	12.0	10.0	8.1	7.4	6.8	6.3	5.8											
37.5	2.75- 21.3	12.0	10.1	8.2	7.5	6.8	6.3												
35	2.75- 21.5	12.0	10.1	8.3	7.5	6.9													
32.5	2.75- 21.4	12.0	10.1	8.2	7.5														
30	2.75- 21.4	12.0	10.1	8.2															

Tab. 4.5: Load capacity table WOLFF 6031.12 clear (12 t)

The load capacity figures relate to 42.0 m hook travel. At larger hook travels, the permissible load capacity is reduced by the weight of the additional hoist rope (for double rope operation = 2.5 kg per metre hook travel).

4.3.4 Arrangement of counterweights on the use of the hoist winch (Hw 845 FU, Hw 875 FU)
















l = 65 m	l = 62.5 m	l = 60 m	l = 57.5 m	l = 55 m
9 x 2.7 t  g = 28.0 t	9 x 2.7 t  g = 28.0 t	8 x 2.7 t  g = 25.3 t	8 x 2.7 t  g = 25.3 t	8 x 2.7 t  g = 25.3 t
l = 52.5 m	l = 50 m	l = 47.5 m	l = 45 m	l = 42.5 m
8 x 2.7 t  g = 25.3 t	7 x 2.7 t  g = 22.6 t	7 x 2.7 t  g = 22.6 t	7 x 2.7 t  g = 22.6 t	6 x 2.7 t  g = 19.9 t
l = 40 m	l = 37.5 m	l = 35 m	l = 32.5 m	l = 30 m
6 x 2.7 t  g = 19.9 t	5 x 2.7 t  g = 17.2 t	5 x 2.7 t  g = 17.2 t	5 x 2.7 t  g = 17.2 t	4 x 2.7 t  g = 14.5 t

Fig. 4.3: Arrangement of counterweights on the use of the hoist winch (Hw 845 FU, Hw 875 FU)

- [l] Jib length [m]
 [a] To the tower
 [g] Total weight [t]
 Counterweight
 No counterweight

4.3.5 Load capacity table [kg] by the metre (8.5 t, 2-fall) (WOLFF 6031.8 *clear*)

[illegible]

Tab. 4.6: Load capacity table (8.5t, 2-fall) (WOLFF 6031.8 clear)

4.3.6 Load capacity table [kg] by the metre (12 t, 2-fall) (WOLFF 6031.12 *clear*)

Radius	Jib length [m]															
[m]	30	32.5	35	37.5	40	42.5	45	47.5	50	52.5	55	57.5	60	62.5	65	
22	8300	8300	8300	8300	8300	8300	8300	8300	8300	8300	8300	8300	8300	8300	8060	
23	8300	8300	8300	8300	8300	8300	8300	8300	8300	8300	8300	8300	8300	8300	7660	
24	8300	8300	8300	8300	8300	8300	8300	8300	8300	8300	8300	8300	8300	8300	7300	
25	8300	8300	8300	8300	8300	8300	8300	8300	8300	8300	8300	8300	8260	7650	6960	
26	8300	8300	8300	8300	8300	8300	8300	8300	8300	8300	8300	8190	7900	7310	6650	
27	8300	8300	8300	8300	8300	8300	8300	8300	8300	8230	8070	7840	7570	7000	6360	
28	8300	8300	8300	8300	8300	8300	8300	8300	8190	7900	7740	7530	7260	6710	6100	
29	8300	8300	8300	8300	8300	8300	8210	8070	7870	7590	7430	7230	6970	6440	5850	
30	8300	8300	8300	8300	8280	8230	8110	7900	7770	7570	7300	7150	6950	6700	6190 5620	
31		8020	8050	7970	7930	7810	7610	7480	7290	7030	6880	6690	6450	5960	5400	
32		7740	7760	7690	7650	7530	7340	7210	7030	6780	6630	6450	6210	5740	5200	
32.5			7600	7620	7550	7520	7400	7210	7080	6900	6650	6520	6330	6100	5630 5100	
33				7490	7420	7380	7270	7080	6960	6780	6540	6400	6220	5990	5530 5010	
34				7240	7170	7140	7030	6840	6720	6550	6310	6180	6000	5780	5330 4830	
35				7000	6940	6900	6790	6610	6500	6330	6100	5970	5800	5590	5150 4660	
36					6710	6680	6570	6400	6290	6120	5900	5780	5610	5400	4980 4500	
37					6500	6470	6370	6200	6090	5930	5710	5590	5430	5220	4810 4350	
37.5					6400	6370	6270	6100	5990	5830	5620	5500	5340	5140	4730 4270	
38						6270	6170	6010	5900	5740	5530	5410	5260	5060	4660 4200	
39						6080	5980	5820	5720	5570	5360	5250	5090	4900	4510 4070	
40						5900	5810	5650	5550	5400	5200	5090	4940	4750	4370 3940	
41							5640	5490	5390	5240	5050	4940	4790	4610	4240 3810	
42							5480	5330	5230	5090	4900	4790	4650	4470	4110 3700	
42.5							5400	5250	5160	5020	4830	4720	4580	4410	4050 3640	
43								5180	5090	4950	4760	4660	4520	4340	3990 3590	
44								5040	4950	4810	4630	4530	4390	4220	3870 3480	
45								4900	4810	4680	4500	4400	4270	4100	3760 3380	
46									4680	4550	4380	4280	4150	3990	3660 3280	
47									4560	4430	4260	4170	4040	3880	3550 3190	
47.5									4500							

Tab. 4.7: Load capacity table (12t, 2-fall) (WOLFF 6031.12 clear)

4.3.7 Load capacity table [kg] by the metre (12 t, 4-fall) (WOLFF 6031.12 clear)


Radius	Jib length [m]																
[m]	30	32.5	35	37.5	40	42.5	45	47.5	50	52.5	55	57.5	60	62.5	65		
15	12000	12000	12000	12000	12000	12000	12000	12000	12000	12000	12000	12000	12000	12000	12000		
16	12000	12000	12000	12000	12000	12000	12000	12000	12000	12000	12000	12000	12000	12000	12000		
17	12000	12000	12000	12000	12000	12000	12000	12000	12000	12000	12000	12000	12000	12000	11670		10650
18	12000	12000	12000	12000	12000	12000	12000	12000	12000	12000	12000	12000	12000	11800	10950		9990
19	12000	12000	12000	12000	12000	12000	12000	12000	12000	12000	12000	11830	11510	11120	10310		9410
20	12000	12000	12000	12000	12000	12000	12000	11800	11400	11180	10880	10500	9740	8880			
21	12000	12000	12000	12000	11950	11660	11470	11180	10800	10590	10300	9940	9220	8400			
22	11620	11650	11690	11580	11530	11360	11070	10890	10620	10250	10050	9780	9440	8740	7960		
23	11060	11090	11130	11030	10970	10810	10540	10370	10100	9760	9560	9300	8970	8310	7560		
24	10550	10580	10610	10520	10470	10310	10050	9880	9630	9300	9110	8860	8550	7910	7200		
25	10080	10110	10140	10050	10000	9850	9600	9440	9200	8880	8700	8460	8160	7550	6860		
26	9650	9680	9700	9620	9570	9430	9180	9030	8800	8490	8320	8090	7800	7210	6550		
27	9240	9270	9300	9220	9170	9030	8800	8650	8430	8130	7970	7740	7470	6900	6260		
28	8870	8900	8930	8840	8800	8670	8440	8300	8090	7800	7640	7430	7160	6610	6000		
29	8520	8550	8580	8500	8460	8330	8110	7970	7770	7490	7330	7130	6870	6340	5750		
30	8200	8230	8250	8180	8130	8010	7800	7670	7470	7200	7050	6850	6600	6090	5520		
31		7920	7950	7870	7830	7710	7510	7380	7190	6930	6780	6590	6350	5860	5300		
32		7640	7660	7590	7550	7430	7240	7110	6930	6680	6530	6350	6110	5640	5100		
32.5		7500	7520	7450	7420	7300	7110	6980	6800	6550	6420	6230	6000	5530	5000		
33			7390	7320	7280	7170	6980	6860	6680	6440	6300	6120	5890	5430	4910		
34			7140	7070	7040	6930	6740	6620	6450	6210	6080	5900	5680	5230	4730		
35			6900	6840	6800	6690	6510	6400	6230	6000	5870	5700	5490	5050	4560		
36				6610	6580	6470	6300	6190	6020	5800	5680	5510	5300	4880	4400		
37				6400	6370	6270	6100	5990	5830	5610	5490	5330	5120	4710	4250		
37.5				6300	6270	6170	6000	5890	5730	5520	5400	5240	5040	4630	4170		
38					6170	6070	5910	5800	5640	5430	5310	5160	4960	4560	4100		
39					5980	5880	5720	5620	5470	5260	5150	4990	4800	4410	3970		
40					5800	5710	5550	5450	5300	5100	4990	4840	4650	4270	3840		
41						5540	5390	5290	5140	4950	4840	4690	4510	4140	3710		
42						5380	5230	5130	4990	4800	4690	4550	4370	4010	3600		
42.5						5300	5150	5060	4920	4730	4620	4480	4310	3950	3540		
43							5080	4990	4850	4660	4560	4420	4240	3890	3490		
44							4940	4850	4710	4530	4430	4290	4120	3770	3380		
45							4800	4710	4580	4400	4300	4170	4000	3660	3280		
46								4580	4450	4280	4180	4050	3890	3560	3180		
47								4460	4330	4160	4070	3940	3780	3450	3090		
47.5								4400	4270	4110	4010	3880	3730	3410	3040		
48									4220	4050	3960	3830	3680	3360	3000		
49									4110	3940	3850	3730	3580	3260	2910		
50									4000	3840	3750	3630	3480	3180	2830		
51										3740	3650	3540	3390	3090	2750		
52										3650	3560	3440	3300	3010	2680		
52.5										3600	3510	3400	3260	2970	2640		
53											3470	3360	3220	2930	2600		
54											3380	3270	3130	2850	2530		
55											3300	3190	3050	2780	2460		
56												3110	2980	2710	2400		
57												3040	2910	2640	2340		
57.5												3000	2870	2600	2300		
58													2830	2570	2270		
59													2770	2510	2220		
60														2700	2450	2160	
61															2390	2100	

Radius	Jib length [m]																
[m]	30	32.5	35	37.5	40	42.5	45	47.5	50	52.5	55	57.5	60	62.5	65		
62																2330	2050
62.5																2300	2020
63																	2000
64																	1950
65																	1900

Tab. 4.8: Load capacity table (12t, 4-fall) (WOLFF 6031.12 clear)


4.4 Operating speeds

4.4.1 Operating speeds WOLFF 6031.8 clear, Hw 845 FU (400 V, 50 Hz)








Tab. 4.9: Operating speeds WOLFF 6031.8 clear, Hw 845 FU (400 V, 50 Hz)

4.4.2 Operating speeds WOLFF 6031.8 clear, Hw 875 FU (400 V, 50 Hz)








Tab. 4.10: Operating speeds WOLFF 6031.8 clear, Hw 875 FU (400 V, 50 Hz)

4.4.3 Operating speeds WOLFF 6031.12 clear , Hw 845 FU (400 V, 50 Hz)

Drive [type]	Operating speeds Load	Hook travel max. [m]	Power rating [kW]	Total load [kVA]
Hw 845 FU	Hoisting 	190	45	67.0 Total load with simultaneity factor 0.8
	 (referred to the 4th rope layer on the drum)			
	Hoisting 	95		
				
KW	Travelling trolley		7,5	95.0 Total load with simultaneity factor 0.8
				
DW	Slewing		2 x 6.0	
				

Tab. 4.11: Operating speeds WOLFF 6031.12 clear , Hw 845 FU (400 V, 50 Hz)

4.4.4 Operating speeds WOLFF 6031.12 clear , Hw 875 FU (400 V, 50 Hz)

Drive [type]	Operating speeds Load	Hook travel max. [m]	Power rating [kW]	Total load [kVA]
Hw 875 FU	Hoisting 	460	75	95.0 Total load with simultaneity factor 0.8
	 (referred to the 4th rope layer on the drum)			
	Hoisting 	230		
				
KW	Travelling trolley		7,5	95.0 Total load with simultaneity factor 0.8
				
DW	Slewing		2 x 6.0	
				


Tab. 4.12: Operating speeds WOLFF 6031.12 clear , Hw 845 FU (400 V, 50 Hz)

4.5 Tower combinations

NOTE The tower combinations shown here represent recommendations for low cost crane erection.
Tower combinations with other tower elements are possible, however they must be checked by the manufacturer and approved in writing prior to the erection of the tower crane.

4.5.1 Tower combinations – on foundation


Tower combinations for a free-standing tower crane without climbing frame on a concrete foundation.

Element						
1	UV 20	UV 20	UV 20	UV 20	UV 20	
2	UV 20	UV 20	UV 20	UV 20	UV 20	
3	UV 20	UV 20	UV 20	UV 20	UV 20	
4	UV 20	UV 20	UV 20	UV 20	UV 20	
5	UV 20	UV 20	UV 20	UV 20	UV 20	
6	UV 20	UV 20	UV 20	UV 20	UV 20	
7	UV 20	UV 20	UV 20	UV 20	UV 20	
8	UV 20	UV 20	UV 20	UV 20	UV 20	
9	UV 20	UV 20	UV 20	UV 20	UV 20	
10	UV 20	UV 20	UV 20	TVA 20	TVA 20	
11	UV 20	TVA 20	TVA 20	TV 20	TV 20	
12		TV 20	TV 20	TV 20	TV 20	
13		TV 20	TV 20	TV 20	TV 20	
14		TV 20	TV 20	TV 20	TVÜ 20	
15		TV 20	TVÜ 25	TVÜ 20	TV 25	
16			TV 25	TV 25	UVA 25	
17			TV 25	UVA 25	VR 2529	
18				UV 25	UV 29	
19					UV 29	
20					UV 29	
21					UV 29	
22					BT 29	
Foundation	FuA	FuA	FuA	FuA	FuA	
Tower height [m]	49.5	67.5	76.5	81	101.2	
Hook height (4-fall) [m]	50.6	68.6	77.6	82.1	102.3	

Tab. 4.13: Tower combinations – on foundation WOLFF 6031.12 clear / WOLFF 6031.8 clear

4.5.2 Tower combinations – on cross frame


Tower combinations for a free-standing, stationary tower crane without climbing frame on a frame, cross frame.

Element						
1	UV 20	UV 20	UV 20	UV 20	UV 20	UV 20
2	UV 20	UV 20	UV 20	UV 20	UV 20	UV 20
3	UV 20	UV 20	UV 20	UV 20	UV 20	UV 20
4	UV 20	UV 20	UV 20	UV 20	UV 20	UV 20
5	UV 20	UV 20	UV 20	UV 20	UV 20	UV 20
6	UV 20	UV 20	UV 20	UV 20	UV 20	UV 20
7	UV 20	UV 20	UV 20	UV 20	UV 20	UV 20
8		UV 20	UV 20	UV 20	UV 20	UV 20
9		UV 20	UV 20	UV 20	UV 20	UV 20
10		UV 20	UV 20	UV 20	TVA 20	TVA 20
11		TVA 20	TVA 20	TVA 20	TV 20	TV 20
12		TV 20	TV 20	TV 20	TV 20	TV 20
13		TV 20	TV 20	TV 20	TV 20	TV 20
14				TV 20	TVÜ 20	TVÜ 20
15				TVÜ 20	TV 25	TV 25
16					UVA 25	UVA 25
17					VR 2529	VR 2529
18					UV 29	UV 29
19					UV 29	UV 29
20					UV 29	UV 29
21					BT 29	BT 29
22						
Base	KRV 7-32 / 46	KR 10-46	KR 10-46 / 60	KR 1000-8	KR 16-80	KR 16- 80 /100
[m x m]	4.6 x 4.6	4.6 x 4.6	6.0 x 6.0	8 x 8	8 x 8	10 x 10
Tower height [m]	32.4	59.7	59.7	68.7	98.5	98.5
Hook height (4-fall) [m]	33.5	60.8	60.8	69.8	99.6	99.6

Tab. 4.14: Tower combinations – on cross frame WOLFF 6031.12 clear / WOLFF 6031.8 clear

4.5.3 Tower combinations – on cross frame element


Tower combinations for a free-standing, stationary tower crane without climbing frame on a cross frame element.

Element					
1	UV 20	UV 20	UV 20	UV 20	UV 20
2	UV 20	UV 20	UV 20	UV 20	UV 20
3	UV 20	UV 20	UV 20	UV 20	UV 20
4	UV 20	UV 20	UV 20	UV 20	UV 20
5	UV 20	UV 20	UV 20	UV 20	UV 20
6	UV 20	UV 20	UV 20	UV 20	UV 20
7	UV 20	UV 20	UV 20	UV 20	UV 20
8		UV 20	UV 20	UV 20	UV 20
9			UV 20	UV 20	UV 20
10			UV 20	UV 20	UV 20
11			TVA 20	TVA 20	TVA 20
12				TV 20	TV 20
13					TV 20
14					TVÜ 20
15					UVA 25
16					
17					
18					
19					
20					
21					
22					
Base	KRE260.1	KRE260.1	KRE260.2	KRE260.2	KRE480
[m x m]	5 x 6.79	6 x 6	5 x 6.79	6 x 6	8 x 8
Tower height [m]	35.5	40.0	53.5	58.0	71.5
Hook height (4-fall) [m]	36.6	41.1	54.6	59.1	72.6

Tab. 4.15: Tower combinations – on cross frame element WOLFF 6031.12 clear / WOLFF 6031.8 clear

4.5.4 Tower combinations – on undercarriage

Tower combinations for a free-standing, stationary tower crane without climbing frame on an undercarriage.







Element							
1	UV 20	UV 20	UV 20	UV 20	UV 20	UV 20	UV 20
2	UV 20	UV 20	UV 20	UV 20	UV 20	UV 20	UV 20
3	UV 20	UV 20	UV 20	UV 20	UV 20	UV 20	UV 20
4	UV 20	UV 20	UV 20	UV 20	UV 20	UV 20	UV 20
5	UV 20	UV 20	UV 20	UV 20	UV 20	UV 20	UV 20
6	UV 20	UV 20	UV 20	UV 20	UV 20	UV 20	UV 20
7		UV 20	UV 20	UV 20	UV 20	UV 20	UV 20
8			TVA 20	UV 20	UV 20	UV 20	UV 20
9				TVA 20	UV 20	UV 20	UV 20
10					UV 20	UV 20	UV 20
11					TVA 20	TVA 20	TVA 20
12						TV 20	TV 20
13							TV 20
14							TVÜ 20
15							UVA 25
16							
17							
18							
19							
20							
21							
22							
Base	UW260.1	UW260.1	UW260.2	UW260.2	UW260.3	UW260.3	UW480
[m x m]	5 x 6.79	6 x 6	5 x 6.79	6 x 6	5 x 6.79	6 x 6	8 x 8
Tower height [m]	31.5	36.0	40.5	45.0	54.0	58.5	72.5
Hook height (4-fall) [m]	32.6	37.1	41.6	46.1	55.1	59.6	73.6

Tab. 4.16: Tower combinations – on undercarriage
WOLFF 6031.12 clear / WOLFF 6031.8 clear

5 Package list WOLFF 6031 clear

NOTE! Loose items and small parts may be distributed depending on space available.

5.1 Package list, general, WOLFF 6031 clear

Item	Qty.	Description	Package	L (m)	W (m)	H (m)	Weight (kg)	Volume (m³)
1	1	Tower head section compl. with slewing frame, ball bearing slewing rim, slewing gear and slip ring system		6.67	2.30	2.54	9370	38.97
Item 1 dismantled		Upper part of tower head section with stay parts		2.33	0.58	2.81	1300	3.80
		Lower part of tower head section with slewing frame, slewing rim, slewing gear and slip ring system		5.77	2.30	2.54	8070	33.71
2	1	Cab with cab mounting		4.46	1.96	2.55	2390	22.29
3	1	Counterjib with stay parts and railings		14.04	2.30	0.80	6840	25.84
		Counterjib without ballast carrier and without loose parts		11.87	2.30	0.70	5280	19.11
4	1	Hoist winch platform Hw 845 FU		2.17	1.57	1.04	2035	3.54
5	1	Hoist winch platform Hw 875 FU		2.17	1.88	1.18	2375	4.82
6	1	Crate (small items)		0.63	0.5	0.38	100	1.12

Tab. 5.1: Package list, general, 6031 clear

5.2 Package list, special, WOLFF 6031.8 clear

Item	Qty.	Description	Package	L (m)	W (m)	H (m)	Weight (kg)	Volume (m³)
7	1	Jib section 1 with trolley running gear		10.34	1.20	2.38	3265	29.53
8	1	Jib section 2		10.32	1.20	2.36	2150	29.23
9	1	Jib section 3		10.29	1.20	2.34	1600	28.90
10	1	Jib section 4		5.27	1.20	1.74	775	11.00
11	1	Jib section 5		2.77	1.20	1.74	470	5.78
12		Jib section 6		10.25	1.20	1.72	1365	21.16
13		Jib section 7		10.07	1.20	1.70	1045	20.75
14		Jib section 8		10.17	1.20	1.70	800	20.75
15		Rope swivel crossbeam		0.99	1.09	0.45	126	0.49
16		Trolley LK 8		1.87	1.36	0.95	290	2.42
17		Maintenance cage for LK 8		0.75	0.55	1.69	55	0.70
18		Bottom block U 6 (8)		0.50	0.22	1.11	350	0.12

Tab. 5.2: Package list, special, WOLFF 6031.8 clear

5.3 Package list, special, WOLFF 6031.12 clear

Item	Qty.	Description	Package	L (m)	W (m)	H (m)	Weight (kg)	Volume (m³)
7	1	Jib section 1 with trolley running gear		10.34	1.20	2.38	3265	29.53
8	1	Jib section 2		10.32	1.20	2.36	2150	29.23
9	1	Jib section 3		10.29	1.20	2.34	1600	28.90
10	1	Jib section 4		5.27	1.20	1.74	775	11.00
11	1	Jib section 5		2.77	1.20	1.74	470	5.78
12		Jib section 6		10.25	1.20	1.72	1365	21.16
13		Jib section 7		10.07	1.20	1.70	1045	20.75
14		Jib section 8		10.17	1.20	1.70	800	20.75
15		Rope swivel crossbeam		0.99	1.09	0.45	126	0.49
16		Trolley LK 8 / 12		1.87	1.38	1.03	355	2.66
17		Maintenance cage for LK 8 / 12		0.75	0.55	1.69	55	0.70
18		Bottom block U 8 / 16 AU		1.02	0.27	1.84	550	0.51

Tab. 5.3: Package list, special, WOLFF 6031.12 clear

7 Installation weights

7.1 Counterweights

7.1.1 Counterweight block 2.7 t




Fig. 7.1: Counterweight block 2.7 t

[1] Connection for spigot
($\varnothing 40 / 78 \times 215$
962-4-006490)

[2] Steel reinforcing

[3] Part marking

Data, counterweight block 2.7 t

Item	Data
Material	Concrete made of min. B 25 Density = $2.4 \text{ t} / \text{m}^3$
Max. permissible weight variation	$\pm 2 \%$
Order number	962-2-005966

Tab. 7.1: Data, counterweight block 2.7 t

7.1.2 Counterweight block 3.7 t (under the machine platform)




Fig. 7.2: Counterweight block 3.7 t

[1] Corner protection

[3] Part marking

Data, counterweight block 3.7 t

Item	Data
Material	Concrete made of min. B 25 Density = $2.3 \text{ t} / \text{m}^3$
Max. permissible weight variation	$\pm 2 \%$
Order number	962-2-029759

Tab. 7.2: Data, counterweight block 3.7 t

7.2 Installation weights and heights

7.2.1 Installation weights - slewing section

Assembly	Crane components	Weight [kg]	
Tower head section complete with stay lugs and railings			9370
	- Upper part of tower head section with stay lugs	1300	
	- Lower part of tower head section with slewing frame, slewing rim, slewing gear, railings and slip ring system	8070	
Cab platform complete			2390
	- Cab with switch cabinet, resistor and cab platform		
Counterjib with Hw 845 FU complete			12575
	- Counterjib with stay lugs, railings and ballast frame	6840	
	- Hoist winch platform Hw 845 FU	2035	
	- Concrete counterweight block 3.7 t (under the hoist winch platform)	3700	
Counterjib with Hw 875 FU complete			12915
	- Counterjib with stay lugs, railings and ballast frame	6840	
	- Hoist winch platform Hw 875 FU	2375	
	- Concrete counterweight block 3.7 t (under the hoist winch platform)	3700	

Tab. 7.3: Installation weights, slewing section

7.2.2 Installation weights - trolley jib complete

Trolley jib complete: trolley, trolley ropes, bottom block, railings and rope swivel crossbeam

Jib length [m]	Weight [kg]	
	WOLFF 6031.8 <i>clear</i>	WOLFF 6031.12 <i>clear</i>
65	11800	12100
62.5	11500	11800
60	11000	11300
57.5	10900	11200
55	11000	11300
52.5	10700	11000
50	10200	10500
47.5	10100	10400
45	10000	10300
42.5	9700	10000
40	9200	9500
37.5	9100	9400
35	8600	8900
32.5	8300	8600
30	7800	8100

Tab. 7.4: Installation weights - trolley jib complete

7.2.3 Installation weights - cross frame

Assembly	Crane components	Weight [kg]	
Cross frame KR 6 – 40 (without accessories)			3 450
(4.0 m x 4.0 m)	- 4 bolted spigots AZ 93.4	200	
	- 4 bolted spigots AZ 93.4 E 15	240	
Cross frame KR 7 – 32 (without accessories)			3 350
(3.2 m x 3.2 m)	- 4 bolted spigots AZ 85 E 20.5	210	
	- 4 bolted spigots AZ 93.4 E 15	240	
	- 4 bolted spigots AZ 120 M	292	
Cross frame KRV 7 – 32 (without accessories)			3 680
(3.2 m x 3.2 m)	- 4 bolted spigots AZ 85 E 20.5	210	
	- 4 bolted spigots AZ 93.4 E 15	240	
	- 4 bolted spigots AZ 120 M	292	
Cross frame KRV 7 – 32 / 46 (without accessories)			5 090
(4.6 m x 4.6 m)	- 4 bolted spigots AZ 85 E 20.5	210	
	- 4 bolted spigots AZ 93.4 E 15	240	
	- 4 bolted spigots AZ 120 M	292	
Cross frame KR 8 – 46 (without accessories)			5 250
(4.6 m x 4.6 m)	- 4 bolted spigots AZ 85 E 20.5	210	
	- 4 bolted spigots AZ 93.4 E 15	240	
	- 4 bolted spigots AZ 120 M	292	
Cross frame KR 10 – 46 (without accessories)			7 020
(4.6 m x 4.6 m)	- 4 bolted spigots AZR 120 E 15.5	552	
	- 4 bolted spigots AZ 140 M	698	
Cross frame KR 10 – 46 / 60 (without accessories)			8 875
(6.0 m x 6.0 m)	- 4 bolted spigots AZR 120 E 15.5	552	
	- 4 bolted spigots AZ 140 M	698	
Cross frame KR HEB 700 – 4 (without accessories)			4 450
(4.0 m x 4.0 m)	- 4 bolted spigots AZ 93.4	240	
Cross frame KR HEB 700 – 5 (without accessories)			5 410
(5.0 m x 5.0 m)	- 4 bolted spigots AZ 93.4	240	
Cross frame KR HEB 800 – 5 (without accessories)			5 860
(5.0 m x 5.0 m)	- 4 bolted spigots AZ 120 M	292	
Cross frame KR HEB 800 – 6 (without accessories)			6 600
(6.0 m x 6.0 m)	- 4 bolted spigots AZ 120 M	292	
Frame SR 150 (without accessories)			5 460
(4.0 m x 4.0 m)	- 4 bolted spigots AZ 85 E 20.5	210	
	- 4 bolted spigots AZ 93.4 E 15	240	
	- 4 bolted spigots AZ 120 M	292	

Assembly	Crane components	Weight [kg]	
Cross frame KR 1000 – 8 (without accessories)			14 630
(8 m x 8m)	- 4 bolted spigots AZ 140 E	684	
	- 4 bolted spigots AZ 156 M	748	
Cross frame KR 16 – 80 (without accessories)			21 450
(8 m x 8 m)	- 4 bolted spigots AZ 140 E KR 16-80	620	
	- 4 bolted spigots AZ 156 M KR 16-80	680	
	- 4 bolted spigots AZ 156S M KR 16-80	675	
Cross frame KR 16 – 80 / 100 (without accessories)			25 400
(10 m x 10 m)	- 4 bolted spigots AZ 140 E KR 16-80	620	
	- 4 bolted spigots AZ 156 M KR 16-80	680	
	- 4 bolted spigots AZ 156S M KR 16-80	675	

Tab. 7.5: Installation weights, cross frame

7.2.4 Installation weights - cross frame elements

Assembly	Crane components	Weight [kg]	
Cross frame element KRE 138 complete			3 800
	- Cross frame platform with crossbeams, corner bearings and transport locks	2 100	
	- Mast base with struts	1 700	
Cross frame element KRE 250 complete			5 750
	- Cross frame platform with pivoting arm, corner bearings and transport locks	2 730	
	- Mast base with struts and tie bars	3 020	
Cross frame element KRE 260.1 complete			8 100
	- Cross frame platform with pivoting arm, corner bearings and transport locks	4 320	
	- Mast base with struts and tie bars	3 780	
Cross frame element KRE 260.2 complete			10 900
	- Cross frame platform with pivoting arm, corner bearings and transport locks	5 455	
	- Mast base with struts and tie bars	5 445	
Cross frame element KRE 480 complete			24 250
	- Mast base	7 100	
	- Pivoting arms with corner bearing	6 250	
	- Struts and ballast carrier	9 260	
	- Assembly platform, ladder and small items	1 640	

Tab. 7.6: Installation weights, cross frame elements

7.2.5 Installation weights - undercarriage

Assembly	Crane components	Weight [kg]	
Undercarriage UW 138 complete			5 750
	- Undercarriage platform with crossbeams, spacers and subframes	3 970	
	- Mast base with struts	1 780	
Undercarriage UW 250 complete			8 800
	- Undercarriage platform with pivoting arms, subframes and transport locks	5 600	
	- Mast base with struts and tie bars	3 200	
Undercarriage UW 260.1 complete			11 400
	- Undercarriage platform with pivoting arms, subframes and transport locks	7 150	
	- Mast base with struts and tie bars	4 250	
Undercarriage UW 260.2 complete			13 930
	- Undercarriage platform with pivoting arms, subframes and transport locks	7 150	
	- Mast base with struts and tie bars	4 250	
Undercarriage UW 260.3 complete			17 200
	- Undercarriage platform with pivoting arms, subframes and transport locks	11 300	
	- Mast base with struts and tie bars	5 900	
Undercarriage UW 480 complete			34 000
	- Mast base	7 100	
	- Pivoting arms with crossbeam and subframes	16 000	
	- Struts and ballast carrier	9 260	
	- Assembly platform, ladder and small items	1 640	

Tab. 7.7: Installation weights, undercarriage

7.2.6 Hook height necessary for mobile crane

Danger!

Use ropes with adequate load capacity and pay attention to lifting diagram!

Hook height necessary for mobile crane = hook height of the WOLFF tower crane + 11 m.

Please refer to the tower combinations for the hook height of the WOLFF tower crane.

Height differences (mobile crane - tower crane base) are to be taken into account during assembly.




Fig. 7.3: Hook height necessary for the mobile crane

- | | |
|--|--|
| [1] Undercarriage | [6] Four-leg sling (4 m with shackles) |
| [2] Tower element | [7] Trolley jib complete |
| [3] Counterjib complete | [8] Tower head section complete |
| [4] Four-leg sling (4 m with shackles) | [X] Hook height for the mobile crane |
| [5] Single sling (1 m with shackles) | |

9 Suitable climbing frames

DANGER!

The climbing frame is an assembly aid and is not allowed to be left on the WOLFF tower crane under normal operating conditions.

9.1 Exterior climbing frame (KWH)
9.1.1 KWH 20.3

Minimum height for stationary erection:

3 tower elements = 13.5 m tower height

Minimum height for mobile erection:

2 tower elements + undercarriage approx. 13.5 m tower height


DANGER!

The radius stated refers to the middle of the tower and is a general figure. Exact counterbalancing is obtained by moving the trolley with the tower element given in the table or a load and can be checked by moving to the tower's end stops without offset.

Counterbalancing weights WOLFF 6031.8 clear

6031.8	Jib length [m]													
	65	62.5	60	57.5	55	52.5	50	47.5	45	42.5	40	37.5	35	32.5
No Weight	32.6	-	-	-	-	-	-	-	-	-	-	-	-	-
UV 20 = 1.95 t *	8.3	15.1	14.7	18.5	17.2	22.8	21.7	24.0	26.6	24.0	28.6	24.8	26.9	-
TV 20 = 3.05 t	-	10.2	9.9	12.8	11.8	16.1	15.3	17.0	19.0	17.0	20.5	17.6	19.2	21.2

Tab. 9.1: Counterbalancing weights KWH20.3 (WOLFF 6031.8 clear)

Counterbalancing weights WOLFF 6031.12 clear

6031.12	Jib length [m]													
	65	62.5	60	57.5	55	52.5	50	47.5	45	42.5	40	37.5	35	32.5
No Weight	21.3	37.5	36.6	45.5	42.5	-	-	-	-	-	-	-	-	-
UV 20 = 1.95 t *	7.1	13.1	12.8	16.1	14.9	19.9	18.9	20.9	23.2	20.9	25.0	21.6	23.4	26.9
TV 20 = 3.05 t	-	9.1	8.9	11.4	10.6	14.4	13.7	15.2	17.0	15.2	18.4	15.8	17.2	20.0

Tab. 9.2: Counterbalancing weights KWH20.3 (WOLFF 6031.12 clear)

9.1.2 KWH 20.6

Minimum height for stationary erection:
2 tower elements = 9.0 m tower height
 Minimum height for mobile erection:
2 tower elements + undercarriage approx. 13.5 m tower height


DANGER!

The radius stated refers to the middle of the tower and is a general figure. Exact counterbalancing is obtained by moving the trolley with the tower element given in the table or a load and can be checked by moving to the tower's end stops without offset.

Counterbalancing weights WOLFF 6031.8 clear

	Jib length [m]														
6031.8	65	62.5	60	57.5	55	52.5	50	47.5	45	42.5	40	37.5	35	32.5	30
No Weight	29.7	-	-	-	-	-	-	-	-	-	-	-	-	-	-
UV 20 = 1.95 t *	7.5	14.3	13.9	17.7	16.4	22.0	20.9	23.2	25.8	23.2	27.8	24.0	26.1	-	-
TV 20 = 3.05 t	-	9.6	9.3	12.2	11.2	15.5	14.7	16.4	18.3	16.4	19.9	17.0	18.6	21.6	20.5

Tab. 9.3: Counterbalancing weights KWH20.6 (WOLFF 6031.8 clear)

Counterbalancing weights WOLFF 6031.12 clear

	Jib length [m]														
6031.12	65	62.5	60	57.5	55	52.5	50	47.5	45	42.5	40	37.5	35	32.5	30
No Weight	19.4	35.5	34.7	43.6	40.5	-	-	-	-	-	-	-	-	-	-
UV 20 = 1.95 t *	6.4	12.4	12.0	15.3	14.2	19.1	18.2	20.2	22.4	20.2	24.2	20.9	22.7	26.2	25.0
TV 20 = 3.05 t	-	8.6	8.3	10.9	10.0	13.9	13.1	14.7	16.5	14.7	17.9	15.2	16.7	19.4	18.5

Tab. 9.4: Counterbalancing weights KWH20.6 (WOLFF 6031.12 clear)

9.2 Interior climbing frame (KSH)
9.2.1 KSH 20 SH

Tower combination for tower crane with internal climber.

Element					
1	UV 20.4	UV 20.4	UV 20.4	UV 20.4	
2	UV 20.4	UV 20.4	UV 20.4	UV 20.4	
3	UV 20.4	UV 20.4	UV 20.4	UV 20.4	
4	UV 20.4	UV 20.4	UV 20.4	UV 20.4	
5	UV 20.4	UV 20.4	UV 20.4	UV 20.4	
6	UV 20.4	UV 20.4	UV 20.4	UV 20.4	
7	TVA 20.4	UV 20.4	UV 20.4	UV 20.4	
8		TVA 20.4	UV 20.4	UV 20.4	
9			TVA 20.4	UV 20.4	
10				TVA 20.4	
Internal climber	KSH 20 SH	KSH 20 SH	KSH 20 SH	KSH 20 SH	
Foundation	Type F / S	Type F / S	Type F / S	Type F / S	
Tower height [m]	46.5	51.0	55.5	60.0	
Hook height (4-fall) [m]	47.6	52.1	56.6	61.1	

Tab. 9.5: Tower combination with internal climber on baseplate WOLFF 6031.12 clear / WOLFF 6031.8 clear


DANGER!

The radius stated refers to the middle of the tower and is a general figure. Exact counterbalancing is achieved by moving the trolley with the tower element stated in the table or a load.
 Counterbalancing is correct if there is an even air gap between the corner clamps on the climbing frame and the corner posts.

Counterbalancing weights WOLFF 6031.8 clear

	Jib length [m]														
6031.8	65	62.5	60	57.5	55	52.5	50	47.5	45	42.5	40	37.5	35	32.5	30
UV 20 = 1.95 t *	39.3	46.0	44.3	48.0	46.7	-	-	-	-	-	-	-	-	-	-
TV 20 = 3.05 t	29.9	34.9	33.6	36.5	35.5	39.7	37.9	39.5	41.4	38.5	-	-	-	-	-
Weight = 5.00 t	19.3	22.6	21.7	23.6	23.0	25.7	24.5	25.5	26.8	24.9	27.1	24.6	25.5	27.4	26.1

Tab. 9.6: Counterbalancing weights KSH 20 SH (WOLFF 6031.8 clear)

Counterbalancing weights WOLFF 6031.12 clear

	Jib length [m]														
6031.12	65	62.5	60	57.5	55	52.5	50	47.5	45	42.5	40	37.5	35	32.5	30
UV 20 = 1.95 t *	34.5	40.3	38.8	42.1	41.0	45.8	43.7	-	-	-	-	-	-	-	-
TV 20 = 3.05 t	27.0	31.6	30.4	32.9	32.1	35.9	34.2	35.7	37.5	34.8	-	-	-	-	-
Weight = 5.00 t	18.1	21.1	20.1	22.1	21.5	24.0	22.9	23.9	25.1	23.3	25.3	23.0	23.9	25.7	24.4

Tab. 9.7: Counterbalancing weights KSH 20 SH (WOLFF 6031.12 clear)


9.2.2 Clamping forces in the building for hydraulic interior climbing frame KSH 20 SH


Fig. 1: Climbing frame KSH 20 SH

[A] = tower height
 [C] = distance between guide frames
 [B] = A - C - D
 [D] = 0.77 m

Clamping forces in the building [kN] in service

A [m]	60				55.5				51				46.5			
C [m]	11	12	13	14	11	12	13	14	11	12	13	14	11	12	13	14
V	1132				1113				1094				1075			
H _o	340	310	290	270	320	290	270	250	300	270	250	230	280	260	240	220
H _u	300	270	250	230	280	250	230	210	260	240	220	200	240	220	200	180
T	52				52				52				52			

Tab. 9.8: Clamping forces in the building [kN] in service

Clamping forces in the building [kN] out of service


A [m]	60				55.5				51				46.5			
C [m]	11	12	13	14	11	12	13	14	11	12	13	14	11	12	13	14
V	100				981				962				943			
H _o	760	700	640	600	670	610	570	530	590	540	500	460	510	470	430	400
H _u	530	470	420	370	450	400	350	310	380	330	290	260	310	270	240	210
T	0				0				0				0			

Tab. 9.9: Clamping forces in the building [kN] out of service

12 Structural data

12.1 Foundation loads in accordance with EN 13001 and FEM 1.005

Tower crane without climbing frame


Jib length: 30m to 65m


Hook height		Crane in service Slewing torque: 280 kNm			Crane out of service Wind region: C25			Assembly		
 [m]	 [m]	M [kNm]	V [kN]	H [kN]	M [kNm]	V [kN]	H [kN]	M [kNm]	V [kN]	H [kN]
5.6	6.0	1800	629	19	1410	488	28	1650	385	6
10.1	10.5	1890	647	20	1560	507	33	1680	404	7
14.6	15.0	2000	665	21	1720	525	37	1720	422	7
19.1	19.5	2120	684	23	1910	543	42	1760	440	8
23.6	24.0	2250	702	24	2130	561	47	1810	458	9
28.1	28.5	2400	720	26	2380	580	52	1870	476	10
32.6	33.0	2560	738	27	2660	598	57	1940	495	11
37.1	37.5	2740	756	29	2970	616	61	2010	513	11
41.6	42.0	2950	774	30	3320	634	66	2100	531	12
46.1	46.5	3170	792	32	3700	652	71	2190	549	13
50.6	51.0	3430	811	33	4130	670	76	2290	567	14
55.1	55.5	3620	849	36	4650	852	116	2380	605	15
59.6	60.0	3880	877	38	5450	880	126	2490	634	16
64.1	64.5	4170	906	40	6330	909	136	2610	663	17
68.6	69.0	4490	934	42	7330	937	146	2740	690	19
73.1	73.5	4750	974	44	8290	977	157	2860	730	20
77.6	78.0	5070	1006	46	9400	1009	168	3000	762	21
82.1	82.5	5350	1056	49	10590	1059	182	3120	813	23
84.3	84.7	5350	1114	51	10930	1117	192	3130	870	24
88.8	89.2	5680	1160	54	12220	1163	205	3280	917	25
93.3	93.7	6040	1206	56	13640	1209	218	3440	963	27
97.8	98.2	6420	1253	59	15170	1255	231	3610	1009	28
102.3	102.7	6840	1299	62	16840	1302	245	3790	1056	30

12.2 Central ballast and corner loads in accordance with EN 13001 and FEM 1.005

12.2.1 Jib positions

The corner loads are stated for 2 jib positions; jib position 1 produces the maximum corner load.

 For square installation the following applies: $a = b$

 For rectangular installations the following applies: $a > b$


For detailed information on the base see the related operating manual

12.2.2 Wind load out of service

The calculation of the stability in storms is based on wind region C (EN 13001-2). The reference velocity for zone C is 28 m/s (10m above the ground; averaged over 10 minutes). A recurrence interval of 25 years was used.

12.2.3 Slewing section with 30 m Jib on KRV 7-32/46 or KR 8-46

Tower crane without climbing frame

- ☒ Stationary
☐ Mobile

Size across corners: 4.6 m x 4.6 m

[illegible]

12.2.4 Slewing section with 32.5 m Jib on KRV 7-32/46 or KR 8-46

Tower crane without climbing frame

- ☒ Stationary
 - ☐ Mobile

Size across corners: 4.6 m x 4.6 m

[illegible]

12.2.5 Slewing section with 35 m Jib on KRV 7-32/46 or KR 8-46

Tower crane without climbing frame

- ☒ Stationary
 - ☐ Mobile

Size across corners: 4.6 m x 4.6 m

[illegible]

12.2.6 Slewing section with 37.5 m Jib on KRV 7-32/46 or KR 8-46

Tower crane without climbing frame

- ☒ Stationary
 - ☐ Mobile

Size across corners: 4.6 m x 4.6 m

[illegible]

12.2.7 Slewing section with 40 m Jib on KRV 7-32/46 or KR 8-46

Tower crane without climbing frame

- ☒ Stationary
☐ Mobile

Size across corners: 4.6 m x 4.6 m

[illegible]

12.2.8 Slewing section with 42.5 m Jib on KRV 7-32/46 or KR 8-46

Tower crane without climbing frame

- ☒ Stationary
☐ Mobile

Size across corners: 4.6 m x 4.6 m

[illegible]

12.2.9 Slewing section with 45 m Jib on KRV 7-32/46 or KR 8-46

Tower crane without climbing frame

- ☒ Stationary
☐ Mobile

Size across corners: 4.6 m x 4.6 m

[illegible]

12.2.10 Slewing section with 47.5 m Jib on KRV 7-32/46 or KR 8-46

Tower crane without climbing frame

- ☒ Stationary
☐ Mobile

Size across corners: 4.6 m x 4.6 m

[illegible]

12.2.11 Slewing section with 50 m Jib on KRV 7-32/46 or KR 8-46

Tower crane without climbing frame

- ☒ Stationary
 - ☐ Mobile

Size across corners: 4.6 m x 4.6 m

[illegible]

12.2.12 Slewing section with 52.5 m Jib on KRV 7-32/46 or KR 8-46

Tower crane without climbing frame

- ☒ Stationary
 - ☐ Mobile

Size across corners: 4.6 m x 4.6 m

[illegible]

12.2.13 Slewing section with 55 m Jib on KRV 7-32/46 or KR 8-46

Tower crane without climbing frame

☒ Stationary☐ Mobile

Size across corners: 4.6 m x 4.6 m

[illegible]

12.2.14 Slewing section with 57.5 m Jib on KRV 7-32/46 or KR 8-46

Tower crane without climbing frame

☒ Stationary☐ Mobile

Size across corners: 4.6 m x 4.6 m

[illegible]

12.2.15 Slewing section with 60 m Jib on KRV 7-32/46 or KR 8-46

Tower crane without climbing frame

☒ Stationary☐ Mobile

Size across corners: 4.6 m x 4.6 m

[illegible]

12.2.16 Slewing section with 62.5 m Jib on KRV 7-32/46 or KR 8-46

Tower crane without climbing frame

☒ Stationary☐ Mobile

Size across corners: 4.6 m x 4.6 m

[illegible]

12.2.17 Slewing section with 65 m Jib on KRV 7-32/46 or KR 8-46

Tower crane without climbing frame

- ☒ Stationary
☐ Mobile

Size across corners: 4.6 m x 4.6 m

[illegible]

12.2.18 Slewing section with 30 m Jib on KR 10-46

Tower crane without climbing frame

- ☒ Stationary
☐ Mobile

Size across corners: 4.6 m x 4.6 m

[illegible]

12.2.19 Slewing section with 32.5 m Jib on KR 10-46

Tower crane without climbing frame

☒ Stationary

☐ Mobile

Size across corners: 4.6 m x 4.6 m

Hook height		Central ballast	Jib position	Crane in service					Horizontal load	Crane out of service				Horizontal load
Slewing torque: 280 kNm				Wind region: C25										
Corner loads				Corner loads										
			A	B	C	D		A	B	C	D			
[m]	[m]	[t]	[kN]	[kN]	[kN]	[kN]	[kN]	[kN]	[kN]	[kN]	[kN]	[kN]		
6.8	7.2	55	1	275	537	275	14	24	212	464	212	0	41	
			2	460	460	90	90		386	386	58	58		
11.3	11.7	55	1	280	553	280	7	25	217	472	217	0	48	
			2	473	473	87	87		394	394	59	59		
15.8	16.2	55	1	283	573	283	0	27	221	483	221	0	55	
			2	488	488	141	141		402	402	60	60		
20.3	20.7	55	1	277	603	276	0	28	224	494	224	0	62	
			2	505	505	133	133		411	411	61	61		
24.8	25.2	55	1	269	637	269	0	30	227	508	226	0	69	
			2	524	524	124	124		420	420	60	60		
29.3	29.7	55	1	259	675	259	0	31	228	524	228	0	76	
			2	543	543	113	113		430	430	59	59		
33.8	34.2	55	1	247	717	247	0	33	228	542	228	0	83	
			2	565	565	100	100		441	441	58	58		
38.3	38.7	65	1	283	764	283	0	34	277	561	277	0	91	
			2	613	613	111	111		478	478	80	80		
42.8	43.2	80	1	341	815	341	0	36	374	622	374	126	98	
			2	676	676	132	132		550	550	199	199		
47.3	47.7	95	1	397	872	397	0	37	416	747	416	86	106	
			2	741	741	151	151		650	650	182	182		
51.8	52.2	115	1	501	954	501	48	39	471	894	471	48	114	
			2	821	821	180	180		770	770	172	172		
56.3	56.7	125	1	536	1018	535	52	41	491	1041	490	0	125	
			2	877	877	194	194		874	874	137	137		
60.8	61.2	145	1	593	1114	592	71	43	493	1264	493	0	134	
			2	961	961	224	224		1010	1010	115	115		

12.2.20 Slewing section with 35 m Jib on KR 10-46

Tower crane without climbing frame

☒ Stationary

☐ Mobile

Size across corners: 4.6 m x 4.6 m

Hook height		Central ballast	Jib position	Crane in service					Horizontal load	Crane out of service				Horizontal load
				Slewing torque: 280 kNm				Wind region: C25						
				Corner loads				Corner loads						
[m]	[m]	[t]		A [kN]	B [kN]	C [kN]	D [kN]	[kN]	A [kN]	B [kN]	C [kN]	D [kN]	[kN]	
6.8	7.2	60	1	319	552	319	85	24	235	467	234	2	41	
			2	484	484	153	153		399	399	70	70		
11.3	11.7	60	1	323	571	323	75	26	239	476	239	2	48	
			2	499	499	148	148		406	406	72	72		
15.8	16.2	60	1	328	592	328	63	27	244	485	244	2	55	
			2	515	515	141	141		414	414	73	73		
20.3	20.7	60	1	332	615	332	50	29	248	496	248	1	62	
			2	532	532	133	133		423	423	73	73		
24.8	25.2	60	1	337	639	337	35	30	251	509	251	0	69	
			2	550	550	123	123		433	433	73	73		
29.3	29.7	60	1	341	666	341	17	32	253	524	252	0	76	
			2	571	571	112	112		443	443	72	72		
33.8	34.2	60	1	344	697	343	0	33	253	542	253	0	84	
			2	593	593	99	99		454	454	70	70		
38.3	38.7	60	1	326	751	325	0	35	252	562	252	0	91	
			2	616	616	85	85		465	465	67	67		
42.8	43.2	75	1	380	811	379	0	36	363	636	362	88	99	
			2	679	679	105	105		556	556	169	169		
47.3	47.7	90	1	430	878	430	0	38	405	762	404	47	106	
			2	745	745	124	124		657	657	152	152		
51.8	52.2	105	1	477	953	476	0	39	443	902	442	0	114	
			2	813	813	140	140		766	766	128	128		
56.3	56.7	120	1	524	1030	524	17	42	439	1098	438	0	125	
			2	882	882	165	165		882	882	105	105		
60.8	61.2	140	1	581	1126	581	35	43	440	1323	440	0	135	
			2	966	966	195	195		1019	1019	83	83		

12.2.21 Slewing section with 37.5 m Jib on KR 10-46

Tower crane without climbing frame

☒ Stationary

☐ Mobile

Size across corners: 4.6 m x 4.6 m

Hook height		Central ballast	Jib position	Crane in service					Horizontal load	Crane out of service				Horizontal load
				Slewing torque: 280 kNm				Wind region: C25						
				Corner loads				Corner loads						
[m]	[m]	[t]		A	B	C	D		A	B	C	D		
				[kN]	[kN]	[kN]	[kN]	[kN]		[kN]	[kN]	[kN]	[kN]	[kN]
6.8	7.2	60	1	320	559	320	81	24	235	467	234	2	42	
			2	489	489	151	151		399	399	70	70		
11.3	11.7	60	1	324	578	324	71	26	239	476	239	2	48	
			2	503	503	145	145		406	406	72	72		
15.8	16.2	60	1	329	598	329	59	27	244	485	244	2	55	
			2	519	519	138	138		415	415	73	73		
20.3	20.7	60	1	333	621	333	46	29	248	496	248	0	62	
			2	537	537	130	130		423	423	73	73		
24.8	25.2	60	1	338	646	338	30	30	251	509	251	0	70	
			2	555	555	120	120		433	433	73	73		
29.3	29.7	60	1	343	672	342	13	32	252	525	252	0	77	
			2	576	576	109	109		443	443	72	72		
33.8	34.2	60	1	340	708	340	0	33	253	543	252	0	84	
			2	598	598	96	96		454	454	70	70		
38.3	38.7	60	1	322	763	322	0	35	252	563	252	0	92	
			2	622	622	82	82		474	474	169	169		
42.8	43.2	70	1	351	824	351	0	36	351	642	351	60	99	
			2	673	673	90	90		557	557	146	146		
47.3	47.7	85	1	401	891	401	0	38	393	768	393	18	107	
			2	738	738	108	108		659	659	128	128		
51.8	52.2	105	1	473	966	473	0	39	427	938	426	0	115	
			2	819	819	136	136		780	780	116	116		
56.3	56.7	115	1	512	1027	511	0	42	397	1136	397	0	125	
			2	876	876	149	149		884	884	81	81		
60.8	61.2	140	1	582	1135	582	29	44	423	1362	423	0	135	
			2	973	973	191	191		1034	1034	70	70		

12.2.22 Slewing section with 40 m Jib on KR 10-46

Tower crane without climbing frame

☒ Stationary

☐ Mobile

Size across corners: 4.6 m x 4.6 m

Hook height		Central ballast	Jib position	Crane in service					Horizontal load	Crane out of service				Horizontal load
				Slewing torque: 280 kNm				Wind region: C25						
				Corner loads				Corner loads						
				A	B	C	D	A		B	C	D		
[m]	[m]	[t]		[kN]	[kN]	[kN]	[kN]	[kN]	[kN]	[kN]	[kN]	[kN]	[kN]	
6.8	7.2	50	1	272	531	272	13	24	187	464	187	0	42	
			2	455	455	89	89		374	374	45	45		
11.3	11.7	50	1	276	547	276	6	26	192	473	192	0	49	
			2	469	469	144	144		381	381	47	47		
15.8	16.2	50	1	278	568	278	0	27	196	483	196	0	56	
			2	484	484	137	137		390	390	48	48		
20.3	20.7	50	1	272	599	272	0	29	199	495	199	0	63	
			2	502	502	129	129		398	398	48	48		
24.8	25.2	50	1	264	634	263	0	30	201	509	201	0	70	
			2	520	520	120	120		408	408	47	47		
29.3	29.7	55	1	278	672	278	0	32	227	525	227	0	77	
			2	553	553	121	121		431	431	59	59		
33.8	34.2	55	1	266	715	266	0	33	227	543	227	0	84	
			2	575	575	108	108		441	441	57	57		
38.3	38.7	60	1	276	763	276	0	35	251	563	251	0	92	
			2	611	611	106	106		470	470	188	188		
42.8	43.2	75	1	334	816	334	0	36	371	646	371	96	99	
			2	674	674	127	127		565	565	176	176		
47.3	47.7	90	1	389	875	388	0	38	413	772	413	53	107	
			2	740	740	146	146		667	667	158	158		
51.8	52.2	105	1	485	942	485	27	39	455	909	455	0	115	
			2	808	808	161	161		776	776	133	133		
56.3	56.7	120	1	532	1020	532	44	42	451	1107	450	0	126	
			2	877	877	187	187		894	894	110	110		
60.8	61.2	140	1	589	1116	589	62	44	451	1335	451	0	135	
			2	962	962	216	216		1031	1031	87	87		

12.2.23 Slewing section with 42.5 m Jib on KR 10-46

Tower crane without climbing frame

☒ Stationary

☐ Mobile

Size across corners: 4.6 m x 4.6 m

Hook height		Central ballast	Jib position	Crane in service					Horizontal load	Crane out of service				Horizontal load
Slewing torque: 280 kNm				Wind region: C25										
Corner loads				Corner loads										
		[t]		A	B	C	D		A	B	C	D		
[m]	[m]		[kN]	[kN]	[kN]	[kN]	[kN]	[kN]	[kN]	[kN]	[kN]	[kN]	[kN]	[kN]
6.8	7.2	55	1	316	544	315	87	24	212	465	212	0	42	
			2	477	477	154	154		386	386	58	58		
11.3	11.7	55	1	320	563	320	77	26	217	473	217	0	49	
			2	492	492	148	148		394	394	59	59		
15.8	16.2	55	1	325	584	325	65	27	221	484	221	0	56	
			2	508	508	141	141		402	402	60	60		
20.3	20.7	55	1	329	607	329	51	29	224	496	224	0	63	
			2	526	526	133	133		411	411	60	60		
24.8	25.2	55	1	334	632	334	36	30	226	510	226	0	70	
			2	544	544	123	123		421	421	60	60		
29.3	29.7	55	1	338	659	338	18	32	227	526	227	0	77	
			2	565	565	112	112		431	431	59	59		
33.8	34.2	60	1	355	700	355	10	33	252	544	252	0	85	
			2	599	599	111	111		454	454	69	69		
38.3	38.7	60	1	348	745	348	0	35	251	564	251	0	92	
			2	623	623	96	96		491	491	169	169		
42.8	43.2	65	1	351	806	351	0	36	347	652	347	42	100	
			2	662	662	92	92		562	562	131	131		
47.3	47.7	80	1	401	874	401	0	38	388	781	388	0	108	
			2	728	728	110	110		665	665	113	113		
51.8	52.2	100	1	472	950	472	0	39	401	973	401	0	115	
			2	810	810	137	137		788	788	99	99		
56.3	56.7	115	1	521	1027	521	14	42	395	1173	395	0	126	
			2	879	879	163	163		906	906	76	76		
60.8	61.2	140	1	590	1136	590	44	44	419	1403	419	0	136	
			2	976	976	204	204		1057	1057	64	64		

12.2.24 Slewing section with 45 m Jib on KR 10-46

Tower crane without climbing frame

☒ Stationary

☐ Mobile

Size across corners: 4.6 m x 4.6 m

Hook height		Central ballast	Jib position	Crane in service					Horizontal load	Crane out of service					Horizontal load
				Slewing torque: 280 kNm				Wind region: C25							
				Corner loads				Corner loads							
 [m]	 [m]	[t]		A [kN]	B [kN]	C [kN]	D [kN]	[kN]	A [kN]	B [kN]	C [kN]	D [kN]	[kN]		
6.8	7.2	45	1	268	525	268	11	24	162	465	162	0	42		
			2	449	449	87	87		361	361	32	32			
11.3	11.7	50	1	285	554	285	16	26	192	473	191	0	49		
			2	475	475	95	95		382	382	46	46			
15.8	16.2	50	1	290	572	290	7	27	195	484	195	0	56		
			2	490	490	90	90		390	390	47	47			
20.3	20.7	50	1	291	596	290	0	29	198	496	198	0	63		
			2	505	505	83	83		399	399	48	48			
24.8	25.2	55	1	307	631	307	0	30	226	510	225	0	71		
			2	535	535	88	88		421	421	60	60			
29.3	29.7	55	1	296	671	296	0	32	227	526	227	0	78		
			2	553	553	139	139		431	431	58	58			
33.8	34.2	60	1	309	715	309	0	33	252	544	252	0	85		
			2	587	587	138	138		454	454	69	69			
38.3	38.7	60	1	293	763	293	0	35	251	564	251	0	93		
			2	611	611	124	124		492	492	183	183			
42.8	43.2	70	1	325	818	325	0	36	367	662	367	72	100		
			2	662	662	132	132		576	576	158	158			
47.3	47.7	85	1	379	878	379	0	38	409	791	409	27	108		
			2	728	728	150	150		679	679	139	139			
51.8	52.2	105	1	455	945	455	0	39	449	957	449	0	116		
			2	809	809	178	178		802	802	125	125			
56.3	56.7	115	1	528	1005	528	51	42	418	1158	417	0	127		
			2	866	866	191	191		908	908	88	88			
60.8	61.2	135	1	585	1102	585	68	44	415	1391	415	0	136		
			2	951	951	220	220		1047	1047	63	63			

12.2.25 Slewing section with 47.5 m Jib on KR 10-46

Tower crane without climbing frame

☒ Stationary

☐ Mobile

Size across corners: 4.6 m x 4.6 m

Hook height		Central ballast	Jib position	Crane in service					Horizontal load	Crane out of service					Horizontal load
Slewing torque: 280 kNm				Wind region: C25											
Corner loads				Corner loads											
				A	B	C	D		A	B	C	D			
[m]	[m]	[t]		[kN]	[kN]	[kN]	[kN]	[kN]	[kN]	[kN]	[kN]	[kN]	[kN]	[kN]	
6.8	7.2	45	1	268	516	268	21	24	162	465	162	0	43		
			2	446	446	151	151		362	362	32	32			
11.3	11.7	50	1	286	545	285	26	26	192	474	191	0	50		
			2	474	474	157	157		382	382	46	46			
15.8	16.2	50	1	290	563	290	17	27	195	484	195	0	57		
			2	490	490	150	150		390	390	47	47			
20.3	20.7	50	1	295	583	294	6	29	198	496	198	0	64		
			2	507	507	142	142		399	399	47	47			
24.8	25.2	55	1	342	620	342	64	30	225	511	225	0	71		
			2	538	538	145	145		421	421	59	59			
29.3	29.7	55	1	307	651	307	0	32	226	527	226	0	78		
			2	559	559	134	134		431	431	58	58			
33.8	34.2	60	1	319	694	319	0	33	251	545	251	0	86		
			2	593	593	133	133		455	455	69	69			
38.3	38.7	60	1	304	743	304	0	35	338	575	338	100	93		
			2	617	617	118	118		506	506	170	170			
42.8	43.2	65	1	312	797	311	0	36	355	670	355	40	101		
			2	656	656	114	114		578	578	132	132			
47.3	47.7	80	1	366	857	366	0	38	392	804	392	0	108		
			2	722	722	132	132		681	681	112	112			
51.8	52.2	100	1	481	937	481	26	39	403	1000	403	0	116		
			2	804	804	159	159		805	805	98	98			
56.3	56.7	115	1	529	1015	528	42	42	396	1203	396	0	127		
			2	872	872	185	185		924	924	73	73			
60.8	61.2	145	1	611	1137	610	84	44	443	1437	443	0	137		
			2	983	983	238	238		1089	1089	72	72			

12.2.26 Slewing section with 50 m Jib on KR 10-46

Tower crane without climbing frame

☒ Stationary

☐ Mobile

Size across corners: 4.6 m x 4.6 m

Hook height		Central ballast	Jib position	Crane in service					Horizontal load	Crane out of service				Horizontal load
				Slewing torque: 280 kNm				Wind region: C25						
				Corner loads				Corner loads						
 [m]	 [m]	[t]		A [kN]	B [kN]	C [kN]	D [kN]		A [kN]	B [kN]	C [kN]	D [kN]		
6.8	7.2	45	1	299	506	299	91	24	162	465	162	0	43	
			2	446	446	152	152		362	362	32	32		
11.3	11.7	50	1	316	538	316	93	26	191	474	191	0	50	
			2	473	473	159	159		382	382	46	46		
15.8	16.2	50	1	320	559	320	82	27	195	484	195	0	57	
			2	489	489	152	152		390	390	47	47		
20.3	20.7	50	1	325	582	325	68	29	198	497	198	0	64	
			2	506	506	143	143		399	399	47	47		
24.8	25.2	55	1	342	619	342	65	30	225	511	225	0	71	
			2	538	538	146	146		421	421	59	59		
29.3	29.7	55	1	347	646	346	47	32	226	527	226	0	78	
			2	558	558	135	135		431	431	58	58		
33.8	34.2	60	1	364	688	363	39	33	251	545	251	0	86	
			2	593	593	134	134		465	465	202	202		
38.3	38.7	60	1	368	720	368	16	35	338	593	338	83	93	
			2	617	617	119	119		518	518	158	158		
42.8	43.2	65	1	324	773	324	0	36	355	688	355	22	101	
			2	655	655	115	115		591	591	119	119		
47.3	47.7	75	1	413	832	413	0	38	349	842	348	0	109	
			2	709	709	120	120		683	683	87	87		
51.8	52.2	95	1	469	924	469	15	39	359	1040	359	0	117	
			2	791	791	148	148		807	807	71	71		
56.3	56.7	115	1	529	1014	529	43	42	376	1243	376	0	127	
			2	872	872	185	185		939	939	59	59		
60.8	61.2	150	1	623	1149	623	98	44	448	1479	447	0	137	
			2	995	995	252	252		1117	1117	70	70		

12.2.27 Slewing section with 52.5 m Jib on KR 10-46

Tower crane without climbing frame

☒ Stationary

☐ Mobile

Size across corners: 4.6 m x 4.6 m

Hook height		Central ballast	Jib position	Crane in service Slewing torque: 280 kNm				Horizontal load	Crane out of service Wind region: C25				Horizontal load				
				Corner loads					Corner loads								
				A	B	C	D		A	B	C	D					
[m]	[m]	[t]		[kN]	[kN]	[kN]	[kN]	[kN]	[kN]	[kN]	[kN]	[kN]	[kN]				
6.8	7.2	45	1	277	523	277	30	24	162	465	161	0	43				
			2	451	451	102	102		362	362	32	32					
11.3	11.7	50	1	294	553	294	35	26	191	474	191	0	50				
			2	477	477	110	110		382	382	46	46					
15.8	16.2	50	1	298	571	298	25	27	195	485	195	0	58				
			2	491	491	105	105		390	390	47	47					
20.3	20.7	50	1	303	592	303	14	29	198	497	198	0	65				
			2	507	507	98	98		399	399	47	47					
24.8	25.2	55	1	320	627	320	13	30	225	512	225	0	72				
			2	537	537	103	103		421	421	59	59					
29.3	29.7	55	1	322	653	322	0	32	226	528	226	0	79				
			2	556	556	93	93		432	432	58	58					
33.8	34.2	60	1	334	698	334	0	33	251	546	251	0	87				
			2	588	588	95	95		471	471	212	212					
38.3	38.7	65	1	344	747	343	0	35	359	613	358	104	94				
			2	623	623	94	94		538	538	179	179					
42.8	43.2	65	1	325	803	325	0	36	363	697	363	30	102				
			2	647	647	139	139		599	599	127	127					
47.3	47.7	75	1	353	864	353	0	38	363	845	363	0	109				
			2	700	700	145	145		692	692	94	94					
51.8	52.2	95	1	428	933	428	0	39	372	1046	371	0	117				
			2	782	782	172	172		817	817	77	77					
56.3	56.7	115	1	507	1001	507	12	42	388	1252	388	0	128				
			2	863	863	210	210		950	950	64	64					
60.8	61.2	150	1	631	1133	631	130	44	458	1491	457	0	138				
			2	986	986	276	276		1129	1129	74	74					

12.2.28 Slewing section with 55 m Jib on KR 10-46

Tower crane without climbing frame

☒ Stationary

☐ Mobile

Size across corners: 4.6 m x 4.6 m

Hook height		Central ballast	Jib position	Crane in service					Horizontal load	Crane out of service					Horizontal load
				Slewing torque: 280 kNm				Wind region: C25							
				Corner loads				Corner loads							
				A	B	C	D	A		B	C	D			
[m]	[m]	[t]		[kN]	[kN]	[kN]	[kN]	[kN]	[kN]	[kN]	[kN]	[kN]	[kN]		
6.8	7.2	45	1	307	510	307	105	25	162	465	161	0	43		
			2	450	450	164	164		362	362	32	32			
11.3	11.7	50	1	324	541	324	107	26	191	474	191	0	50		
			2	478	478	171	171		382	382	46	46			
15.8	16.2	50	1	329	562	329	96	28	195	485	195	0	58		
			2	494	494	164	164		390	390	47	47			
20.3	20.7	50	1	334	585	333	82	29	198	497	198	0	65		
			2	512	512	156	156		399	399	47	47			
24.8	25.2	55	1	351	623	351	78	31	225	512	225	0	72		
			2	543	543	158	158		421	421	59	59			
29.3	29.7	55	1	355	650	355	60	32	226	528	226	0	79		
			2	564	564	147	147		432	432	218	218			
33.8	34.2	60	1	372	692	372	52	34	342	556	342	128	87		
			2	598	598	146	146		494	494	191	191			
38.3	38.7	65	1	389	737	389	41	35	359	644	359	74	94		
			2	635	635	143	143		561	561	158	158			
42.8	43.2	65	1	394	773	394	15	37	363	730	363	0	102		
			2	662	662	126	126		622	622	105	105			
47.3	47.7	70	1	408	827	408	0	38	307	911	306	0	109		
			2	704	704	118	118		703	703	59	59			
51.8	52.2	95	1	478	931	478	25	40	339	1114	339	0	117		
			2	798	798	158	158		842	842	54	54			
56.3	56.7	125	1	563	1047	562	78	42	405	1320	405	0	128		
			2	905	905	220	220		1000	1000	65	65			
60.8	61.2	160	1	657	1182	657	132	44	474	1562	473	0	138		
			2	1028	1028	286	286		1179	1179	75	75			

12.2.29 Slewing section with 57.5 m Jib on KR 10-46

Tower crane without climbing frame

☒ Stationary

☐ Mobile

Size across corners: 4.6 m x 4.6 m

Hook height		Central ballast	Jib position	Crane in service					Horizontal load	Crane out of service				Horizontal load
Slewing torque: 280 kNm				Wind region: C25										
Corner loads				Corner loads										
				A	B	C	D		A	B	C	D		
[m]	[m]	[t]		[kN]	[kN]	[kN]	[kN]	[kN]	[kN]	[kN]	[kN]	[kN]	[kN]	
6.8	7.2	45	1	277	505	277	49	25	161	466	161	0	44	
			2	440	440	175	175		362	362	32	32		
11.3	11.7	50	1	294	535	294	54	26	191	475	191	0	51	
			2	467	467	181	181		382	382	46	46		
15.8	16.2	50	1	299	553	299	44	28	195	485	195	0	58	
			2	483	483	174	174		390	390	47	47		
20.3	20.7	50	1	303	573	303	33	29	198	498	198	0	65	
			2	501	501	166	166		399	399	47	47		
24.8	25.2	55	1	320	608	320	33	31	225	512	224	0	72	
			2	532	532	169	169		421	421	59	59		
29.3	29.7	55	1	355	634	355	76	32	226	528	225	0	80	
			2	552	552	157	157		433	433	217	217		
33.8	34.2	60	1	372	676	372	68	34	342	558	342	126	87	
			2	587	587	157	157		494	494	189	189		
38.3	38.7	65	1	389	721	389	57	35	359	646	359	72	95	
			2	624	624	154	154		562	562	156	156		
42.8	43.2	65	1	347	761	347	0	37	360	735	360	0	102	
			2	650	650	137	137		623	623	104	104		
47.3	47.7	70	1	351	822	350	0	38	304	916	303	0	110	
			2	691	691	130	130		705	705	57	57		
51.8	52.2	95	1	478	912	478	43	40	336	1120	336	0	118	
			2	785	785	170	170		844	844	52	52		
56.3	56.7	125	1	562	1028	562	96	42	401	1327	401	0	129	
			2	892	892	233	233		1002	1002	63	63		
60.8	61.2	160	1	657	1163	657	151	44	469	1569	469	0	138	
			2	1015	1015	299	299		1182	1182	72	72		

12.2.30 Slewing section with 60 m Jib on KR 10-46

Tower crane without climbing frame

☒ Stationary

☐ Mobile

Size across corners: 4.6 m x 4.6 m

Hook height		Central ballast	Jib position	Crane in service					Horizontal load	Crane out of service					Horizontal load
				Slewing torque: 280 kNm				Wind region: C25							
				Corner loads				Corner loads							
[m]	[m]	[t]		A [kN]	B [kN]	C [kN]	D [kN]	[kN]	A [kN]	B [kN]	C [kN]	D [kN]	[kN]		
6.8	7.2	45	1	307	500	307	115	25	161	466	161	0	44		
			2	444	444	171	171		362	362	32	32			
11.3	11.7	50	1	325	532	324	117	26	191	475	191	0	51		
			2	471	471	178	178		382	382	46	46			
15.8	16.2	50	1	329	553	329	105	28	195	486	195	0	58		
			2	487	487	171	171		390	390	47	47			
20.3	20.7	50	1	334	575	334	92	29	197	498	197	0	65		
			2	505	505	163	163		399	399	47	47			
24.8	25.2	55	1	351	613	351	88	31	224	513	224	0	73		
			2	536	536	165	165		422	422	59	59			
29.3	29.7	55	1	355	640	355	70	32	225	529	225	0	80		
			2	557	557	154	154		450	450	201	201			
33.8	34.2	60	1	372	682	372	63	34	342	582	342	102	87		
			2	591	591	153	153		512	512	172	172			
38.3	38.7	65	1	389	727	389	52	35	359	672	359	47	95		
			2	628	628	151	151		580	580	138	138			
42.8	43.2	70	1	406	775	406	38	37	359	787	359	0	103		
			2	667	667	146	146		655	655	98	98			
47.3	47.7	75	1	423	826	423	21	38	302	971	302	0	110		
			2	708	708	138	138		737	737	50	50			
51.8	52.2	105	1	503	945	503	61	40	358	1177	358	0	118		
			2	815	815	191	191		889	889	57	57			
56.3	56.7	135	1	588	1060	587	115	42	423	1386	422	0	129		
			2	922	922	253	253		1048	1048	67	67			
60.8	61.2	170	1	682	1195	682	169	44	490	1630	489	0	139		
			2	1045	1045	319	319		1229	1229	76	76			

12.2.31 Slewing section with 62.5 m Jib on KR 10-46

Tower crane without climbing frame

☒ Stationary

☐ Mobile

Size across corners: 4.6 m x 4.6 m

Hook height		Central ballast	Jib position	Crane in service					Horizontal load	Crane out of service				Horizontal load
Slewing torque: 280 kNm				Wind region: C25										
Corner loads				Corner loads										
				A	B	C	D		A	B	C	D		
[m]	[m]	[t]		[kN]	[kN]	[kN]	[kN]	[kN]	[kN]	[kN]	[kN]	[kN]	[kN]	[kN]
6.8	7.2	55	1	310	530	310	91	25	239	519	238	0	44	
			2	466	466	155	155		433	433	65	65		
11.3	11.7	55	1	315	547	315	83	26	243	529	243	0	51	
			2	479	479	151	151		440	440	66	66		
15.8	16.2	60	1	332	578	332	86	28	271	541	270	0	59	
			2	506	506	158	158		462	462	79	79		
20.3	20.7	60	1	337	599	336	75	29	273	554	273	0	66	
			2	522	522	151	151		471	471	79	79		
24.8	25.2	65	1	354	633	354	74	31	292	577	292	7	73	
			2	551	551	156	156		494	494	90	90		
29.3	29.7	65	1	358	658	358	58	32	297	591	297	2	80	
			2	570	570	146	146		505	505	89	89		
33.8	34.2	70	1	375	697	375	53	34	314	618	314	9	88	
			2	603	603	148	148		545	545	206	206		
38.3	38.7	75	1	392	739	392	46	35	392	705	392	80	95	
			2	637	637	207	207		613	613	171	171		
42.8	43.2	80	1	409	784	409	35	37	409	804	409	14	103	
			2	676	676	203	203		689	689	130	130		
47.3	47.7	85	1	426	831	426	21	38	365	975	365	0	111	
			2	717	717	196	196		771	771	81	81		
51.8	52.2	100	1	468	908	468	29	40	345	1184	345	0	119	
			2	786	786	211	211		887	887	49	49		
56.3	56.7	130	1	583	1021	583	145	42	409	1395	409	0	129	
			2	893	893	273	273		1046	1046	60	60		
60.8	61.2	165	1	678	1155	677	200	44	474	1642	474	0	139	
			2	1015	1015	340	340		1228	1228	67	67		

12.2.32 Slewing section with 65 m Jib on KR 10-46

Tower crane without climbing frame

☒ Stationary

☐ Mobile

Size across corners: 4.6 m x 4.6 m

Hook height		Central ballast	Jib position	Crane in service					Horizontal load	Crane out of service				Horizontal load
				Slewing torque: 280 kNm				Wind region: C25						
				Corner loads				Corner loads						
				A	B	C	D	A		B	C	D		
[m]	[m]	[t]		[kN]	[kN]	[kN]	[kN]	[kN]	[kN]	[kN]	[kN]	[kN]	[kN]	
6.8	7.2	65	1	366	531	366	202	25	261	578	261	0	45	
			2	482	482	250	250		479	479	70	70		
11.3	11.7	65	1	371	550	371	192	26	265	587	265	0	52	
			2	497	497	244	244		487	487	71	71		
15.8	16.2	65	1	375	571	375	180	28	268	599	268	0	59	
			2	513	513	237	237		496	496	72	72		
20.3	20.7	70	1	392	606	392	179	29	295	613	295	0	66	
			2	543	543	241	241		518	518	84	84		
24.8	25.2	75	1	409	643	409	176	31	318	633	318	3	73	
			2	575	575	244	244		541	541	95	95		
29.3	29.7	75	1	414	670	414	158	32	321	649	321	0	81	
			2	595	595	233	233		552	552	93	93		
33.8	34.2	80	1	431	712	431	150	34	401	679	401	123	88	
			2	629	629	232	232		598	598	204	204		
38.3	38.7	85	1	448	756	448	140	35	418	770	418	66	96	
			2	666	666	230	230		667	667	169	169		
42.8	43.2	90	1	465	804	465	126	37	435	872	434	0	103	
			2	705	705	226	226		744	744	127	127		
47.3	47.7	95	1	482	855	482	109	38	374	1061	374	0	111	
			2	746	746	218	218		827	827	77	77		
51.8	52.2	115	1	537	948	537	125	40	377	1273	377	0	119	
			2	827	827	246	246		957	957	56	56		
56.3	56.7	145	1	621	1064	621	179	42	440	1486	440	0	130	
			2	934	934	308	308		1117	1117	66	66		
60.8	61.2	180	1	716	1199	716	233	44	504	1737	503	0	139	
			2	1057	1057	374	374		1300	1300	72	72		

12.2.33 Slewing section with 30 m Jib on KR 10-46/60

Tower crane without climbing frame

☒ Stationary

☐ Mobile

Size across corners: 6.0 m x 6.0 m

Hook height		Central ballast	Jib position	Crane in service					Horizontal load	Crane out of service					Horizontal load
Slewing torque: 280 kNm				Wind region: C25											
Corner loads				Corner loads											
				A	B	C	D		A	B	C	D			
[m]	[m]	[t]		[kN]	[kN]	[kN]	[kN]	[kN]	[kN]	[kN]	[kN]	[kN]	[kN]	[kN]	
6.8	7.2	30	1	237	411	237	64	24	146	355	146	0	41		
			2	360	360	115	115		288	288	36	36			
11.3	11.7	30	1	242	426	242	58	25	152	362	152	0	48		
			2	372	372	112	112		295	295	38	38			
15.8	16.2	30	1	246	443	246	50	27	158	370	158	0	55		
			2	385	385	108	108		302	302	40	40			
20.3	20.7	30	1	251	461	251	41	28	162	379	162	0	62		
			2	399	399	103	103		310	310	42	42			
24.8	25.2	30	1	256	480	256	31	30	166	389	166	0	69		
			2	414	414	97	97		318	318	42	42			
29.3	29.7	30	1	260	501	260	19	31	169	401	169	0	76		
			2	431	431	90	90		327	327	43	43			
33.8	34.2	30	1	206	527	206	0	33	171	415	171	0	83		
			2	448	448	81	81		336	336	42	42			
38.3	38.7	35	1	223	562	223	0	34	198	430	198	0	91		
			2	479	479	84	84		358	358	54	54			
42.8	43.2	45	1	311	613	311	9	36	281	475	281	87	98		
			2	525	525	98	98		418	418	144	144			
47.3	47.7	55	1	341	667	341	14	37	311	568	311	54	106		
			2	572	572	110	110		492	492	129	129			
51.8	52.2	70	1	383	737	383	29	39	353	680	353	26	114		
			2	633	633	133	133		584	584	122	122			
56.3	56.7	80	1	417	794	417	41	41	374	802	374	0	124		
			2	684	684	151	151		671	671	104	104			
60.8	61.2	95	1	462	868	462	57	43	379	971	379	0	134		
			2	749	749	175	175		776	776	88	88			

12.2.34 Slewing section with 32.5 m Jib on KR 10-46/60

Tower crane without climbing frame

☒ Stationary

☐ Mobile

Size across corners: 6.0 m x 6.0 m

Hook height		Central ballast	Jib position	Crane in service					Horizontal load	Crane out of service				Horizontal load
				Slewing torque: 280 kNm				Wind region: C25						
				Corner loads				Corner loads						
		[t]		A	B	C	D		A	B	C	D		
[m]	[m]			[kN]	[kN]	[kN]	[kN]	[kN]	[kN]	[kN]	[kN]	[kN]	[kN]	[kN]
6.8	7.2	25	1	203	403	203	2	24	121	356	121	0	41	
			2	350	350	116	116		281	281	125	125		
11.3	11.7	25	1	206	419	206	0	25	127	362	127	0	48	
			2	362	362	113	113		282	282	26	26		
15.8	16.2	30	1	224	444	224	5	27	158	370	158	0	55	
			2	388	388	121	121		302	302	40	40		
20.3	20.7	30	1	227	462	227	0	28	162	379	162	0	62	
			2	402	402	116	116		310	310	41	41		
24.8	25.2	30	1	223	488	223	0	30	166	389	166	0	69	
			2	417	417	110	110		318	318	42	42		
29.3	29.7	30	1	218	517	218	0	31	169	401	169	0	76	
			2	433	433	103	103		327	327	43	43		
33.8	34.2	30	1	211	550	211	0	33	171	415	171	0	83	
			2	451	451	95	95		336	336	42	42		
38.3	38.7	35	1	227	585	227	0	34	198	430	198	0	91	
			2	482	482	97	97		359	359	54	54		
42.8	43.2	45	1	266	625	266	0	36	289	479	289	99	98	
			2	528	528	111	111		424	424	155	155		
47.3	47.7	55	1	303	669	303	0	37	319	572	319	65	106	
			2	575	575	123	123		498	498	140	140		
51.8	52.2	70	1	391	738	391	43	39	361	685	361	36	114	
			2	636	636	145	145		590	590	131	131		
56.3	56.7	80	1	425	796	425	55	41	392	798	392	0	125	
			2	687	687	164	164		678	678	113	113		
60.8	61.2	95	1	470	869	470	71	43	396	969	396	0	134	
			2	752	752	188	188		783	783	97	97		

12.2.35 Slewing section with 35 m Jib on KR 10-46/60

Tower crane without climbing frame

☒ Stationary

☐ Mobile

Size across corners: 6.0 m x 6.0 m

Hook height		Central ballast	Jib position	Crane in service					Horizontal load	Crane out of service					Horizontal load
Slewing torque: 280 kNm				Wind region: C25											
Corner loads				Corner loads											
				A	B	C	D		A	B	C	D			
[m]	[m]	[t]		[kN]	[kN]	[kN]	[kN]	[kN]	[kN]	[kN]	[kN]	[kN]	[kN]	[kN]	
6.8	7.2	30	1	246	425	246	67	24	146	356	146	0	41		
			2	373	373	119	119		288	288	36	36			
11.3	11.7	30	1	251	441	251	60	26	152	362	152	0	48		
			2	385	385	116	116		295	295	38	38			
15.8	16.2	30	1	255	458	255	53	27	157	370	157	0	55		
			2	398	398	112	112		302	302	40	40			
20.3	20.7	30	1	260	476	260	43	29	162	379	162	0	62		
			2	413	413	107	107		310	310	41	41			
24.8	25.2	30	1	264	496	264	33	30	166	390	166	0	69		
			2	428	428	100	100		318	318	42	42			
29.3	29.7	30	1	269	517	269	20	32	169	402	169	0	76		
			2	445	445	93	93		327	327	42	42			
33.8	34.2	30	1	273	541	273	6	33	171	415	171	0	84		
			2	462	462	84	84		336	336	42	42			
38.3	38.7	35	1	290	579	290	2	35	198	431	198	0	91		
			2	494	494	87	87		368	368	152	152			
42.8	43.2	40	1	304	622	304	0	36	277	488	277	67	99		
			2	527	527	87	87		426	426	129	129			
47.3	47.7	50	1	337	674	337	0	38	307	581	307	33	106		
			2	575	575	99	99		501	501	113	113			
51.8	52.2	65	1	379	744	379	14	39	349	695	349	3	114		
			2	637	637	121	121		594	594	105	105			
56.3	56.7	75	1	414	802	414	25	42	347	842	347	0	125		
			2	688	688	139	139		681	681	86	86			
60.8	61.2	90	1	458	876	458	40	43	350	1014	350	0	135		
			2	754	754	163	163		787	787	70	70			

12.2.36 Slewing section with 37.5 m Jib on KR 10-46/60

Tower crane without climbing frame

☒ Stationary

☐ Mobile

Size across corners: 6.0 m x 6.0 m

Hook height		Central ballast	Jib position	Crane in service					Horizontal load	Crane out of service				Horizontal load
				Slewing torque: 280 kNm				Wind region: C25						
				Corner loads				Corner loads						
 [m]	 [m]	[t]		A [kN]	B [kN]	C [kN]	D [kN]		A [kN]	B [kN]	C [kN]	D [kN]		
6.8	7.2	30	1	247	430	247	64	24	146	356	146	0	42	
			2	377	377	118	118		288	288	36	36		
11.3	11.7	30	1	252	446	252	58	26	152	362	152	0	48	
			2	389	389	115	115		295	295	38	38		
15.8	16.2	30	1	256	463	256	50	27	157	370	157	0	55	
			2	402	402	110	110		302	302	40	40		
20.3	20.7	30	1	261	481	261	41	29	162	379	162	0	62	
			2	417	417	105	105		310	310	41	41		
24.8	25.2	30	1	265	501	265	30	30	166	390	166	0	70	
			2	432	432	99	99		318	318	42	42		
29.3	29.7	30	1	270	523	270	17	32	169	402	169	0	77	
			2	449	449	91	91		327	327	42	42		
33.8	34.2	35	1	287	559	287	15	33	196	416	196	0	84	
			2	479	479	95	95		349	349	55	55		
38.3	38.7	35	1	291	585	291	0	35	197	431	197	0	92	
			2	499	499	85	85		378	378	145	145		
42.8	43.2	35	1	277	631	277	0	36	266	489	266	43	99	
			2	520	520	73	73		424	424	109	109		
47.3	47.7	50	1	335	683	335	0	38	308	596	308	21	107	
			2	580	580	97	97		512	512	105	105		
51.8	52.2	60	1	366	740	366	0	39	316	719	316	0	115	
			2	630	630	106	106		592	592	83	83		
56.3	56.7	70	1	402	796	402	9	42	310	871	310	0	125	
			2	681	681	124	124		680	680	64	64		
60.8	61.2	85	1	447	871	447	23	44	312	1044	312	0	135	
			2	747	747	147	147		786	786	48	48		

12.2.37 Slewing section with 40 m Jib on KR 10-46/60

Tower crane without climbing frame

☒ Stationary

☐ Mobile

Size across corners: 6.0 m x 6.0 m

Hook height		Central ballast	Jib position	Crane in service					Horizontal load	Crane out of service					Horizontal load
Slewing torque: 280 kNm				Wind region: C25											
Corner loads				Corner loads											
			A	B	C	D		A	B	C	D				
[m]	[m]	[t]	[kN]	[kN]	[kN]	[kN]	[kN]	[kN]	[kN]	[kN]	[kN]	[kN]			
6.8	7.2	25	1 212	410	212	14	24	121	356	121	0	42			
			2 358	358	125	125		280	280	144	144				
11.3	11.7	30	1 229	436	229	21	26	152	362	152	0	49			
			2 383	383	135	135		295	295	38	38				
15.8	16.2	30	1 263	452	263	75	27	157	370	157	0	56			
			2 396	396	130	130		302	302	40	40				
20.3	20.7	30	1 268	470	268	66	29	162	380	162	0	63			
			2 411	411	125	125		310	310	41	41				
24.8	25.2	30	1 273	490	273	55	30	165	390	165	0	70			
			2 426	426	119	119		318	318	42	42				
29.3	29.7	30	1 237	515	237	0	32	168	402	168	0	77			
			2 443	443	112	112		327	327	42	42				
33.8	34.2	35	1 254	548	254	0	33	196	416	196	0	84			
			2 473	473	115	115		349	349	54	54				
38.3	38.7	35	1 245	585	245	0	35	197	432	197	0	92			
			2 492	492	105	105		377	377	161	161				
42.8	43.2	40	1 259	625	259	0	36	286	497	286	75	99			
			2 525	525	106	106		435	435	137	137				
47.3	47.7	50	1 296	670	296	0	38	315	591	315	40	107			
			2 573	573	117	117		510	510	120	120				
51.8	52.2	65	1 387	738	387	37	39	357	706	357	9	115			
			2 635	635	139	139		604	604	111	111				
56.3	56.7	75	1 422	796	422	48	42	360	849	360	0	126			
			2 686	686	157	157		692	692	92	92				
60.8	61.2	90	1 467	871	467	62	44	362	1023	362	0	135			
			2 752	752	181	181		798	798	75	75				

12.2.38 Slewing section with 42.5 m Jib on KR 10-46/60

Tower crane without climbing frame

☒ Stationary

☐ Mobile

Size across corners: 6.0 m x 6.0 m

Hook height		Central ballast	Jib position	Crane in service					Horizontal load	Crane out of service				Horizontal load
				Slewing torque: 280 kNm				Wind region: C25						
				Corner loads				Corner loads						
 [m]	 [m]	[t]		A [kN]	B [kN]	C [kN]	D [kN]	[kN]	A [kN]	B [kN]	C [kN]	D [kN]	[kN]	
6.8	7.2	25	1	243	418	243	68	24	121	356	121	0	42	
			2	367	367	119	119		276	276	23	23		
11.3	11.7	30	1	260	447	260	74	26	152	363	152	0	49	
			2	392	392	128	128		295	295	38	38		
15.8	16.2	30	1	265	464	265	66	27	157	371	157	0	56	
			2	405	405	124	124		302	302	40	40		
20.3	20.7	30	1	269	482	269	56	29	162	380	162	0	63	
			2	420	420	119	119		310	310	41	41		
24.8	25.2	30	1	274	502	274	45	30	165	391	165	0	70	
			2	435	435	112	112		318	318	42	42		
29.3	29.7	30	1	278	524	278	33	32	168	403	168	0	77	
			2	452	452	105	105		327	327	42	42		
33.8	34.2	35	1	295	560	295	31	33	195	417	195	0	85	
			2	482	482	108	108		352	352	179	179		
38.3	38.7	35	1	300	586	300	14	35	270	445	270	95	92	
			2	502	502	98	98		394	394	146	146		
42.8	43.2	40	1	317	626	317	8	36	287	520	287	53	100	
			2	536	536	98	98		452	452	122	122		
47.3	47.7	45	1	333	670	333	0	38	304	603	304	5	108	
			2	571	571	97	97		516	516	92	92		
51.8	52.2	60	1	376	740	376	12	39	319	746	319	0	115	
			2	634	634	118	118		610	610	82	82		
56.3	56.7	70	1	411	799	411	23	42	312	899	312	0	126	
			2	685	685	136	136		699	699	63	63		
60.8	61.2	90	1	468	886	468	49	44	338	1076	338	0	136	
			2	764	764	172	172		818	818	57	57		

12.2.39 Slewing section with 45 m Jib on KR 10-46/60

Tower crane without climbing frame

☒ Stationary

☐ Mobile

Size across corners: 6.0 m x 6.0 m

Hook height		Central ballast	Jib position	Crane in service Slewing torque: 280 kNm				Horizontal load	Crane out of service Wind region: C25				Horizontal load				
 [m]	 [m]			Corner loads					Corner loads								
				A	B	C	D		A	B	C	D					
[kN]	[kN]	[t]		[kN]	[kN]	[kN]	[kN]	[kN]	[kN]	[kN]	[kN]	[kN]	[kN]				
6.8	7.2	30	1	233	430	233	36	24	146	356	146	0	42				
			2	373	373	153	153		294	294	172	172					
11.3	11.7	30	1	238	444	238	32	26	152	363	152	0	49				
			2	385	385	150	150		295	295	38	38					
15.8	16.2	30	1	242	459	242	25	27	157	371	157	0	56				
			2	398	398	146	146		302	302	40	40					
20.3	20.7	30	1	247	475	247	18	29	161	380	161	0	63				
			2	413	413	141	141		310	310	41	41					
24.8	25.2	30	1	251	493	251	9	30	165	391	165	0	71				
			2	428	428	134	134		319	319	42	42					
29.3	29.7	30	1	255	514	255	0	32	168	403	168	0	78				
			2	445	445	127	127		327	327	42	42					
33.8	34.2	35	1	272	548	272	0	33	195	417	195	0	85				
			2	475	475	131	131		354	354	192	192					
38.3	38.7	35	1	262	585	262	0	35	277	445	277	110	93				
			2	494	494	121	121		396	396	159	159					
42.8	43.2	40	1	276	627	276	0	36	294	521	294	68	100				
			2	528	528	121	121		454	454	134	134					
47.3	47.7	45	1	287	673	287	0	38	311	604	311	19	108				
			2	563	563	120	120		518	518	105	105					
51.8	52.2	60	1	384	726	384	41	39	341	733	341	0	116				
			2	626	626	141	141		613	613	94	94					
56.3	56.7	70	1	418	784	418	52	42	333	888	333	0	127				
			2	677	677	159	159		702	702	74	74					
60.8	61.2	85	1	463	859	463	66	44	333	1066	333	0	136				
			2	743	743	183	183		810	810	56	56					

12.2.40 Slewing section with 47.5 m Jib on KR 10-46/60

Tower crane without climbing frame

☒ Stationary

☐ Mobile

Size across corners: 6.0 m x 6.0 m

Hook height		Central ballast	Jib position	Crane in service Slewing torque: 280 kNm				Horizontal load	Crane out of service Wind region: C25				Horizontal load				
 [m]	 [m]			Corner loads					Corner loads								
				A	B	C	D		A	B	C	D					
[kN]	[kN]	[t]		[kN]	[kN]	[kN]	[kN]	[kN]	[kN]	[kN]	[kN]	[kN]	[kN]				
6.8	7.2	30	1	263	424	263	103	24	146	356	146	0	43				
			2	377	377	150	150		288	288	36	36					
11.3	11.7	30	1	268	439	268	97	26	152	363	152	0	50				
			2	389	389	147	147		295	295	38	38					
15.8	16.2	30	1	273	456	273	89	27	157	371	157	0	57				
			2	402	402	143	143		302	302	40	40					
20.3	20.7	30	1	277	475	277	79	29	161	380	161	0	64				
			2	417	417	137	137		310	310	41	41					
24.8	25.2	30	1	282	495	282	68	30	165	391	165	0	71				
			2	432	432	131	131		319	319	42	42					
29.3	29.7	30	1	286	516	286	56	32	168	404	168	0	78				
			2	449	449	123	123		328	328	42	42					
33.8	34.2	35	1	303	552	303	54	33	195	417	195	0	86				
			2	479	479	127	127		364	364	182	182					
38.3	38.7	35	1	308	578	308	37	35	278	460	278	96	93				
			2	499	499	117	117		406	406	149	149					
42.8	43.2	40	1	325	619	325	31	36	295	536	295	53	101				
			2	533	533	117	117		466	466	124	124					
47.3	47.7	45	1	342	662	342	22	38	312	620	312	3	108				
			2	568	568	116	116		530	530	94	94					
51.8	52.2	55	1	371	721	371	22	39	300	767	300	0	116				
			2	618	618	124	124		613	613	70	70					
56.3	56.7	65	1	406	779	406	33	42	291	922	291	0	127				
			2	670	670	142	142		702	702	50	50					
60.8	61.2	90	1	476	879	476	72	44	341	1101	341	0	137				
			2	761	761	190	190		835	835	56	56					

12.2.41 Slewing section with 50 m Jib on KR 10-46/60

Tower crane without climbing frame

☒ Stationary

☐ Mobile

Size across corners: 6.0 m x 6.0 m

Hook height		Central ballast	Jib position	Crane in service					Horizontal load	Crane out of service					Horizontal load
				Slewing torque: 280 kNm				Wind region: C25							
				Corner loads				Corner loads							
[m]	[m]	[t]		A [kN]	B [kN]	C [kN]	D [kN]	[kN]	A [kN]	B [kN]	C [kN]	D [kN]	[kN]		
6.8	7.2	30	1	264	423	264	104	24	146	356	146	0	43		
			2	376	376	151	151		288	288	36	36			
11.3	11.7	30	1	268	439	268	98	26	152	363	152	0	50		
			2	389	389	148	148		295	295	38	38			
15.8	16.2	30	1	273	456	273	90	27	157	371	157	0	57		
			2	402	402	143	143		302	302	40	40			
20.3	20.7	30	1	277	474	277	81	29	161	381	161	0	64		
			2	417	417	138	138		310	310	41	41			
24.8	25.2	30	1	282	494	282	70	30	165	392	165	0	71		
			2	432	432	132	132		319	319	42	42			
29.3	29.7	35	1	299	528	299	70	32	193	404	193	0	78		
			2	461	461	137	137		340	340	54	54			
33.8	34.2	35	1	304	552	304	55	33	195	418	195	0	86		
			2	479	479	128	128		374	374	173	173			
38.3	38.7	35	1	308	578	308	38	35	278	473	278	83	93		
			2	499	499	117	117		416	416	140	140			
42.8	43.2	40	1	325	618	325	32	36	295	551	295	40	101		
			2	532	532	118	118		476	476	114	114			
47.3	47.7	40	1	330	649	330	10	38	277	645	277	0	109		
			2	555	555	104	104		528	528	71	71			
51.8	52.2	55	1	372	720	372	23	39	285	797	285	0	117		
			2	618	618	125	125		624	624	60	60			
56.3	56.7	70	1	419	791	419	47	42	301	953	301	0	127		
			2	682	682	156	156		726	726	52	52			
60.8	61.2	95	1	488	891	488	85	44	350	1134	350	0	137		
			2	773	773	203	203		859	859	57	57			

12.2.42 Slewing section with 52.5 m Jib on KR 10-46/60

Tower crane without climbing frame

☒ Stationary

☐ Mobile

Size across corners: 6.0 m x 6.0 m

Hook height		Central ballast	Jib position	Crane in service					Horizontal load	Crane out of service				Horizontal load
				Slewing torque: 280 kNm				Wind region: C25						
				Corner loads				Corner loads						
		[t]		A	B	C	D		A	B	C	D		
[m]	[m]			[kN]	[kN]	[kN]	[kN]	[kN]	[kN]	[kN]	[kN]	[kN]	[kN]	[kN]
6.8	7.2	30	1	242	431	242	52	24	146	357	146	0	43	
			2	375	375	108	108		289	289	195	195		
11.3	11.7	30	1	246	445	246	48	26	152	363	152	0	50	
			2	387	387	106	106		295	295	38	38		
15.8	16.2	30	1	251	460	251	41	27	157	372	157	0	58	
			2	399	399	103	103		303	303	39	39		
20.3	20.7	30	1	255	477	255	34	29	161	381	161	0	65	
			2	412	412	159	159		311	311	41	41		
24.8	25.2	30	1	260	495	260	25	30	165	392	165	0	72	
			2	427	427	152	152		319	319	41	41		
29.3	29.7	35	1	277	527	277	26	32	192	405	192	0	79	
			2	457	457	157	157		343	343	211	211		
33.8	34.2	35	1	281	549	281	14	33	281	422	281	141	87	
			2	475	475	148	148		381	381	182	182		
38.3	38.7	35	1	286	573	286	0	35	286	481	286	91	94	
			2	494	494	138	138		424	424	148	148		
42.8	43.2	40	1	299	615	299	0	36	303	559	303	47	102	
			2	527	527	139	139		484	484	122	122		
47.3	47.7	40	1	284	662	284	0	38	292	648	292	0	109	
			2	550	550	125	125		537	537	78	78		
51.8	52.2	55	1	342	715	342	0	39	299	802	299	0	117	
			2	613	613	146	146		633	633	66	66		
56.3	56.7	65	1	414	768	414	60	42	289	959	289	0	128	
			2	665	665	164	164		724	724	45	45		
60.8	61.2	90	1	484	868	484	99	44	336	1143	336	0	138	
			2	756	756	212	212		858	858	50	50		

12.2.43 Slewing section with 55 m Jib on KR 10-46/60

Tower crane without climbing frame

☒ Stationary

☐ Mobile

Size across corners: 6.0 m x 6.0 m

Hook height [m]	Central ballast [t]	Jib position	Crane in service Slewing torque: 280 kNm				Horizontal load [kN]	Crane out of service Wind region: C25				Horizontal load [kN]		
			Corner loads					Corner loads						
			A [kN]	B [kN]	C [kN]	D [kN]		A [kN]	B [kN]	C [kN]	D [kN]			
6.8	7.2	30	1	272	427	272	117	25	146	357	146	0	43	
			2	382	382	163	163		288	288	36	36		
11.3	11.7	30	1	277	443	277	111	26	152	363	152	0	50	
			2	395	395	159	159		295	295	38	38		
15.8	16.2	30	1	282	460	282	103	28	157	372	157	0	58	
			2	408	408	155	155		303	303	39	39		
20.3	20.7	30	1	286	479	286	93	29	161	381	161	0	65	
			2	423	423	150	150		311	311	41	41		
24.8	25.2	30	1	291	499	291	82	31	165	392	165	0	72	
			2	438	438	143	143		319	319	41	41		
29.3	29.7	35	1	308	534	308	82	32	192	405	192	0	79	
			2	467	467	148	148		360	360	196	196		
33.8	34.2	35	1	312	557	312	67	34	282	446	282	118	87	
			2	486	486	139	139		398	398	166	166		
38.3	38.7	35	1	317	583	317	50	35	287	505	287	68	94	
			2	505	505	128	128		441	441	132	132		
42.8	43.2	40	1	334	624	334	43	37	304	584	304	24	102	
			2	539	539	128	128		502	502	106	106		
47.3	47.7	45	1	351	668	351	34	38	293	698	293	0	109	
			2	575	575	126	126		568	568	74	74		
51.8	52.2	55	1	380	728	380	33	40	274	854	274	0	117	
			2	626	626	135	135		652	652	48	48		
56.3	56.7	75	1	440	811	440	69	42	314	1012	314	0	128	
			2	702	702	178	178		768	768	52	52		
60.8	61.2	100	1	510	912	510	107	44	361	1197	361	0	138	
			2	794	794	225	225		903	903	56	56		

12.2.44 Slewing section with 57.5 m Jib on KR 10-46/60

Tower crane without climbing frame

☒ Stationary

☐ Mobile

Size across corners: 6.0 m x 6.0 m

Hook height [m]	Central ballast [t]	Jib position	Crane in service Slewing torque: 280 kNm				Horizontal load [kN]	Crane out of service Wind region: C25				Horizontal load [kN]		
			Corner loads					Corner loads						
			A [kN]	B [kN]	C [kN]	D [kN]		A [kN]	B [kN]	C [kN]	D [kN]			
6.8	7.2	30	1	242	417	242	67	25	146	357	146	0	44	
			2	374	374	170	170		288	288	36	36		
11.3	11.7	30	1	277	432	277	122	26	151	364	151	0	51	
			2	386	386	167	167		295	295	38	38		
15.8	16.2	30	1	281	449	281	114	28	156	372	156	0	58	
			2	400	400	163	163		303	303	39	39		
20.3	20.7	30	1	286	467	286	104	29	161	381	161	0	65	
			2	414	414	157	157		311	311	41	41		
24.8	25.2	30	1	290	487	290	93	31	164	392	164	0	72	
			2	430	430	151	151		319	319	41	41		
29.3	29.7	35	1	307	521	307	93	32	192	405	192	0	80	
			2	459	459	156	156		360	360	195	195		
33.8	34.2	35	1	312	545	312	79	34	282	447	282	117	87	
			2	477	477	147	147		399	399	165	165		
38.3	38.7	35	1	317	571	317	62	35	287	507	287	66	95	
			2	496	496	137	137		442	442	131	131		
42.8	43.2	40	1	334	611	334	56	37	304	585	304	22	102	
			2	530	530	137	137		503	503	104	104		
47.3	47.7	45	1	351	655	351	47	38	290	702	290	0	110	
			2	566	566	136	136		569	569	72	72		
51.8	52.2	55	1	380	713	380	47	40	271	858	271	0	118	
			2	616	616	144	144		654	654	47	47		
56.3	56.7	75	1	440	797	440	83	42	311	1017	311	0	129	
			2	692	692	187	187		770	770	50	50		
60.8	61.2	100	1	509	897	509	121	44	357	1203	357	0	138	
			2	784	784	235	235		905	905	54	54		

12.2.45 Slewing section with 60 m Jib on KR 10-46/60

Tower crane without climbing frame

☒ Stationary

☐ Mobile

Size across corners: 6.0 m x 6.0 m

Hook height [m]	Central ballast [t]	Jib position	Crane in service Slewing torque: 280 kNm				Horizontal load [kN]	Crane out of service Wind region: C25				Horizontal load [kN]		
			Corner loads					Corner loads						
			A [kN]	B [kN]	C [kN]	D [kN]		A [kN]	B [kN]	C [kN]	D [kN]			
6.8	7.2	30	1	272	420	272	125	25	146	357	146	0	44	
			2	377	377	168	168		290	290	86	86		
11.3	11.7	30	1	277	436	277	118	26	151	364	151	0	51	
			2	389	389	165	165		297	297	88	88		
15.8	16.2	30	1	282	453	282	110	28	156	372	156	0	58	
			2	403	403	160	160		304	304	89	89		
20.3	20.7	30	1	286	472	286	101	29	161	382	161	0	65	
			2	417	417	155	155		312	312	90	90		
24.8	25.2	30	1	291	492	291	90	31	164	393	164	0	73	
			2	433	433	149	149		326	326	196	196		
29.3	29.7	35	1	308	526	308	89	32	278	413	278	143	80	
			2	462	462	153	153		373	373	182	182		
33.8	34.2	35	1	312	550	312	75	34	282	466	282	98	87	
			2	480	480	144	144		412	412	152	152		
38.3	38.7	40	1	329	588	329	71	35	299	539	299	60	95	
			2	512	512	146	146		469	469	130	130		
42.8	43.2	40	1	334	616	334	51	37	304	606	304	2	103	
			2	534	534	134	134		517	517	90	90		
47.3	47.7	45	1	351	660	351	42	38	270	744	270	0	110	
			2	569	569	133	133		584	584	58	58		
51.8	52.2	60	1	393	731	393	54	40	275	902	275	0	118	
			2	632	632	154	154		682	682	44	44		
56.3	56.7	80	1	453	815	453	90	42	314	1062	314	0	129	
			2	709	709	196	196		798	798	47	47		
60.8	61.2	105	1	522	916	522	129	44	360	1249	360	0	139	
			2	800	800	244	244		934	934	50	50		

12.2.46 Slewing section with 62.5 m Jib on KR 10-46/60

Tower crane without climbing frame

☒ Stationary

☐ Mobile

Size across corners: 6.0 m x 6.0 m

Hook height [m]	Central ballast [t]	Jib position	Crane in service Slewing torque: 280 kNm				Horizontal load [kN]	Crane out of service Wind region: C25				Horizontal load [kN]		
			Corner loads					Corner loads						
			A [kN]	B [kN]	C [kN]	D [kN]		A [kN]	B [kN]	C [kN]	D [kN]			
6.8	7.2	30	1	250	419	250	82	25	179	398	179	0	44	
			2	369	369	131	131		330	330	48	48		
11.3	11.7	30	1	255	433	255	77	26	185	405	185	0	51	
			2	381	381	129	129		337	337	50	50		
15.8	16.2	30	1	260	448	260	71	28	189	414	189	0	59	
			2	394	394	185	185		344	344	51	51		
20.3	20.7	35	1	277	477	277	76	29	215	427	215	3	66	
			2	421	421	193	193		365	365	65	65		
24.8	25.2	35	1	281	496	281	67	31	220	438	220	1	73	
			2	436	436	186	186		374	374	65	65		
29.3	29.7	35	1	286	515	286	56	32	223	451	223	0	80	
			2	453	453	179	179		384	384	65	65		
33.8	34.2	40	1	303	550	303	56	34	303	487	303	119	88	
			2	483	483	182	182		433	433	173	173		
38.3	38.7	40	1	307	573	307	41	35	307	547	307	68	95	
			2	502	502	172	172		477	477	138	138		
42.8	43.2	45	1	354	611	354	98	37	324	627	324	21	103	
			2	536	536	173	173		538	538	110	110		
47.3	47.7	50	1	371	654	371	89	38	309	747	309	0	111	
			2	571	571	172	172		606	606	77	77		
51.8	52.2	55	1	388	700	388	77	40	263	908	263	0	119	
			2	609	609	168	168		680	680	37	37		
56.3	56.7	80	1	461	796	461	125	42	327	1069	327	0	129	
			2	698	698	223	223		809	809	52	52		
60.8	61.2	105	1	530	896	530	164	44	371	1259	371	0	139	
			2	789	789	271	271		945	945	55	55		

12.2.47 Slewing section with 65 m Jib on KR 10-46/60

Tower crane without climbing frame

☒ Stationary

☐ Mobile

Size across corners: 6.0 m x 6.0 m

Hook height [m]	Central ballast [t]	Jib position	Crane in service Slewing torque: 280 kNm				Horizontal load [kN]	Crane out of service Wind region: C25				Horizontal load [kN]		
			Corner loads					Corner loads						
			A [kN]	B [kN]	C [kN]	D [kN]		A [kN]	B [kN]	C [kN]	D [kN]			
6.8	7.2	35	1	294	420	294	168	25	183	443	183	0	45	
			2	383	383	205	205		359	359	45	45		
11.3	11.7	40	1	311	448	311	173	26	213	450	213	0	52	
			2	408	408	214	214		379	379	60	60		
15.8	16.2	40	1	315	465	315	165	28	218	459	218	0	59	
			2	421	421	209	209		386	386	61	61		
20.3	20.7	40	1	320	483	320	156	29	222	470	222	0	66	
			2	436	436	204	204		395	395	62	62		
24.8	25.2	45	1	337	516	337	158	31	245	487	245	4	73	
			2	464	464	210	210		416	416	74	74		
29.3	29.7	45	1	341	538	341	145	32	250	499	250	1	81	
			2	480	480	203	203		427	427	196	196		
33.8	34.2	45	1	346	561	346	131	34	316	529	316	103	88	
			2	498	498	194	194		467	467	165	165		
38.3	38.7	50	1	363	599	363	127	35	333	603	333	63	96	
			2	530	530	196	196		524	524	142	142		
42.8	43.2	55	1	380	640	380	120	37	350	684	350	16	103	
			2	564	564	196	196		586	586	114	114		
47.3	47.7	60	1	397	683	397	111	38	328	813	328	0	111	
			2	599	599	195	195		655	655	80	80		
51.8	52.2	65	1	414	729	414	99	40	281	976	281	0	119	
			2	637	637	191	191		729	729	39	39		
56.3	56.7	90	1	486	825	486	147	42	343	1139	343	0	130	
			2	726	726	246	246		859	859	53	53		
60.8	61.2	115	1	556	926	556	186	44	386	1331	386	0	139	
			2	818	818	294	294		997	997	55	55		

12.2.48 Slewing section with 30 m Jib on KR 1000-8

Tower crane without climbing frame

☒ Stationary

☐ Mobile

Size across corners: 8.0 m x 8.0 m

Hook height [m]	Central ballast [t]	Jib position	Crane in service Slewing torque: 280 kNm				Horizontal load [kN]	Crane out of service Wind region: C25				Horizontal load [kN]		
			Corner loads					Corner loads						
			A [kN]	B [kN]	C [kN]	D [kN]		A [kN]	B [kN]	C [kN]	D [kN]			
6.8	7.2	5	1	193	323	193	63	25	102	267	102	0	43	
			2	285	285	101	101		218	218	108	108		
11.3	11.7	5	1	200	339	200	62	27	114	272	114	0	51	
			2	298	298	102	102		221	221	29	29		
15.8	16.2	5	1	205	352	205	58	28	120	277	120	0	58	
			2	309	309	101	101		227	227	31	31		
20.3	20.7	5	1	209	366	209	52	30	126	284	126	0	65	
			2	320	320	98	98		234	234	33	33		
24.8	25.2	5	1	214	381	214	46	31	131	291	131	0	72	
			2	332	332	95	95		242	242	35	35		
29.3	29.7	5	1	218	398	218	39	33	136	300	136	0	80	
			2	345	345	91	91		249	249	37	37		
33.8	34.2	5	1	223	416	223	30	34	141	309	141	0	87	
			2	359	359	87	87		257	257	38	38		
38.3	38.7	5	1	227	434	227	20	36	144	320	144	0	94	
			2	374	374	81	81		271	271	124	124		
42.8	43.2	10	1	245	467	245	22	37	215	360	215	69	102	
			2	402	402	87	87		317	317	112	112		
47.3	47.7	15	1	262	502	262	21	39	232	423	232	40	110	
			2	431	431	92	92		367	367	96	96		
51.8	52.2	25	1	291	551	291	32	40	261	504	261	18	117	
			2	475	475	108	108		433	433	89	89		
56.3	56.7	35	1	321	601	321	40	42	282	599	282	0	125	
			2	519	519	122	122		503	503	79	79		
60.8	61.2	45	1	353	655	353	51	44	283	725	283	0	135	
			2	566	566	139	139		579	579	66	66		
65.3	65.7	55	1	385	710	385	60	45	278	864	278	0	144	
			2	615	615	155	155		660	660	49	49		
69.8	70.2	75	1	442	793	442	91	47	315	1018	315	0	154	
			2	690	690	194	194		772	772	52	52		

12.2.49 Slewing section with 32.5 m Jib on KR 1000-8

Tower crane without climbing frame

☒ Stationary

☐ Mobile

Size across corners: 8.0 m x 8.0 m

Hook height		Central ballast	Jib position	Crane in service Slewing torque: 280 kNm				Horizontal load	Crane out of service Wind region: C25				Horizontal load				
				Corner loads					Corner loads								
				A	B	C	D		A	B	C	D					
[m]	[m]	[t]		[kN]	[kN]	[kN]	[kN]	[kN]	[kN]	[kN]	[kN]	[kN]	[kN]				
6.8	7.2	5	1	201	325	201	77	25	102	267	102	0	43				
			2	289	289	113	113		229	229	113	113					
11.3	11.7	5	1	208	340	208	76	27	114	272	114	0	52				
			2	302	302	115	115		224	224	132	132					
15.8	16.2	5	1	213	354	213	71	28	120	277	120	0	59				
			2	312	312	113	113		228	228	31	31					
20.3	20.7	5	1	217	368	217	66	30	126	284	126	0	66				
			2	324	324	110	110		234	234	33	33					
24.8	25.2	5	1	222	383	222	60	31	131	291	131	0	73				
			2	336	336	107	107		242	242	35	35					
29.3	29.7	5	1	226	400	226	53	33	136	300	136	0	80				
			2	349	349	103	103		249	249	37	37					
33.8	34.2	5	1	231	418	231	44	34	140	310	140	0	87				
			2	363	363	99	99		257	257	38	38					
38.3	38.7	5	1	235	437	235	34	36	144	321	144	0	95				
			2	378	378	93	93		277	277	134	134					
42.8	43.2	10	1	252	470	252	35	37	222	365	222	80	102				
			2	406	406	99	99		323	323	122	122					
47.3	47.7	15	1	270	504	270	35	39	240	429	240	50	110				
			2	436	436	103	103		373	373	106	106					
51.8	52.2	25	1	299	553	299	45	40	269	510	269	28	118				
			2	479	479	119	119		439	439	99	99					
56.3	56.7	35	1	329	604	329	53	42	299	597	299	1	125				
			2	524	524	134	134		509	509	88	88					
60.8	61.2	45	1	361	658	361	63	44	300	723	300	0	135				
			2	571	571	150	150		586	586	75	75					
65.3	65.7	55	1	393	714	393	72	46	294	863	294	0	145				
			2	620	620	166	166		668	668	57	57					
69.8	70.2	70	1	437	784	437	90	47	305	1019	305	0	155				
			2	683	683	192	192		768	768	47	47					

12.2.50 Slewing section with 35 m Jib on KR 1000-8

Tower crane without climbing frame

☒ Stationary

☐ Mobile

Size across corners: 8.0 m x 8.0 m

Hook height		Central ballast	Jib position	Crane in service Slewing torque: 280 kNm				Horizontal load	Crane out of service Wind region: C25				Horizontal load				
				Corner loads					Corner loads								
				A	B	C	D		A	B	C	D					
[m]	[m]	[t]		[kN]	[kN]	[kN]	[kN]	[kN]	[kN]	[kN]	[kN]	[kN]	[kN]				
6.8	7.2	5	1	202	336	202	67	25	102	267	102	0	43				
			2	297	297	107	107		221	221	123	123					
11.3	11.7	5	1	209	352	209	66	27	114	272	114	0	52				
			2	310	310	108	108		221	221	28	28					
15.8	16.2	5	1	213	365	213	62	28	120	277	120	0	59				
			2	321	321	106	106		228	228	31	31					
20.3	20.7	5	1	218	380	218	56	30	126	284	126	0	66				
			2	332	332	104	104		234	234	33	33					
24.8	25.2	5	1	223	395	223	50	31	131	292	131	0	73				
			2	345	345	100	100		242	242	35	35					
29.3	29.7	5	1	227	412	227	42	33	136	300	136	0	80				
			2	358	358	96	96		249	249	37	37					
33.8	34.2	5	1	232	430	232	33	34	140	310	140	0	88				
			2	372	372	91	91		257	257	147	147					
38.3	38.7	5	1	236	449	236	23	36	206	321	206	91	95				
			2	387	387	86	86		288	288	125	125					
42.8	43.2	5	1	241	470	241	11	37	211	368	211	53	103				
			2	403	403	79	79		322	322	99	99					
47.3	47.7	10	1	258	505	258	10	39	228	432	228	24	110				
			2	433	433	83	83		372	372	83	83					
51.8	52.2	20	1	287	555	287	20	40	257	514	257	1	118				
			2	476	476	98	98		439	439	76	76					
56.3	56.7	30	1	317	606	317	28	42	260	628	260	0	126				
			2	521	521	112	112		509	509	65	65					
60.8	61.2	40	1	349	660	349	38	44	260	756	260	0	135				
			2	569	569	129	129		586	586	51	51					
65.3	65.7	55	1	394	729	394	58	46	278	898	278	0	145				
			2	631	631	156	156		681	681	46	46					
69.8	70.2	75	1	451	812	451	89	48	314	1055	314	0	155				
			2	706	706	195	195		794	794	47	47					

12.2.51 Slewing section with 37.5 m Jib on KR 1000-8

Tower crane without climbing frame

☒ Stationary

☐ Mobile

Size across corners: 8.0 m x 8.0 m

Hook height [m]	Central ballast [t]	Jib position	Crane in service Slewing torque: 280 kNm				Horizontal load [kN]	Crane out of service Wind region: C25				Horizontal load [kN]		
			Corner loads					Corner loads						
			A [kN]	B [kN]	C [kN]	D [kN]		A [kN]	B [kN]	C [kN]	D [kN]			
6.8	7.2	5	1	203	340	203	66	25	102	267	102	0	43	
			2	300	300	106	106		217	217	129	129		
11.3	11.7	5	1	210	356	210	64	27	114	272	114	0	52	
			2	313	313	107	107		221	221	28	28		
15.8	16.2	5	1	215	369	215	60	28	120	278	120	0	59	
			2	324	324	105	105		228	228	31	31		
20.3	20.7	5	1	219	384	219	54	30	126	284	126	0	66	
			2	336	336	103	103		235	235	33	33		
24.8	25.2	5	1	224	400	224	48	31	131	292	131	0	73	
			2	348	348	99	99		242	242	35	35		
29.3	29.7	5	1	228	416	228	40	33	136	301	136	0	80	
			2	361	361	95	95		249	249	37	37		
33.8	34.2	5	1	233	434	233	31	34	140	310	140	0	88	
			2	375	375	90	90		264	264	142	142		
38.3	38.7	5	1	237	454	237	21	36	207	332	207	83	95	
			2	390	390	84	84		295	295	119	119		
42.8	43.2	5	1	242	475	242	9	37	212	379	212	45	103	
			2	407	407	77	77		330	330	94	94		
47.3	47.7	10	1	259	510	259	8	39	229	443	229	15	111	
			2	436	436	82	82		380	380	78	78		
51.8	52.2	20	1	289	560	289	17	40	251	533	251	0	118	
			2	480	480	97	97		447	447	70	70		
56.3	56.7	25	1	306	599	306	12	42	226	650	226	0	126	
			2	513	513	98	98		505	505	46	46		
60.8	61.2	40	1	350	666	350	35	44	251	779	251	0	136	
			2	573	573	127	127		596	596	45	45		
65.3	65.7	60	1	407	747	407	67	46	294	922	294	0	145	
			2	647	647	167	167		703	703	51	51		
69.8	70.2	80	1	464	831	464	98	48	329	1080	329	0	155	
			2	723	723	205	205		816	816	52	52		

12.2.52 Slewing section with 40 m Jib on KR 1000-8

Tower crane without climbing frame

☒ Stationary

☐ Mobile

Size across corners: 8.0 m x 8.0 m

Hook height [m]	Central ballast [t]	Jib position	Crane in service Slewing torque: 280 kNm				Horizontal load [kN]	Crane out of service Wind region: C25				Horizontal load [kN]		
			Corner loads					Corner loads						
			A [kN]	B [kN]	C [kN]	D [kN]		A [kN]	B [kN]	C [kN]	D [kN]			
6.8	7.2	5	1	210	334	210	86	25	102	267	102	0	44	
			2	297	297	123	123		231	231	129	129		
11.3	11.7	5	1	217	349	217	85	27	114	272	114	0	52	
			2	310	310	124	124		225	225	149	149		
15.8	16.2	5	1	222	363	222	81	28	120	278	120	0	59	
			2	321	321	122	122		228	228	31	31		
20.3	20.7	5	1	226	377	226	75	30	126	284	126	0	66	
			2	333	333	119	119		235	235	33	33		
24.8	25.2	5	1	231	393	231	69	31	131	292	131	0	74	
			2	345	345	116	116		242	242	35	35		
29.3	29.7	5	1	235	409	235	61	33	136	301	136	0	81	
			2	358	358	112	112		249	249	36	36		
33.8	34.2	5	1	240	427	240	52	34	140	311	140	0	88	
			2	372	372	107	107		265	265	155	155		
38.3	38.7	5	1	244	447	244	42	36	214	330	214	99	96	
			2	387	387	101	101		296	296	133	133		
42.8	43.2	5	1	249	467	249	31	37	219	377	219	61	103	
			2	403	403	95	95		331	331	107	107		
47.3	47.7	10	1	266	502	266	30	39	236	441	236	31	111	
			2	433	433	99	99		381	381	91	91		
51.8	52.2	20	1	296	552	296	39	40	266	524	266	8	119	
			2	477	477	114	114		448	448	83	83		
56.3	56.7	30	1	325	604	325	46	42	274	633	274	0	127	
			2	522	522	128	128		519	519	71	71		
60.8	61.2	40	1	357	658	357	56	44	273	763	273	0	136	
			2	570	570	145	145		597	597	57	57		
65.3	65.7	55	1	402	727	402	77	46	290	907	290	0	146	
			2	632	632	172	172		693	693	51	51		
69.8	70.2	75	1	459	811	459	107	48	325	1067	325	0	156	
			2	708	708	210	210		806	806	52	52		

12.2.53 Slewing section with 42.5 m Jib on KR 1000-8

Tower crane without climbing frame

☒ Stationary

☐ Mobile

Size across corners: 8.0 m x 8.0 m

Hook height [m]	Central ballast [t]	Jib position	Crane in service Slewing torque: 280 kNm				Horizontal load [kN]	Crane out of service Wind region: C25				Horizontal load [kN]		
			Corner loads					Corner loads						
			A [kN]	B [kN]	C [kN]	D [kN]		A [kN]	B [kN]	C [kN]	D [kN]			
6.8	7.2	5	1	211	343	211	80	25	102	267	102	0	44	
			2	304	304	118	118		222	222	141	141		
11.3	11.7	5	1	218	358	218	78	27	114	272	114	0	53	
			2	317	317	119	119		221	221	28	28		
15.8	16.2	5	1	223	372	223	74	28	120	278	120	0	60	
			2	328	328	117	117		228	228	31	31		
20.3	20.7	5	1	227	387	227	68	30	126	285	126	0	67	
			2	340	340	115	115		235	235	33	33		
24.8	25.2	5	1	232	402	232	62	31	131	292	131	0	74	
			2	352	352	112	112		242	242	35	35		
29.3	29.7	5	1	237	419	237	54	33	136	301	136	0	81	
			2	366	366	107	107		250	250	36	36		
33.8	34.2	5	1	241	437	241	45	34	140	311	140	0	89	
			2	380	380	102	102		277	277	145	145		
38.3	38.7	5	1	246	457	246	35	36	216	347	216	84	96	
			2	395	395	96	96		309	309	123	123		
42.8	43.2	10	1	263	490	263	35	37	233	407	233	58	104	
			2	424	424	102	102		356	356	109	109		
47.3	47.7	10	1	267	513	267	21	39	237	460	237	15	111	
			2	441	441	93	93		395	395	80	80		
51.8	52.2	15	1	284	551	284	18	40	233	552	233	0	119	
			2	473	473	96	96		449	449	59	59		
56.3	56.7	25	1	314	603	314	25	42	232	671	232	0	127	
			2	518	518	109	109		521	521	46	46		
60.8	61.2	40	1	358	670	358	47	44	256	802	256	0	137	
			2	579	579	138	138		612	612	45	45		
65.3	65.7	60	1	415	752	415	79	46	297	947	297	0	146	
			2	653	653	178	178		721	721	50	50		
69.8	70.2	80	1	473	836	473	109	48	331	1109	331	0	156	
			2	729	729	216	216		835	835	50	50		

12.2.54 Slewing section with 45 m Jib on KR 1000-8

Tower crane without climbing frame

☒ Stationary

☐ Mobile

Size across corners: 8.0 m x 8.0 m

Hook height [m]	Central ballast [t]	Jib position	Crane in service Slewing torque: 280 kNm				Horizontal load [kN]	Crane out of service Wind region: C25				Horizontal load [kN]		
			Corner loads					Corner loads						
			A [kN]	B [kN]	C [kN]	D [kN]		A [kN]	B [kN]	C [kN]	D [kN]			
6.8	7.2	5	1	189	336	189	41	25	102	267	102	0	44	
			2	301	301	136	136		234	234	143	143		
11.3	11.7	5	1	226	351	226	101	27	114	272	114	0	53	
			2	314	314	138	138		229	229	163	163		
15.8	16.2	5	1	230	364	230	97	28	120	278	120	0	60	
			2	325	325	136	136		228	228	31	31		
20.3	20.7	5	1	235	379	235	91	30	126	285	126	0	67	
			2	336	336	133	133		235	235	33	33		
24.8	25.2	5	1	239	394	239	85	31	131	293	131	0	74	
			2	349	349	130	130		242	242	35	35		
29.3	29.7	5	1	244	411	244	77	33	135	301	135	0	82	
			2	362	362	126	126		251	251	177	177		
33.8	34.2	5	1	249	429	249	68	34	140	311	140	0	89	
			2	376	376	121	121		280	280	157	157		
38.3	38.7	5	1	253	448	253	58	36	223	349	223	97	96	
			2	391	391	115	115		312	312	134	134		
42.8	43.2	10	1	270	482	270	59	37	240	409	240	71	104	
			2	420	420	121	121		360	360	121	121		
47.3	47.7	10	1	275	504	275	45	39	245	462	245	27	112	
			2	437	437	112	112		398	398	91	91		
51.8	52.2	15	1	292	542	292	42	40	253	542	253	0	120	
			2	468	468	115	115		453	453	70	70		
56.3	56.7	25	1	321	594	321	49	42	252	662	252	0	127	
			2	514	514	129	129		526	526	57	57		
60.8	61.2	35	1	353	648	353	59	44	250	794	250	0	137	
			2	562	562	145	145		604	604	42	42		
65.3	65.7	55	1	410	730	410	91	46	290	941	290	0	147	
			2	636	636	185	185		713	713	47	47		
69.8	70.2	75	1	468	814	468	121	48	323	1105	323	0	157	
			2	713	713	222	222		828	828	47	47		

12.2.55 Slewing section with 47.5 m Jib on KR 1000-8

Tower crane without climbing frame

☒ Stationary

☐ Mobile

Size across corners: 8.0 m x 8.0 m

Hook height [m]	Central ballast [t]	Jib position	Crane in service Slewing torque: 280 kNm				Horizontal load [kN]	Crane out of service Wind region: C25				Horizontal load [kN]		
			Corner loads					Corner loads						
			A [kN]	B [kN]	C [kN]	D [kN]		A [kN]	B [kN]	C [kN]	D [kN]			
6.8	7.2	5	1	219	339	219	99	25	102	267	102	0	45	
			2	304	304	134	134		228	228	150	150		
11.3	11.7	5	1	226	355	226	97	27	113	273	113	0	53	
			2	317	317	135	135		222	222	170	170		
15.8	16.2	5	1	231	368	231	93	29	120	278	120	0	60	
			2	328	328	133	133		228	228	31	31		
20.3	20.7	5	1	235	383	235	88	30	125	285	125	0	67	
			2	340	340	131	131		235	235	33	33		
24.8	25.2	5	1	240	399	240	81	32	131	293	131	0	75	
			2	352	352	128	128		242	242	35	35		
29.3	29.7	5	1	244	415	244	73	33	135	302	135	0	82	
			2	365	365	123	123		259	259	170	170		
33.8	34.2	5	1	249	434	249	64	35	219	317	219	121	89	
			2	379	379	118	118		288	288	150	150		
38.3	38.7	5	1	253	453	253	54	36	223	360	223	87	97	
			2	395	395	112	112		320	320	127	127		
42.8	43.2	10	1	271	487	271	54	38	241	421	241	60	104	
			2	423	423	118	118		368	368	113	113		
47.3	47.7	10	1	275	510	275	41	39	245	474	245	16	112	
			2	441	441	109	109		407	407	83	83		
51.8	52.2	10	1	280	534	280	25	41	216	566	216	0	120	
			2	460	460	99	99		450	450	49	49		
56.3	56.7	20	1	309	587	309	32	42	215	688	215	0	128	
			2	505	505	113	113		522	522	36	36		
60.8	61.2	40	1	366	666	366	66	44	262	821	262	0	137	
			2	578	578	154	154		627	627	46	46		
65.3	65.7	60	1	423	748	423	98	46	302	969	302	0	147	
			2	653	653	194	194		736	736	51	51		
69.8	70.2	80	1	480	833	480	128	48	334	1133	334	0	157	
			2	730	730	231	231		851	851	50	50		

12.2.56 Slewing section with 50 m Jib on KR 1000-8

Tower crane without climbing frame

☒ Stationary

☐ Mobile

Size across corners: 8.0 m x 8.0 m

Hook height [m]	Central ballast [t]	Jib position	Crane in service Slewing torque: 280 kNm				Horizontal load [kN]	Crane out of service Wind region: C25				Horizontal load [kN]		
			Corner loads					Corner loads						
			A [kN]	B [kN]	C [kN]	D [kN]		A [kN]	B [kN]	C [kN]	D [kN]			
6.8	7.2	5	1	219	339	219	100	25	102	267	102	0	45	
			2	304	304	135	135		222	222	157	157		
11.3	11.7	5	1	226	355	226	98	27	113	273	113	0	54	
			2	317	317	136	136		221	221	28	28		
15.8	16.2	5	1	231	368	231	94	29	120	278	120	0	61	
			2	328	328	134	134		228	228	31	31		
20.3	20.7	5	1	236	383	236	88	30	125	285	125	0	68	
			2	340	340	132	132		235	235	33	33		
24.8	25.2	5	1	240	398	240	82	32	131	293	131	0	75	
			2	352	352	128	128		242	242	35	35		
29.3	29.7	5	1	245	415	245	74	33	135	302	135	0	82	
			2	365	365	124	124		266	266	163	163		
33.8	34.2	5	1	249	433	249	65	35	219	327	219	112	90	
			2	379	379	119	119		295	295	143	143		
38.3	38.7	5	1	254	453	254	55	36	224	370	224	77	97	
			2	394	394	113	113		327	327	120	120		
42.8	43.2	10	1	271	486	271	55	38	241	431	241	50	105	
			2	423	423	118	118		376	376	106	106		
47.3	47.7	10	1	275	509	275	41	39	245	485	245	6	112	
			2	441	441	110	110		415	415	76	76		
51.8	52.2	10	1	280	534	280	26	41	206	588	206	0	120	
			2	460	460	100	100		458	458	42	42		
56.3	56.7	25	1	322	599	322	45	42	229	711	229	0	128	
			2	518	518	126	126		543	543	41	41		
60.8	61.2	40	1	367	666	367	67	44	251	845	251	0	138	
			2	578	578	155	155		635	635	38	38		
65.3	65.7	60	1	424	748	424	99	46	291	994	291	0	147	
			2	653	653	194	194		745	745	42	42		
69.8	70.2	85	1	493	845	493	141	48	347	1160	347	0	157	
			2	742	742	244	244		873	873	53	53		

12.2.57 Slewing section with 52.5 m Jib on KR 1000-8

Tower crane without climbing frame

☒ Stationary

☐ Mobile

Size across corners: 8.0 m x 8.0 m

Hook height		Central ballast	Jib position	Crane in service Slewing torque: 280 kNm				Horizontal load	Crane out of service Wind region: C25				Horizontal load				
				Corner loads					Corner loads								
				A	B	C	D		A	B	C	D					
[m]	[m]	[t]		[kN]	[kN]	[kN]	[kN]	[kN]	[kN]	[kN]	[kN]	[kN]	[kN]				
6.8	7.2	5	1	197	339	197	55	25	102	267	102	0	45				
			2	303	303	152	152		232	232	162	162					
11.3	11.7	5	1	204	354	204	55	27	113	273	113	0	54				
			2	316	316	153	153		226	226	182	182					
15.8	16.2	5	1	209	366	209	52	29	119	279	119	0	61				
			2	327	327	151	151		228	228	31	31					
20.3	20.7	5	1	214	379	214	48	30	125	286	125	0	68				
			2	338	338	149	149		235	235	33	33					
24.8	25.2	5	1	218	394	218	43	32	130	293	130	0	76				
			2	351	351	146	146		246	246	190	190					
29.3	29.7	5	1	253	410	253	95	33	135	302	135	0	83				
			2	364	364	141	141		273	273	172	172					
33.8	34.2	5	1	257	428	257	86	35	227	334	227	121	90				
			2	378	378	136	136		302	302	152	152					
38.3	38.7	10	1	274	460	274	89	36	244	390	244	98	98				
			2	405	405	143	143		347	347	141	141					
42.8	43.2	10	1	279	481	279	77	38	249	439	249	58	105				
			2	422	422	136	136		383	383	114	114					
47.3	47.7	10	1	283	504	283	63	39	253	494	253	13	113				
			2	439	439	128	128		423	423	83	83					
51.8	52.2	10	1	288	529	288	47	41	220	591	220	0	121				
			2	458	458	118	118		467	467	49	49					
56.3	56.7	20	1	317	581	317	54	42	217	715	217	0	129				
			2	504	504	131	131		540	540	34	34					
60.8	61.2	40	1	375	660	375	89	44	264	851	264	0	139				
			2	577	577	172	172		646	646	43	43					
65.3	65.7	60	1	432	742	432	121	46	302	1003	302	0	148				
			2	651	651	212	212		756	756	47	47					
69.8	70.2	85	1	501	840	501	163	48	357	1171	357	0	158				
			2	740	740	262	262		885	885	57	57					

12.2.58 Slewing section with 55 m Jib on KR 1000-8

Tower crane without climbing frame

☒ Stationary

☐ Mobile

Size across corners: 8.0 m x 8.0 m

Hook height		Central ballast	Jib position	Crane in service Slewing torque: 280 kNm				Horizontal load	Crane out of service Wind region: C25				Horizontal load				
				Corner loads					Corner loads								
				A	B	C	D		A	B	C	D					
[m]	[m]	[t]		[kN]	[kN]	[kN]	[kN]	[kN]	[kN]	[kN]	[kN]	[kN]	[kN]				
6.8	7.2	5	1	228	345	228	112	25	102	267	102	0	45				
			2	310	310	146	146		221	221	175	175					
11.3	11.7	5	1	235	360	235	110	27	113	273	113	0	54				
			2	324	324	147	147		224	224	76	76					
15.8	16.2	5	1	240	374	240	106	29	119	279	119	0	61				
			2	335	335	145	145		231	231	79	79					
20.3	20.7	5	1	244	388	244	100	30	125	286	125	0	68				
			2	346	346	142	142		238	238	81	81					
24.8	25.2	5	1	249	404	249	93	32	130	293	130	0	76				
			2	359	359	139	139		259	259	179	179					
29.3	29.7	5	1	253	421	253	86	33	223	312	223	135	83				
			2	372	372	135	135		286	286	161	161					
33.8	34.2	5	1	258	439	258	76	35	228	352	228	104	90				
			2	386	386	130	130		315	315	141	141					
38.3	38.7	10	1	275	472	275	78	36	245	409	245	81	98				
			2	414	414	136	136		361	361	129	129					
42.8	43.2	10	1	280	493	280	66	38	250	458	250	41	105				
			2	430	430	129	129		397	397	102	102					
47.3	47.7	10	1	284	516	284	52	39	250	517	250	0	113				
			2	448	448	120	120		437	437	71	71					
51.8	52.2	15	1	301	554	301	48	41	228	629	228	0	121				
			2	480	480	122	122		494	494	49	49					
56.3	56.7	25	1	331	607	331	54	42	224	754	224	0	129				
			2	526	526	135	135		568	568	34	34					
60.8	61.2	45	1	388	687	388	89	44	270	892	270	0	139				
			2	599	599	176	176		673	673	42	42					
65.3	65.7	65	1	445	769	445	120	46	308	1044	308	0	148				
			2	674	674	215	215		784	784	45	45					
69.8	70.2	90	1	514	867	514	162	48	362	1214	362	0	158				
			2	764	764	265	265		914	914	55	55					

12.2.59 Slewing section with 57.5 m Jib on KR 1000-8

Tower crane without climbing frame

☒ Stationary

☐ Mobile

Size across corners: 8.0 m x 8.0 m

Hook height [m]	Central ballast [t]	Jib position	Crane in service Slewing torque: 280 kNm				Horizontal load [kN]	Crane out of service Wind region: C25				Horizontal load [kN]		
			Corner loads					Corner loads						
			A [kN]	B [kN]	C [kN]	D [kN]		A [kN]	B [kN]	C [kN]	D [kN]			
6.8	7.2	5	1	228	336	228	120	25	102	268	102	0	46	
			2	304	304	152	152		221	221	175	175		
11.3	11.7	5	1	235	351	235	118	27	113	273	113	0	55	
			2	317	317	153	153		222	222	78	78		
15.8	16.2	5	1	239	365	239	114	29	119	279	119	0	62	
			2	328	328	151	151		229	229	81	81		
20.3	20.7	5	1	244	380	244	108	30	125	286	125	0	69	
			2	340	340	148	148		236	236	83	83		
24.8	25.2	5	1	249	395	249	102	32	130	294	130	0	76	
			2	352	352	145	145		259	259	178	178		
29.3	29.7	5	1	253	412	253	94	33	223	312	223	134	83	
			2	366	366	141	141		286	286	160	160		
33.8	34.2	5	1	258	430	258	85	35	228	352	228	103	91	
			2	380	380	136	136		316	316	140	140		
38.3	38.7	10	1	275	462	275	87	36	245	409	245	80	98	
			2	407	407	142	142		361	361	128	128		
42.8	43.2	10	1	279	483	279	75	38	249	459	249	40	106	
			2	424	424	135	135		398	398	101	101		
47.3	47.7	10	1	284	506	284	61	39	248	520	248	0	114	
			2	441	441	127	127		438	438	70	70		
51.8	52.2	10	1	288	531	288	45	41	201	632	201	0	121	
			2	460	460	117	117		482	482	35	35		
56.3	56.7	25	1	330	596	330	65	42	222	758	222	0	129	
			2	518	518	143	143		569	569	32	32		
60.8	61.2	45	1	388	676	388	99	44	267	896	267	0	139	
			2	591	591	184	184		674	674	41	41		
65.3	65.7	65	1	445	758	445	131	46	305	1049	305	0	149	
			2	666	666	223	223		786	786	44	44		
69.8	70.2	90	1	514	855	514	173	48	359	1219	359	0	159	
			2	755	755	273	273		915	915	53	53		

12.2.60 Slewing section with 60 m Jib on KR 1000-8

Tower crane without climbing frame

☒ Stationary

☐ Mobile

Size across corners: 8.0 m x 8.0 m

Hook height [m]	Central ballast [t]	Jib position	Crane in service Slewing torque: 280 kNm				Horizontal load [kN]	Crane out of service Wind region: C25				Horizontal load [kN]		
			Corner loads					Corner loads						
			A [kN]	B [kN]	C [kN]	D [kN]		A [kN]	B [kN]	C [kN]	D [kN]			
6.8	7.2	5	1	228	339	228	117	25	102	268	102	0	46	
			2	306	306	150	150		220	220	67	67		
11.3	11.7	5	1	235	355	235	116	27	113	273	113	0	55	
			2	320	320	151	151		229	229	72	72		
15.8	16.2	5	1	240	368	240	111	29	119	279	119	0	62	
			2	331	331	149	149		236	236	74	74		
20.3	20.7	5	1	244	383	244	106	30	125	286	125	0	69	
			2	342	342	146	146		244	244	184	184		
24.8	25.2	5	1	249	399	249	99	32	130	294	130	0	76	
			2	355	355	143	143		269	269	169	169		
29.3	29.7	5	1	253	416	253	91	33	223	326	223	121	84	
			2	368	368	139	139		296	296	151	151		
33.8	34.2	5	1	258	434	258	82	35	228	366	228	90	91	
			2	382	382	134	134		326	326	130	130		
38.3	38.7	10	1	275	466	275	84	36	245	424	245	66	99	
			2	410	410	140	140		372	372	119	119		
42.8	43.2	10	1	280	487	280	72	38	250	474	250	25	106	
			2	426	426	133	133		408	408	91	91		
47.3	47.7	10	1	284	510	284	58	39	233	550	233	0	114	
			2	444	444	124	124		449	449	59	59		
51.8	52.2	15	1	301	548	301	55	41	210	664	210	0	122	
			2	476	476	127	127		506	506	36	36		
56.3	56.7	30	1	343	613	343	74	42	231	792	231	0	130	
			2	534	534	153	153		593	593	33	33		
60.8	61.2	50	1	400	693	400	108	44	276	931	276	0	139	
			2	607	607	193	193		699	699	41	41		
65.3	65.7	70	1	457	775	457	140	46	312	1085	312	0	149	
			2	682	682	233	233		811	811	44	44		
69.8	70.2	95	1	527	873	527	181	48	366	1257	366	0	159	
			2	771	771	282	282		942	942	52	52		

12.2.61 Slewing section with 62.5 m Jib on KR 1000-8

Tower crane without climbing frame

☒ Stationary

☐ Mobile

Size across corners: 8.0 m x 8.0 m

Hook height [m]	Central ballast [t]	Jib position	Crane in service Slewing torque: 280 kNm				Horizontal load [kN]	Crane out of service Wind region: C25				Horizontal load [kN]		
			Corner loads					Corner loads						
			A [kN]	B [kN]	C [kN]	D [kN]		A [kN]	B [kN]	C [kN]	D [kN]			
6.8	7.2	5	1	206	332	206	80	25	140	298	140	0	46	
			2	302	302	170	170		250	250	39	39		
11.3	11.7	5	1	213	347	213	80	27	152	304	152	0	55	
			2	315	315	171	171		259	259	44	44		
15.8	16.2	5	1	218	359	218	76	29	156	311	156	1	62	
			2	326	326	170	170		266	266	46	46		
20.3	20.7	5	1	252	373	252	132	30	161	320	161	2	69	
			2	338	338	167	167		273	273	48	48		
24.8	25.2	5	1	257	388	257	125	32	165	329	165	2	77	
			2	350	350	164	164		281	281	50	50		
29.3	29.7	5	1	261	405	261	118	33	170	338	170	2	84	
			2	363	363	160	160		303	303	159	159		
33.8	34.2	10	1	278	436	278	121	35	248	387	248	110	91	
			2	390	390	167	167		346	346	151	151		
38.3	38.7	10	1	283	455	283	111	36	253	432	253	74	99	
			2	405	405	161	161		380	380	126	126		
42.8	43.2	10	1	288	476	288	99	38	258	482	258	33	107	
			2	421	421	154	154		417	417	98	98		
47.3	47.7	10	1	292	499	292	85	39	248	552	248	0	114	
			2	438	438	146	146		458	458	67	67		
51.8	52.2	15	1	309	536	309	82	41	225	668	225	0	122	
			2	470	470	149	149		515	515	43	43		
56.3	56.7	30	1	351	601	351	102	42	244	797	244	0	130	
			2	528	528	175	175		603	603	39	39		
60.8	61.2	50	1	408	680	408	136	44	288	937	288	0	140	
			2	601	601	216	216		710	710	47	47		
65.3	65.7	70	1	465	762	465	168	46	324	1094	324	0	150	
			2	675	675	255	255		822	822	48	48		
69.8	70.2	95	1	535	860	535	210	48	376	1269	376	0	160	
			2	765	765	305	305		954	954	56	56		

12.2.62 Slewing section with 65 m Jib on KR 1000-8

Tower crane without climbing frame

☒ Stationary

☐ Mobile

Size across corners: 8.0 m x 8.0 m

Hook height [m]	Central ballast [t]	Jib position	Crane in service Slewing torque: 280 kNm				Horizontal load [kN]	Crane out of service Wind region: C25				Horizontal load [kN]		
			Corner loads					Corner loads						
			A [kN]	B [kN]	C [kN]	D [kN]		A [kN]	B [kN]	C [kN]	D [kN]			
6.8	7.2	10	1	249	344	249	155	25	150	332	150	0	47	
			2	316	316	182	182		275	275	40	40		
11.3	11.7	10	1	256	360	256	153	27	161	338	161	0	56	
			2	329	329	183	183		284	284	45	45		
15.8	16.2	10	1	261	373	261	149	29	167	344	167	0	63	
			2	340	340	182	182		291	291	48	48		
20.3	20.7	10	1	266	388	266	143	30	172	352	172	0	70	
			2	352	352	179	179		298	298	50	50		
24.8	25.2	10	1	270	404	270	137	32	177	360	177	0	77	
			2	364	364	176	176		306	306	51	51		
29.3	29.7	10	1	275	420	275	129	33	181	371	181	0	84	
			2	378	378	172	172		332	332	158	158		
33.8	34.2	10	1	279	438	279	120	35	249	409	249	89	92	
			2	392	392	167	167		362	362	136	136		
38.3	38.7	15	1	296	470	296	122	36	266	468	266	65	99	
			2	419	419	173	173		409	409	124	124		
42.8	43.2	15	1	301	491	301	110	38	271	519	271	23	107	
			2	436	436	166	166		446	446	95	95		
47.3	47.7	20	1	318	527	318	109	39	276	600	276	0	115	
			2	466	466	170	170		500	500	75	75		
51.8	52.2	20	1	322	552	322	93	41	226	717	226	0	123	
			2	485	485	160	160		546	546	39	39		
56.3	56.7	35	1	364	617	364	112	42	245	849	245	0	131	
			2	543	543	186	186		635	635	34	34		
60.8	61.2	55	1	422	696	422	147	44	288	991	288	0	140	
			2	616	616	227	227		742	742	41	41		
65.3	65.7	80	1	491	791	491	191	46	348	1150	348	0	150	
			2	703	703	279	279		868	868	54	54		
69.8	70.2	105	1	561	889	561	233	48	398	1327	398	0	160	
			2	793	793	329	329		1000	1000	61	61		

12.2.63 Slewing section with 30 m Jib on KR 16-80

Tower crane without climbing frame

☒ Stationary☐ Mobile

Size across corners: 8.0 m x 8.0 m

12.2.64 Slewing section with 32.5 m Jib on KR 16-80

Tower crane without climbing frame

☒ Stationary☐ Mobile

Size across corners: 8.0 m x 8.0 m

12.2.65 Slewing section with 35 m Jib on KR 16-80

Tower crane without climbing frame

- ☒ Stationary
 - ☐ Mobile

Size across corners: 8.0 m x 8.0 m

12.2.66 Slewing section with 37.5 m Jib on KR 16-80

Tower crane without climbing frame

- ☒ Stationary
 - ☐ Mobile

Size across corners: 8.0 m x 8.0 m

12.2.67 Slewing section with 40 m Jib on KR 16-80

Tower crane without climbing frame

- ☒ Stationary
☐ Mobile

Size across corners: 8.0 m x 8.0 m

12.2.68 Slewing section with 42.5 m Jib on KR 16-80

Tower crane without climbing frame

- ☒ Stationary
 - ☐ Mobile

Size across corners: 8.0 m x 8.0 m

12.2.69 Slewing section with 45 m Jib on KR 16-80

Tower crane without climbing frame

- ☒ Stationary
 - ☐ Mobile

Size across corners: 8.0 m x 8.0 m

12.2.70 Slewing section with 47.5 m Jib on KR 16-80

Tower crane without climbing frame

- ☒ Stationary
 - ☐ Mobile

Size across corners: 8.0 m x 8.0 m

12.2.71 Slewing section with 50 m Jib on KR 16-80

Tower crane without climbing frame

- ☒ Stationary
☐ Mobile

Size across corners: 8.0 m x 8.0 m

12.2.72 Slewing section with 52.5 m Jib on KR 16-80

Tower crane without climbing frame

- ☒ Stationary
☐ Mobile

Size across corners: 8.0 m x 8.0 m

12.2.73 Slewing section with 55 m Jib on KR 16-80

Tower crane without climbing frame

- ☒ Stationary
☐ Mobile

Size across corners: 8.0 m x 8.0 m

12.2.74 Slewing section with 57.5 m Jib on KR 16-80

Tower crane without climbing frame

- ☒ Stationary
 - ☐ Mobile

Size across corners: 8.0 m x 8.0 m

12.2.75 Slewing section with 60 m Jib on KR 16-80

Tower crane without climbing frame

☒ Stationary☐ Mobile

Size across corners: 8.0 m x 8.0 m

12.2.76 Slewing section with 62.5 m Jib on KR 16-80

Tower crane without climbing frame

☒ Stationary☐ Mobile

Size across corners: 8.0 m x 8.0 m

[illegible]

12.2.77 Slewing section with 65 m Jib on KR 16-80

Tower crane without climbing frame

- ☒ Stationary
☐ Mobile

Size across corners: 8.0 m x 8.0 m

12.2.78 Slewing section with 30 m Jib on KR 16-80/100

Tower crane without climbing frame

- ☒ Stationary
☐ Mobile

Size across corners: 10.0 m x 10.0 m

12.2.79 Slewing section with 32.5 m Jib on KR 16-80/100

Tower crane without climbing frame

- ☒ Stationary
 - ☐ Mobile

Size across corners: 10.0 m x 10.0 m

12.2.80 Slewing section with 35 m Jib on KR 16-80/100

Tower crane without climbing frame

- ☒ Stationary
 - ☐ Mobile

Size across corners: 10.0 m x 10.0 m

12.2.81 Slewing section with 37.5 m Jib on KR 16-80/100

Tower crane without climbing frame

- ☒ Stationary
☐ Mobile

Size across corners: 10.0 m x 10.0 m

12.2.82 Slewing section with 40 m Jib on KR 16-80/100

Tower crane without climbing frame

- ☒ Stationary
 - ☐ Mobile

Size across corners: 10.0 m x 10.0 m

[illegible]

12.2.83 Slewing section with 42.5 m Jib on KR 16-80/100

Tower crane without climbing frame

- ☒ Stationary
☐ Mobile

Size across corners: 10.0 m x 10.0 m

12.2.84 Slewing section with 45 m Jib on KR 16-80/100

Tower crane without climbing frame

- ☒ Stationary
 - ☐ Mobile

Size across corners: 10.0 m x 10.0 m

[illegible]

12.2.85 Slewing section with 47.5 m Jib on KR 16-80/100

Tower crane without climbing frame

☒ Stationary☐ Mobile

Size across corners: 10.0 m x 10.0 m

12.2.86 Slewing section with 50 m Jib on KR 16-80/100

Tower crane without climbing frame

☒ Stationary☐ Mobile

Size across corners: 10.0 m x 10.0 m

[illegible]

12.2.87 Slewing section with 52.5 m Jib on KR 16-80/100

Tower crane without climbing frame

☒ Stationary☐ Mobile

Size across corners: 10.0 m x 10.0 m

12.2.88 Slewing section with 55 m Jib on KR 16-80/100

Tower crane without climbing frame

☒ Stationary☐ Mobile

Size across corners: 10.0 m x 10.0 m

12.2.89 Slewing section with 57.5 m Jib on KR 16-80/100

Tower crane without climbing frame

☒ Stationary☐ Mobile

Size across corners: 10.0 m x 10.0 m

12.2.90 Slewing section with 60 m Jib on KR 16-80/100

Tower crane without climbing frame

☒ Stationary☐ Mobile

Size across corners: 10.0 m x 10.0 m

12.2.91 Slewing section with 62.5 m Jib on KR 16-80/100

Tower crane without climbing frame

☒ Stationary☐ Mobile

Size across corners: 10.0 m x 10.0 m

[illegible]

12.2.92 Slewing section with 65 m Jib on KR 16-80/100

Tower crane without climbing frame

☒ Stationary☐ Mobile

Size across corners: 10.0 m x 10.0 m

[illegible]

12.2.93 Slewing section with 30 m Jib on KRE 260.1 (5.0m x 6.79m)

Tower crane without climbing frame

- ☒ Stationary
 - ☐ Mobile

Size across corners: 5.0 m x 6.79 m

12.2.94 Slewing section with 32.5 m Jib on KRE 260.1 (5.0m x 6.79m)

Tower crane without climbing frame

- ☒ Stationary
 - ☐ Mobile

Size across corners: 5.0 m x 6.79 m

12.2.95 Slewing section with 35 m Jib on KRE 260.1 (5.0m x 6.79m)

Tower crane without climbing frame

☒ Stationary☐ Mobile

Size across corners: 5.0 m x 6.79 m

12.2.96 Slewing section with 37.5 m Jib on KRE 260.1 (5.0m x 6.79m)

Tower crane without climbing frame

☒ Stationary☐ Mobile

Size across corners: 5.0 m x 6.79 m

12.2.97 Slewing section with 40 m Jib on KRE 260.1 (5.0m x 6.79m)

Tower crane without climbing frame

☒ Stationary☐ Mobile

Size across corners: 5.0 m x 6.79 m

12.2.98 Slewing section with 42.5 m Jib on KRE 260.1 (5.0m x 6.79m)

Tower crane without climbing frame

☒ Stationary☐ Mobile

Size across corners: 5.0 m x 6.79 m

12.2.99 Slewing section with 45 m Jib on KRE 260.1 (5.0m x 6.79m)

Tower crane without climbing frame

☒ Stationary☐ Mobile

Size across corners: 5.0 m x 6.79 m

12.2.100 Slewing section with 47.5 m Jib on KRE 260.1 (5.0m x 6.79m)

Tower crane without climbing frame

☒ Stationary☐ Mobile

Size across corners: 5.0 m x 6.79 m

12.2.101 Slewing section with 50 m Jib on KRE 260.1 (5.0m x 6.79m)

Tower crane without climbing frame

- ☒ Stationary
☐ Mobile

Size across corners: 5.0 m x 6.79 m

12.2.102 Slewing section with 52.5 m Jib on KRE 260.1 (5.0m x 6.79m)

Tower crane without climbing frame

- ☒ Stationary
☐ Mobile

Size across corners: 5.0 m x 6.79 m

12.2.103 Slewing section with 55 m Jib on KRE 260.1 (5.0m x 6.79m)

Tower crane without climbing frame

- ☒ Stationary
 - ☐ Mobile

Size across corners: 5.0 m x 6.79 m

12.2.104 Slewing section with 57.5 m Jib on KRE 260.1 (5.0m x 6.79m)

Tower crane without climbing frame

- ☒ Stationary
 - ☐ Mobile

Size across corners: 5.0 m x 6.79 m

12.2.105 Slewing section with 60 m Jib on KRE 260.1 (5.0m x 6.79m)

Tower crane without climbing frame

- ☒ Stationary
 - ☐ Mobile

Size across corners: 5.0 m x 6.79 m

12.2.106 Slewing section with 62.5 m Jib on KRE 260.1 (5.0m x 6.79m)

Tower crane without climbing frame

- ☒ Stationary
 - ☐ Mobile

Size across corners: 5.0 m x 6.79 m

12.2.107 Slewing section with 65 m Jib on KRE 260.1 (5.0m x 6.79m)

Tower crane without climbing frame

- ☒ Stationary
☐ Mobile

Size across corners: 5.0 m x 6.79 m

[illegible]

12.2.108 Slewing section with 30 m Jib on KRE 260.1 (6.0m x 6.0m)

Tower crane without climbing frame

- ☒ Stationary
☐ Mobile

Size across corners: 6.0 m x 6.0 m

[illegible]

12.2.109 Slewing section with 32.5 m Jib on KRE 260.1 (6.0m x 6.0m)

Tower crane without climbing frame

☒ Stationary☐ Mobile

Size across corners: 6.0 m x 6.0 m

[illegible]

12.2.110 Slewing section with 35 m Jib on KRE 260.1 (6.0m x 6.0m)

Tower crane without climbing frame

☒ Stationary☐ Mobile

Size across corners: 6.0 m x 6.0 m

[illegible]

12.2.111 Slewing section with 37.5 m Jib on KRE 260.1 (6.0m x 6.0m)

Tower crane without climbing frame

- ☒ Stationary
 - ☐ Mobile

Size across corners: 6.0 m x 6.0 m

[illegible]

12.2.112 Slewing section with 40 m Jib on KRE 260.1 (6.0m x 6.0m)

Tower crane without climbing frame

- ☒ Stationary
 - ☐ Mobile

Size across corners: 6.0 m x 6.0 m

[illegible]

12.2.113 Slewing section with 42.5 m Jib on KRE 260.1 (6.0m x 6.0m)

Tower crane without climbing frame

- ☒ Stationary
☐ Mobile

Size across corners: 6.0 m x 6.0 m

[illegible]

12.2.114 Slewing section with 45 m Jib on KRE 260.1 (6.0m x 6.0m)

Tower crane without climbing frame

- ☒ Stationary
☐ Mobile

Size across corners: 6.0 m x 6.0 m

[illegible]

12.2.115 Slewing section with 47.5 m Jib on KRE 260.1 (6.0m x 6.0m)

Tower crane without climbing frame

☒ Stationary☐ Mobile

Size across corners: 6.0 m x 6.0 m

[illegible]

12.2.116 Slewing section with 50 m Jib on KRE 260.1 (6.0m x 6.0m)

Tower crane without climbing frame

☒ Stationary☐ Mobile

Size across corners: 6.0 m x 6.0 m

[illegible]

12.2.117 Slewing section with 52.5 m Jib on KRE 260.1 (6.0m x 6.0m)

Tower crane without climbing frame

- ☒ Stationary
☐ Mobile

Size across corners: 6.0 m x 6.0 m

[illegible]

12.2.118 Slewing section with 55.0 m Jib on KRE 260.1 (6.0m x 6.0m)

Tower crane without climbing frame

- ☒ Stationary
☐ Mobile

Size across corners: 6.0 m x 6.0 m

[illegible]

12.2.121 Slewing section with 62.5 m Jib on KRE 260.1 (6.0m x 6.0m)

Tower crane without climbing frame

- ☒ Stationary
 - ☐ Mobile

Size across corners: 6.0 m x 6.0 m

[illegible]

12.2.122 Slewing section with 65 m Jib on KRE 260.1 (6.0m x 6.0m)

Tower crane without climbing frame

- ☒ Stationary
 - ☐ Mobile

Size across corners: 6.0 m x 6.0 m

[illegible]

12.2.123 Slewing section with 30 m Jib on KRE 260.2 (5.0m x 6.79m)

Tower crane without climbing frame

☒ Stationary☐ Mobile

Size across corners: 5.0 m x 6.79 m

[illegible]

12.2.124 Slewing section with 32.5 m Jib on KRE 260.2 (5.0m x 6.79m)

Tower crane without climbing frame

☒ Stationary☐ Mobile

Size across corners: 5.0 m x 6.79 m

[illegible]

12.2.125 Slewing section with 35 m Jib on KRE 260.2 (5.0m x 6.79m)

Tower crane without climbing frame

- ☒ Stationary
 - ☐ Mobile

Size across corners: 5.0 m x 6.79 m

[illegible]

12.2.126 Slewing section with 37.5 m Jib on KRE 260.2 (5.0m x 6.79m)

Tower crane without climbing frame

- ☒ Stationary
 - ☐ Mobile

Size across corners: 5.0 m x 6.79 m

[illegible]

12.2.127 Slewing section with 40 m Jib on KRE 260.2 (5.0m x 6.79m)

Tower crane without climbing frame

☒ Stationary☐ Mobile

Size across corners: 5.0 m x 6.79 m

[illegible]

12.2.128 Slewing section with 42.5 m Jib on KRE 260.2 (5.0m x 6.79m)

Tower crane without climbing frame

☒ Stationary☐ Mobile

Size across corners: 5.0 m x 6.79 m

[illegible]

12.2.129 Slewing section with 45 m Jib on KRE 260.2 (5.0m x 6.79m)

Tower crane without climbing frame

☒ Stationary☐ Mobile

Size across corners: 5.0 m x 6.79 m

[illegible]

12.2.130 Slewing section with 47.5 m Jib on KRE 260.2 (5.0m x 6.79m)

Tower crane without climbing frame

☒ Stationary☐ Mobile

Size across corners: 5.0 m x 6.79 m

[illegible]

12.2.131 Slewing section with 50 m Jib on KRE 260.2 (5.0m x 6.79m)

Tower crane without climbing frame

☒ Stationary☐ Mobile

Size across corners: 5.0 m x 6.79 m

12.2.132 Slewing section with 52.5 m Jib on KRE 260.2 (5.0m x 6.79m)

Tower crane without climbing frame

☒ Stationary☐ Mobile

Size across corners: 5.0 m x 6.79 m

[illegible]

12.2.133 Slewing section with 55 m Jib on KRE 260.2 (5.0m x 6.79m)

Tower crane without climbing frame

- ☒ Stationary
 - ☐ Mobile

Size across corners: 5.0 m x 6.79 m

[illegible]

12.2.134 Slewing section with 57.5 m Jib on KRE 260.2 (5.0m x 6.79m)

Tower crane without climbing frame

- ☒ Stationary
 - ☐ Mobile

Size across corners: 5.0 m x 6.79 m

[illegible]

12.2.135 Slewing section with 60 m Jib on KRE 260.2 (5.0m x 6.79m)

Tower crane without climbing frame

- ☒ Stationary
 - ☐ Mobile

Size across corners: 5.0 m x 6.79 m

[illegible]

12.2.136 Slewing section with 62.5 m Jib on KRE 260.2 (5.0m x 6.79m)

Tower crane without climbing frame

- ☒ Stationary
 - ☐ Mobile

Size across corners: 5.0 m x 6.79 m

[illegible]

12.2.137 Slewing section with 65 m Jib on KRE 260.2 (5.0m x 6.79m)

Tower crane without climbing frame

☒ Stationary☐ Mobile

Size across corners: 5.0 m x 6.79 m

[illegible]

12.2.138 Slewing section with 30 m Jib on KRE 260.2 (6.0m x 6.0m)

Tower crane without climbing frame

☒ Stationary☐ Mobile

Size across corners: 6.0 m x 6.0 m

[illegible]

12.2.139 Slewing section with 32.5 m Jib on KRE 260.2 (6.0m x 6.0m)

Tower crane without climbing frame

☒ Stationary

☐ Mobile

Size across corners: 6.0 m x 6.0 m

Hook height		Central ballast	Jib position	Crane in service					Horizontal load	Crane out of service				Horizontal load
Slewing torque: 280 kNm				Wind region: C25										
Corner loads				Corner loads										
				A	B	C	D		A	B	C	D		
[m]	[m]	[t]		[kN]	[kN]	[kN]	[kN]	[kN]	[kN]	[kN]	[kN]	[kN]	[kN]	
9.6	10.0	25	1	210	418	210	3	27	133	361	133	0	54	
			2	363	363	118	118		285	285	29	29		
14.1	14.5	25	1	213	433	213	0	28	139	368	139	0	61	
			2	375	375	114	114		292	292	31	31		
18.6	19.0	25	1	212	455	212	0	30	144	376	144	0	68	
			2	389	389	110	110		299	299	33	33		
23.1	23.5	25	1	209	479	209	0	31	148	386	148	0	75	
			2	448	448	105	105		307	307	34	34		
27.6	28.0	30	1	229	505	229	0	33	177	397	177	0	82	
			2	431	431	111	111		328	328	47	47		
32.1	32.5	30	1	224	535	224	0	34	180	409	180	0	89	
			2	448	448	103	103		337	337	47	47		
36.6	37.0	30	1	216	568	216	0	36	182	423	182	0	97	
			2	465	465	95	95		346	346	47	47		
41.1	41.5	40	1	257	604	257	0	37	280	450	280	109	104	
			2	509	509	110	110		400	400	159	159		
45.6	46.0	50	1	339	644	339	34	39	309	540	309	79	112	
			2	555	555	123	123		472	472	146	146		
50.1	50.5	60	1	369	699	369	38	40	339	635	339	42	120	
			2	602	602	135	135		548	548	129	129		
54.6	55.0	75	1	411	769	411	52	42	381	751	381	10	127	
			2	664	664	157	157		643	643	119	119		
59.1	59.5	85	1	443	829	443	57	44	375	903	375	0	137	
			2	716	716	170	170		732	732	93	93		

12.2.140 Slewing section with 35 m Jib on KRE 260.2 (6.0m x 6.0m)

Tower crane without climbing frame

☒ Stationary

☐ Mobile

Size across corners: 6.0 m x 6.0 m

Hook height		Central ballast	Jib position	Crane in service					Horizontal load	Crane out of service				Horizontal load
				Slewing torque: 280 kNm				Wind region: C25						
				Corner loads				Corner loads						
[m]	[m]	[t]		A [kN]	B [kN]	C [kN]	D [kN]	[kN]	A [kN]	B [kN]	C [kN]	D [kN]	[kN]	
9.6	10.0	25	1	241	428	241	54	27	133	361	133	0	54	
			2	373	373	108	108		285	285	29	29		
14.1	14.5	25	1	246	444	246	47	29	139	368	139	0	61	
			2	386	386	105	105		292	292	31	31		
18.6	19.0	25	1	250	462	250	39	30	144	376	144	0	68	
			2	400	400	100	100		299	299	33	33		
23.1	23.5	25	1	255	480	255	29	32	148	386	148	0	75	
			2	414	414	95	95		307	307	34	34		
27.6	28.0	30	1	272	513	272	30	33	177	397	177	0	82	
			2	442	442	101	101		328	328	47	47		
32.1	32.5	30	1	276	535	276	18	35	180	410	180	0	90	
			2	459	459	93	93		337	337	47	47		
36.6	37.0	30	1	281	558	281	3	36	182	424	182	0	97	
			2	477	477	84	84		347	347	154	154		
41.1	41.5	35	1	297	597	297	0	38	268	458	268	78	105	
			2	509	509	87	87		402	402	133	133		
45.6	46.0	45	1	327	649	327	6	39	297	548	297	47	112	
			2	555	555	100	100		474	474	120	120		
50.1	50.5	55	1	357	704	357	9	41	327	644	327	10	120	
			2	603	603	111	111		551	551	103	103		
54.6	55.0	70	1	399	775	399	23	42	347	783	347	0	128	
			2	665	665	133	133		646	646	92	92		
59.1	59.5	80	1	431	835	431	27	44	329	947	329	0	137	
			2	717	717	145	145		736	736	66	66		

12.2.141 Slewing section with 37.5 m Jib on KRE 260.2 (6.0m x 6.0m)

Tower crane without climbing frame

☒ Stationary

☐ Mobile

Size across corners: 6.0 m x 6.0 m

Hook height		Central ballast	Jib position	Crane in service					Horizontal load	Crane out of service				Horizontal load
				Slewing torque: 280 kNm				Wind region: C25						
				Corner loads				Corner loads						
[m]	[m]	[t]		A	B	C	D		A	B	C	D		
				[kN]	[kN]	[kN]	[kN]	[kN]		[kN]	[kN]	[kN]	[kN]	[kN]
9.6	10.0	25	1	242	433	242	51	27	133	361	133	0	54	
			2	377	377	107	107		285	285	29	29		
14.1	14.5	25	1	247	449	247	44	29	139	368	139	0	61	
			2	390	390	103	103		292	292	31	31		
18.6	19.0	25	1	251	467	251	36	30	144	377	144	0	68	
			2	404	404	99	99		299	299	33	33		
23.1	23.5	30	1	268	498	268	39	32	173	386	173	0	75	
			2	431	431	106	106		320	320	46	46		
27.6	28.0	30	1	273	518	273	27	33	177	397	177	0	83	
			2	446	446	99	99		328	328	47	47		
32.1	32.5	30	1	277	540	277	15	35	179	410	179	0	90	
			2	463	463	92	92		337	337	47	47		
36.6	37.0	30	1	282	564	282	0	36	181	424	181	0	97	
			2	481	481	83	83		357	357	147	147		
41.1	41.5	35	1	295	606	295	0	38	269	472	269	66	105	
			2	513	513	85	85		412	412	126	126		
45.6	46.0	40	1	306	653	306	0	39	286	549	286	23	113	
			2	547	547	85	85		472	472	100	100		
50.1	50.5	55	1	358	711	358	6	41	326	661	326	0	120	
			2	607	607	109	109		562	562	94	94		
54.6	55.0	65	1	388	769	388	6	42	310	811	310	0	128	
			2	657	657	118	118		645	645	71	71		
59.1	59.5	80	1	432	842	432	23	44	317	976	317	0	138	
			2	722	722	143	143		748	748	57	57		

12.2.142 Slewing section with 40 m Jib on KRE 260.2 (6.0m x 6.0m)

Tower crane without climbing frame

☒ Stationary

☐ Mobile

Size across corners: 6.0 m x 6.0 m

Hook height		Central ballast	Jib position	Crane in service					Horizontal load	Crane out of service				Horizontal load
				Slewing torque: 280 kNm				Wind region: C25						
				Corner loads				Corner loads						
 [m]	 [m]	[t]		A [kN]	B [kN]	C [kN]	D [kN]	[kN]	A [kN]	B [kN]	C [kN]	D [kN]	[kN]	
9.6	10.0	25	1	219	425	219	14	27	133	362	133	0	55	
			2	371	371	127	127		285	285	29	29		
14.1	14.5	25	1	224	439	224	9	29	139	369	139	0	62	
			2	384	384	123	123		292	292	31	31		
18.6	19.0	25	1	258	455	258	61	30	144	377	144	0	69	
			2	398	398	119	119		299	299	33	33		
23.1	23.5	30	1	275	487	275	64	32	173	387	173	0	76	
			2	425	425	126	126		320	320	46	46		
27.6	28.0	30	1	280	507	280	53	33	176	398	176	0	83	
			2	440	440	120	120		328	328	47	47		
32.1	32.5	30	1	243	533	243	0	35	179	410	179	0	90	
			2	457	457	112	112		337	337	47	47		
36.6	37.0	30	1	235	567	235	0	36	181	425	181	0	98	
			2	475	475	103	103		355	355	163	163		
41.1	41.5	35	1	250	604	250	0	38	276	467	276	85	105	
			2	507	507	105	105		411	411	141	141		
45.6	46.0	45	1	289	645	289	0	39	306	557	306	54	113	
			2	553	553	118	118		483	483	128	128		
50.1	50.5	55	1	365	698	365	32	41	335	654	335	16	121	
			2	601	601	130	130		561	561	109	109		
54.6	55.0	70	1	407	769	407	45	42	360	789	360	0	128	
			2	663	663	151	151		656	656	98	98		
59.1	59.5	80	1	439	829	439	49	44	341	955	341	0	138	
			2	715	715	164	164		747	747	72	72		

12.2.143 Slewing section with 42.5 m Jib on KRE 260.2 (6.0m x 6.0m)

Tower crane without climbing frame

☒ Stationary

☐ Mobile

Size across corners: 6.0 m x 6.0 m

Hook height		Central ballast	Jib position	Crane in service					Horizontal load	Crane out of service				Horizontal load
Slewing torque: 280 kNm				Wind region: C25										
Corner loads				Corner loads										
				A	B	C	D		A	B	C	D		
[m]	[m]	[t]		[kN]	[kN]	[kN]	[kN]	[kN]	[kN]	[kN]	[kN]	[kN]	[kN]	[kN]
9.6	10.0	25	1	250	434	250	67	27	133	362	133	0	55	
			2	380	380	121	121		285	285	29	29		
14.1	14.5	25	1	255	450	255	60	29	139	369	139	0	62	
			2	393	393	117	117		292	292	31	31		
18.6	19.0	25	1	260	467	260	52	30	144	377	144	0	69	
			2	407	407	112	112		299	299	32	32		
23.1	23.5	30	1	277	499	277	54	32	173	387	173	0	76	
			2	434	434	119	119		320	320	46	46		
27.6	28.0	30	1	281	519	281	43	33	176	398	176	0	83	
			2	449	449	113	113		328	328	47	47		
32.1	32.5	30	1	286	541	286	30	35	179	411	179	0	91	
			2	466	466	105	105		338	338	47	47		
36.6	37.0	35	1	303	578	303	28	36	273	430	273	115	98	
			2	497	497	108	108		384	384	161	161		
41.1	41.5	35	1	307	603	307	11	38	277	490	277	65	106	
			2	517	517	98	98		428	428	127	127		
45.6	46.0	40	1	324	644	324	4	39	294	569	294	20	113	
			2	550	550	98	98		488	488	100	100		
50.1	50.5	50	1	354	700	354	8	41	305	685	305	0	121	
			2	599	599	109	109		566	566	81	81		
54.6	55.0	65	1	396	771	396	21	42	313	838	313	0	129	
			2	661	661	131	131		662	662	69	69		
59.1	59.5	80	1	440	844	440	37	44	318	1006	318	0	138	
			2	726	726	155	155		766	766	55	55		

12.2.144 Slewing section with 45 m Jib on KRE 260.2 (6.0m x 6.0m)

Tower crane without climbing frame

☒ Stationary

☐ Mobile

Size across corners: 6.0 m x 6.0 m

Hook height		Central ballast	Jib position	Crane in service					Horizontal load	Crane out of service				Horizontal load
				Slewing torque: 280 kNm				Wind region: C25						
				Corner loads				Corner loads						
 [m]	 [m]	[t]		A [kN]	B [kN]	C [kN]	D [kN]	[kN]	A [kN]	B [kN]	C [kN]	D [kN]	[kN]	
9.6	10.0	25	1	228	432	228	24	27	133	362	133	0	55	
			2	373	373	143	143		285	285	29	29		
14.1	14.5	25	1	232	446	232	19	29	139	369	139	0	62	
			2	386	386	139	139		292	292	31	31		
18.6	19.0	30	1	250	474	250	25	30	168	377	168	0	69	
			2	412	412	147	147		312	312	45	45		
23.1	23.5	30	1	254	491	254	17	32	173	387	173	0	76	
			2	427	427	142	142		320	320	46	46		
27.6	28.0	30	1	259	509	259	8	33	176	399	176	0	84	
			2	442	442	135	135		329	329	46	46		
32.1	32.5	30	1	261	532	261	0	35	179	411	179	0	91	
			2	459	459	127	127		338	338	47	47		
36.6	37.0	35	1	278	566	278	0	36	280	430	280	130	98	
			2	490	490	131	131		386	386	174	174		
41.1	41.5	35	1	268	604	268	0	38	285	490	285	80	106	
			2	509	509	120	120		430	430	140	140		
45.6	46.0	40	1	281	646	281	0	39	302	569	302	35	114	
			2	543	543	121	121		491	491	113	113		
50.1	50.5	50	1	317	693	317	0	41	327	672	327	0	121	
			2	591	591	132	132		569	569	94	94		
54.6	55.0	65	1	403	757	403	50	42	334	826	334	0	129	
			2	653	653	154	154		666	666	81	81		
59.1	59.5	80	1	448	830	448	66	44	339	995	339	0	139	
			2	718	718	178	178		770	770	66	66		

12.2.145 Slewing section with 47.5 m Jib on KRE 260.2 (6.0m x 6.0m)

Tower crane without climbing frame

☒ Stationary

☐ Mobile

Size across corners: 6.0 m x 6.0 m

Hook height		Central ballast	Jib position	Crane in service					Horizontal load	Crane out of service				Horizontal load
Slewing torque:				Wind region:										
280 kNm				C25										
Corner loads				Corner loads										
			A	B	C	D		A	B	C	D			
[m]	[m]	[t]	[kN]	[kN]	[kN]	[kN]	[kN]	[kN]	[kN]	[kN]	[kN]	[kN]	[kN]	
9.6	10.0	25	1	258	427	258	90	27	133	362	133	0	56	
			2	377	377	139	139		285	285	29	29		
14.1	14.5	25	1	263	443	263	83	29	138	369	138	0	63	
			2	390	390	136	136		292	292	31	31		
18.6	19.0	30	1	280	473	280	87	30	168	378	168	0	70	
			2	416	416	144	144		312	312	45	45		
23.1	23.5	30	1	284	491	284	77	32	172	388	172	0	77	
			2	431	431	138	138		320	320	46	46		
27.6	28.0	30	1	289	512	289	66	33	176	399	176	0	84	
			2	447	447	131	131		329	329	46	46		
32.1	32.5	30	1	294	534	294	53	35	179	412	179	0	91	
			2	463	463	124	124		345	345	182	182		
36.6	37.0	35	1	311	570	311	51	36	281	445	281	116	99	
			2	494	494	127	127		397	397	164	164		
41.1	41.5	35	1	315	596	315	34	38	285	505	285	65	106	
			2	514	514	116	116		441	441	130	130		
45.6	46.0	40	1	332	637	332	28	39	302	585	302	20	114	
			2	548	548	117	117		502	502	102	102		
50.1	50.5	50	1	362	693	362	31	41	312	704	312	0	122	
			2	596	596	128	128		581	581	83	83		
54.6	55.0	60	1	391	751	391	31	42	293	860	293	0	130	
			2	646	646	137	137		665	665	57	57		
59.1	59.5	80	1	448	837	448	60	44	322	1030	322	0	139	
			2	723	723	173	173		783	783	54	54		

12.2.146 Slewing section with 50 m Jib on KRE 260.2 (6.0m x 6.0m)

Tower crane without climbing frame

☒ Stationary

☐ Mobile

Size across corners: 6.0 m x 6.0 m

Hook height		Central ballast	Jib position	Crane in service					Horizontal load	Crane out of service					Horizontal load
				Slewing torque: 280 kNm				Wind region: C25							
				Corner loads				Corner loads							
 [m]	 [m]	[t]		A [kN]	B [kN]	C [kN]	D [kN]	[kN]	A [kN]	B [kN]	C [kN]	D [kN]	[kN]		
9.6	10.0	25	1	259	426	259	91	27	133	362	133	0	56		
			2	377	377	140	140		285	285	29	29			
14.1	14.5	25	1	263	442	263	84	29	138	369	138	0	63		
			2	390	390	137	137		292	292	31	31			
18.6	19.0	30	1	280	472	280	88	30	168	378	168	0	70		
			2	416	416	144	144		312	312	45	45			
23.1	23.5	30	1	285	491	285	79	32	172	388	172	0	77		
			2	431	431	139	139		320	320	46	46			
27.6	28.0	30	1	289	511	289	67	33	176	399	176	0	84		
			2	446	446	132	132		329	329	46	46			
32.1	32.5	30	1	294	533	294	54	35	179	412	179	0	92		
			2	463	463	124	124		354	354	174	174			
36.6	37.0	35	1	311	570	311	52	36	281	458	281	104	99		
			2	494	494	128	128		406	406	155	155			
41.1	41.5	35	1	315	596	315	35	38	285	519	285	52	107		
			2	514	514	117	117		451	451	120	120			
45.6	46.0	40	1	332	636	332	29	39	302	599	302	6	114		
			2	547	547	118	118		512	512	93	93			
50.1	50.5	45	1	350	680	350	19	41	273	733	273	0	122		
			2	583	583	116	116		579	579	60	60			
54.6	55.0	60	1	392	751	392	32	42	278	890	278	0	130		
			2	646	646	137	137		676	676	47	47			
59.1	59.5	85	1	461	849	461	73	44	332	1061	332	0	139		
			2	736	736	187	187		807	807	56	56			

12.2.147 Slewing section with 52.5 m Jib on KRE 260.2 (6.0m x 6.0m)

Tower crane without climbing frame

☒ Stationary

☐ Mobile

Size across corners: 6.0 m x 6.0 m

Hook height		Central ballast	Jib position	Crane in service					Horizontal load	Crane out of service				Horizontal load
Slewing torque: 280 kNm				Wind region: C25										
Corner loads				Corner loads										
				A	B	C	D		A	B	C	D		
[m]	[m]	[t]		[kN]	[kN]	[kN]	[kN]	[kN]	[kN]	[kN]	[kN]	[kN]	[kN]	
9.6	10.0	25	1	237	433	237	40	27	133	362	133	0	56	
			2	375	375	98	98		285	285	29	29		
14.1	14.5	25	1	241	447	241	35	29	138	370	138	0	63	
			2	387	387	95	95		292	292	31	31		
18.6	19.0	30	1	258	475	258	41	30	168	378	168	0	71	
			2	412	412	104	104		312	312	44	44		
23.1	23.5	30	1	263	493	263	33	32	172	388	172	0	78	
			2	426	426	159	159		320	320	46	46		
27.6	28.0	30	1	267	511	267	23	33	175	400	175	0	85	
			2	442	442	153	153		329	329	46	46		
32.1	32.5	30	1	272	531	272	12	35	178	413	178	0	92	
			2	459	459	145	145		361	361	183	183		
36.6	37.0	35	1	289	566	289	12	36	289	465	289	112	100	
			2	489	489	148	148		414	414	164	164		
41.1	41.5	35	1	291	592	291	0	38	293	527	293	60	107	
			2	509	509	138	138		458	458	128	128		
45.6	46.0	40	1	304	635	304	0	39	310	607	310	14	115	
			2	542	542	138	138		520	520	100	100		
50.1	50.5	45	1	314	682	314	0	41	287	736	287	0	123	
			2	578	578	137	137		588	588	67	67		
54.6	55.0	60	1	400	741	400	58	42	292	895	292	0	131	
			2	641	641	158	158		686	686	53	53		
59.1	59.5	80	1	457	827	457	87	44	319	1069	319	0	140	
			2	718	718	195	195		805	805	49	49		

12.2.148 Slewing section with 55.0 m Jib on KRE 260.2 (6.0m x 6.0m)

Tower crane without climbing frame

☒ Stationary

☐ Mobile

Size across corners: 6.0 m x 6.0 m

Hook height		Central ballast	Jib position	Crane in service					Horizontal load	Crane out of service				Horizontal load
				Slewing torque: 280 kNm				Wind region: C25						
				Corner loads				Corner loads						
[m]	[m]	[t]		A [kN]	B [kN]	C [kN]	D [kN]	[kN]	A [kN]	B [kN]	C [kN]	D [kN]	[kN]	
9.6	10.0	25	1	267	431	267	104	28	133	362	133	0	56	
			2	383	383	152	152		285	285	29	29		
14.1	14.5	25	1	272	447	272	97	29	138	370	138	0	63	
			2	396	396	148	148		292	292	31	31		
18.6	19.0	30	1	289	477	289	101	31	168	378	168	0	71	
			2	422	422	156	156		312	312	44	44		
23.1	23.5	30	1	293	496	293	91	32	172	388	172	0	78	
			2	437	437	150	150		320	320	46	46		
27.6	28.0	30	1	298	516	298	80	34	175	400	175	0	85	
			2	452	452	144	144		341	341	195	195		
32.1	32.5	35	1	315	551	315	79	35	285	434	285	136	92	
			2	482	482	148	148		390	390	180	180		
36.6	37.0	35	1	320	575	320	64	37	290	489	290	90	100	
			2	500	500	139	139		431	431	148	148		
41.1	41.5	35	1	324	601	324	47	38	294	551	294	37	107	
			2	520	520	128	128		476	476	112	112		
45.6	46.0	40	1	341	643	341	40	40	302	642	302	0	115	
			2	554	554	128	128		538	538	84	84		
50.1	50.5	40	1	346	674	346	18	41	239	786	239	0	123	
			2	578	578	114	114		594	594	38	38		
54.6	55.0	65	1	413	771	413	55	43	292	947	292	0	131	
			2	666	666	160	160		718	718	48	48		
59.1	59.5	90	1	482	870	482	95	44	344	1122	344	0	140	
			2	756	756	208	208		849	849	56	56		

12.2.149 Slewing section with 57.5 m Jib on KRE 260.2 (6.0m x 6.0m)

Tower crane without climbing frame

☒ Stationary

☐ Mobile

Size across corners: 6.0 m x 6.0 m

Hook height		Central ballast	Jib position	Crane in service					Horizontal load	Crane out of service				Horizontal load
				Slewing torque: 280 kNm				Wind region: C25						
				Corner loads				Corner loads						
				A	B	C	D	A		B	C	D		
[m]	[m]	[t]		[kN]	[kN]	[kN]	[kN]	[kN]	[kN]	[kN]	[kN]	[kN]	[kN]	
9.6	10.0	25	1	267	419	267	115	28	133	363	133	0	57	
			2	375	375	160	160		285	285	28	28		
14.1	14.5	25	1	272	435	272	108	29	138	370	138	0	64	
			2	387	387	156	156		292	292	30	30		
18.6	19.0	30	1	289	465	289	112	31	168	379	168	0	71	
			2	413	413	164	164		313	313	44	44		
23.1	23.5	30	1	293	484	293	102	32	172	389	172	0	78	
			2	428	428	158	158		321	321	45	45		
27.6	28.0	30	1	298	504	298	91	34	175	400	175	0	85	
			2	444	444	152	152		341	341	194	194		
32.1	32.5	35	1	315	539	315	91	35	285	434	285	135	93	
			2	473	473	156	156		391	391	179	179		
36.6	37.0	35	1	319	563	319	76	37	289	490	289	88	100	
			2	491	491	147	147		431	431	147	147		
41.1	41.5	35	1	324	589	324	59	38	294	552	294	35	108	
			2	511	511	137	137		477	477	111	111		
45.6	46.0	40	1	341	629	341	52	40	299	646	299	0	116	
			2	545	545	137	137		539	539	82	82		
50.1	50.5	40	1	345	660	345	31	41	236	790	236	0	123	
			2	568	568	123	123		595	595	36	36		
54.6	55.0	65	1	413	757	413	68	43	289	952	289	0	131	
			2	656	656	169	169		719	719	46	46		
59.1	59.5	90	1	482	855	482	109	44	341	1127	341	0	141	
			2	746	746	218	218		851	851	53	53		

12.2.150 Slewing section with 60 m Jib on KRE 260.2 (6.0m x 6.0m)

Tower crane without climbing frame

☒ Stationary

☐ Mobile

Size across corners: 6.0 m x 6.0 m

Hook height		Central ballast	Jib position	Crane in service					Horizontal load	Crane out of service				Horizontal load
				Slewing torque: 280 kNm				Wind region: C25						
				Corner loads				Corner loads						
		[t]		A	B	C	D		A	B	C	D		
[m]	[m]			[kN]	[kN]	[kN]	[kN]	[kN]	[kN]	[kN]	[kN]	[kN]	[kN]	[kN]
9.6	10.0	25	1	267	423	267	112	28	133	363	133	0	57	
			2	378	378	157	157		287	287	78	78		
14.1	14.5	25	1	272	439	272	104	29	138	370	138	0	64	
			2	390	390	153	153		294	294	80	80		
18.6	19.0	30	1	289	469	289	108	31	168	379	168	0	71	
			2	417	417	161	161		314	314	94	94		
23.1	23.5	30	1	293	488	293	99	32	172	389	172	0	78	
			2	431	431	156	156		322	322	95	95		
27.6	28.0	30	1	298	509	298	87	34	175	401	175	0	86	
			2	447	447	149	149		354	354	182	182		
32.1	32.5	35	1	315	543	315	87	35	285	453	285	117	93	
			2	477	477	154	154		404	404	166	166		
36.6	37.0	35	1	320	567	320	72	37	290	509	290	70	101	
			2	495	495	144	144		445	445	134	134		
41.1	41.5	35	1	324	594	324	55	38	294	572	294	16	108	
			2	515	515	134	134		491	491	98	98		
45.6	46.0	40	1	341	634	341	48	40	280	686	280	0	116	
			2	549	549	134	134		554	554	68	68		
50.1	50.5	50	1	371	691	371	51	41	266	832	266	0	124	
			2	597	597	145	145		635	635	46	46		
54.6	55.0	70	1	425	775	425	76	43	293	996	293	0	132	
			2	672	672	178	178		747	747	43	43		
59.1	59.5	95	1	495	873	495	116	45	344	1173	344	0	141	
			2	763	763	227	227		880	880	50	50		

12.2.151 Slewing section with 62.5 m Jib on KRE 260.2 (6.0m x 6.0m)

Tower crane without climbing frame

☒ Stationary

☐ Mobile

Size across corners: 6.0 m x 6.0 m

Hook height		Central ballast	Jib position	Crane in service					Horizontal load	Crane out of service				Horizontal load
				Slewing torque: 280 kNm				Wind region: C25						
				Corner loads				Corner loads						
				A	B	C	D	A		B	C	D		
[m]	[m]	[t]		[kN]	[kN]	[kN]	[kN]	[kN]	[kN]	[kN]	[kN]	[kN]	[kN]	
9.6	10.0	30	1	258	433	258	82	28	191	404	191	0	57	
			2	382	382	134	134		339	339	53	53		
14.1	14.5	30	1	262	448	262	77	29	196	411	196	0	64	
			2	394	394	191	191		346	346	55	55		
18.6	19.0	30	1	267	464	267	70	31	201	421	201	0	72	
			2	408	408	186	186		354	354	56	56		
23.1	23.5	30	1	271	481	271	62	32	204	432	204	0	79	
			2	422	422	181	181		363	363	57	57		
27.6	28.0	35	1	288	512	288	65	34	227	449	227	5	86	
			2	450	450	187	187		384	384	70	70		
32.1	32.5	35	1	293	532	293	54	35	293	461	293	125	94	
			2	467	467	179	179		412	412	175	175		
36.6	37.0	40	1	310	566	310	54	37	310	530	310	90	101	
			2	498	498	182	182		465	465	155	155		
41.1	41.5	40	1	315	590	315	39	38	315	593	315	36	109	
			2	517	517	172	172		512	512	118	118		
45.6	46.0	45	1	362	629	362	94	40	319	688	319	0	116	
			2	551	551	173	173		575	575	88	88		
50.1	50.5	50	1	379	672	379	85	41	280	836	280	0	124	
			2	586	586	171	171		644	644	53	53		
54.6	55.0	70	1	433	756	433	111	43	306	1001	306	0	132	
			2	661	661	205	205		758	758	49	49		
59.1	59.5	95	1	503	854	503	151	45	356	1181	356	0	142	
			2	751	751	254	254		890	890	55	55		

12.2.152 Slewing section with 65 m Jib on KRE 260.2 (6.0m x 6.0m)

Tower crane without climbing frame

☒ Stationary

☐ Mobile

Size across corners: 6.0 m x 6.0 m

Hook height		Central ballast	Jib position	Crane in service					Horizontal load	Crane out of service				Horizontal load
				Slewing torque: 280 kNm				Wind region: C25						
				Corner loads				Corner loads						
				A	B	C	D	A		B	C	D		
[m]	[m]	[t]		[kN]	[kN]	[kN]	[kN]	[kN]	[kN]	[kN]	[kN]	[kN]	[kN]	
9.6	10.0	35	1	301	435	301	167	28	195	449	195	0	58	
			2	396	396	206	206		368	368	51	51		
14.1	14.5	35	1	306	452	306	160	29	200	457	200	0	65	
			2	409	409	202	202		376	376	52	52		
18.6	19.0	40	1	323	482	323	164	31	229	466	229	0	72	
			2	435	435	210	210		396	396	66	66		
23.1	23.5	40	1	327	500	327	154	32	233	477	233	0	79	
			2	450	450	205	205		405	405	67	67		
27.6	28.0	40	1	332	521	332	143	34	236	490	236	0	86	
			2	465	465	198	198		414	414	67	67		
32.1	32.5	45	1	349	555	349	142	35	319	515	319	122	94	
			2	495	495	203	203		458	458	180	180		
36.6	37.0	45	1	353	579	353	128	37	323	573	323	74	101	
			2	513	513	194	194		500	500	147	147		
41.1	41.5	50	1	370	617	370	123	38	340	649	340	31	109	
			2	545	545	196	196		559	559	122	122		
45.6	46.0	55	1	387	658	387	117	40	339	751	339	0	117	
			2	579	579	196	196		623	623	92	92		
50.1	50.5	55	1	392	689	392	95	41	274	901	274	0	125	
			2	602	602	182	182		681	681	43	43		
54.6	55.0	80	1	459	785	459	133	43	323	1070	323	0	132	
			2	690	690	228	228		807	807	51	51		
59.1	59.5	105	1	529	884	529	173	45	372	1251	372	0	142	
			2	780	780	277	277		941	941	56	56		

12.2.153 Slewing section with 30 m Jib on KRE 480

Tower crane without climbing frame

☒ Stationary

☐ Mobile

Size across corners: 8.0 m x 8.0 m

Hook height		Central ballast	Jib position	Crane in service					Horizontal load	Crane out of service					Horizontal load
Slewing torque: 280 kNm				Wind region: C25											
Corner loads				Corner loads											
 [m]	 [m]	[t]		A [kN]	B [kN]	C [kN]	D [kN]	[kN]	A [kN]	B [kN]	C [kN]	D [kN]	[kN]		
14.1	14.5	0	1	212	357	212	67	31	135	277	135	0	67		
			2	315	315	109	109		234	234	38	38			
18.6	19.0	0	1	219	374	219	64	33	144	286	144	2	76		
			2	329	329	109	109		244	244	43	43			
23.1	23.5	0	1	223	389	223	58	34	148	293	148	3	83		
			2	340	340	107	107		251	251	45	45			
27.6	28.0	0	1	228	404	228	52	36	153	302	153	3	90		
			2	353	353	104	104		258	258	47	47			
32.1	32.5	0	1	233	421	233	44	37	157	311	157	3	97		
			2	366	366	100	100		266	266	48	48			
36.6	37.0	0	1	237	438	237	36	39	162	320	162	3	105		
			2	379	379	95	95		276	276	138	138			
41.1	41.5	0	1	242	457	242	26	40	212	348	212	75	112		
			2	394	394	89	89		308	308	115	115			
45.6	46.0	5	1	259	490	259	27	42	229	409	229	49	120		
			2	423	423	95	95		356	356	101	101			
50.1	50.5	15	1	288	537	288	39	43	258	486	258	30	128		
			2	464	464	112	112		420	420	97	97			
54.6	55.0	20	1	305	573	305	37	45	270	562	270	0	136		
			2	495	495	116	116		474	474	76	76			
59.1	59.5	30	1	335	624	335	46	46	270	680	270	0	143		
			2	539	539	130	130		545	545	64	64			
63.6	64.0	40	1	364	677	364	52	48	264	809	264	0	151		
			2	585	585	143	143		621	621	48	48			
68.1	68.5	60	1	422	758	422	85	50	306	954	306	0	161		
			2	659	659	184	184		729	729	54	54			
72.6	73.0	80	1	479	841	479	117	52	340	1114	340	0	171		
			2	735	735	223	223		843	843	54	54			

12.2.154 Slewing section with 32.5 m Jib on KRE 480

Tower crane without climbing frame

☒ Stationary

☐ Mobile

Size across corners: 8.0 m x 8.0 m

Hook height		Central ballast	Jib position	Crane in service					Horizontal load	Crane out of service				Horizontal load
				Slewing torque: 280 kNm				Wind region: C25						
				Corner loads				Corner loads						
				A	B	C	D	A		B	C	D		
[m]	[m]	[t]		[kN]	[kN]	[kN]	[kN]	[kN]	[kN]	[kN]	[kN]	[kN]	[kN]	
14.1	14.5	0	1	220	359	220	81	31	135	277	135	0	67	
			2	318	318	121	121		235	235	38	38		
18.6	19.0	0	1	227	376	227	78	33	144	286	144	1	76	
			2	332	332	121	121		244	244	43	43		
23.1	23.5	0	1	231	391	231	72	34	148	294	148	3	83	
			2	344	344	119	119		251	251	45	45		
27.6	28.0	0	1	236	406	236	66	36	153	302	153	3	90	
			2	356	356	116	116		258	258	47	47		
32.1	32.5	0	1	241	423	241	58	37	157	311	157	3	98	
			2	369	369	112	112		266	266	48	48		
36.6	37.0	0	1	245	441	245	50	39	162	321	162	3	105	
			2	383	383	107	107		282	282	149	149		
41.1	41.5	0	1	250	460	250	40	40	220	353	220	86	113	
			2	398	398	101	101		314	314	125	125		
45.6	46.0	5	1	267	493	267	41	42	237	414	237	59	120	
			2	427	427	107	107		362	362	111	111		
50.1	50.5	10	1	284	527	284	40	43	254	479	254	28	128	
			2	456	456	111	111		413	413	94	94		
54.6	55.0	20	1	313	576	313	50	45	283	563	283	4	136	
			2	499	499	127	127		481	481	86	86		
59.1	59.5	30	1	343	627	343	59	46	288	677	288	0	144	
			2	544	544	142	142		552	552	73	73		
63.6	64.0	40	1	372	680	372	64	48	281	807	281	0	152	
			2	590	590	155	155		628	628	57	57		
68.1	68.5	55	1	417	749	417	85	50	297	954	297	0	162	
			2	652	652	182	182		724	724	50	50		
72.6	73.0	75	1	474	832	474	116	52	331	1115	331	0	172	
			2	727	727	221	221		839	839	50	50		

12.2.155 Slewing section with 35 m Jib on KRE 480

Tower crane without climbing frame

☒ Stationary

☐ Mobile

Size across corners: 8.0 m x 8.0 m

Hook height [m]	Central ballast [t]	Jib position	Crane in service Slewing torque: 280 kNm				Horizontal load [kN]	Crane out of service Wind region: C25				Horizontal load [kN]		
			Corner loads					Corner loads						
			A [kN]	B [kN]	C [kN]	D [kN]		A [kN]	B [kN]	C [kN]	D [kN]			
14.1	14.5	0	1	221	370	221	71	31	135	277	135	0	68	
			2	327	327	115	115		235	235	38	38		
18.6	19.0	0	1	228	387	228	68	33	144	286	144	1	77	
			2	341	341	115	115		244	244	43	43		
23.1	23.5	0	1	232	402	232	62	34	148	294	148	3	84	
			2	352	352	112	112		251	251	45	45		
27.6	28.0	0	1	237	418	237	56	36	153	302	153	3	91	
			2	365	365	109	109		258	258	47	47		
32.1	32.5	0	1	241	435	241	48	37	157	311	157	3	98	
			2	378	378	104	104		266	266	48	48		
36.6	37.0	0	1	246	453	246	39	39	216	324	216	108	106	
			2	392	392	99	99		292	292	139	139		
41.1	41.5	0	1	250	472	250	29	40	220	368	220	73	113	
			2	407	407	94	94		325	325	116	116		
45.6	46.0	0	1	255	493	255	17	42	225	417	225	33	121	
			2	423	423	87	87		361	361	89	89		
50.1	50.5	10	1	284	540	284	28	43	254	495	254	14	128	
			2	466	466	103	103		425	425	84	84		
54.6	55.0	15	1	302	577	302	26	45	249	589	249	0	136	
			2	497	497	107	107		480	480	63	63		
59.1	59.5	25	1	331	629	331	33	46	248	709	248	0	144	
			2	541	541	121	121		552	552	50	50		
63.6	64.0	40	1	373	695	373	51	48	266	841	266	0	152	
			2	601	601	146	146		641	641	46	46		
68.1	68.5	60	1	430	776	430	84	50	306	989	306	0	162	
			2	675	675	185	185		750	750	50	50		
72.6	73.0	80	1	487	860	487	114	52	339	1152	339	0	172	
			2	751	751	223	223		865	865	50	50		

12.2.156 Slewing section with 37.5 m Jib on KRE 480

Tower crane without climbing frame

☒ Stationary

☐ Mobile

Size across corners: 8.0 m x 8.0 m

Hook height [m]	Central ballast [t]	Jib position	Crane in service Slewing torque: 280 kNm				Horizontal load [kN]	Crane out of service Wind region: C25				Horizontal load [kN]		
			Corner loads					Corner loads						
			A [kN]	B [kN]	C [kN]	D [kN]		A [kN]	B [kN]	C [kN]	D [kN]			
14.1	14.5	0	1	222	375	222	69	31	135	277	135	0	68	
			2	330	330	114	114		235	235	38	38		
18.6	19.0	0	1	229	392	229	66	33	144	286	144	1	77	
			2	344	344	114	114		244	244	43	43		
23.1	23.5	0	1	233	406	233	60	35	148	294	148	2	84	
			2	356	356	111	111		251	251	45	45		
27.6	28.0	0	1	238	422	238	54	36	153	302	153	3	91	
			2	368	368	108	108		258	258	47	47		
32.1	32.5	0	1	242	439	242	46	37	157	311	157	3	98	
			2	381	381	103	103		270	270	155	155		
36.6	37.0	0	1	247	457	247	37	39	217	334	217	100	106	
			2	396	396	98	98		300	300	134	134		
41.1	41.5	0	1	252	477	252	26	40	222	379	222	65	113	
			2	411	411	92	92		333	333	111	111		
45.6	46.0	0	1	256	498	256	15	42	226	428	226	25	121	
			2	427	427	85	85		369	369	84	84		
50.1	50.5	5	1	273	533	273	14	43	236	501	236	0	129	
			2	457	457	90	90		420	420	66	66		
54.6	55.0	15	1	303	582	303	23	45	241	610	241	0	137	
			2	500	500	105	105		489	489	57	57		
59.1	59.5	25	1	332	634	332	31	46	239	731	239	0	145	
			2	546	546	119	119		561	561	44	44		
63.6	64.0	40	1	374	700	374	48	48	257	864	257	0	153	
			2	605	605	144	144		650	650	39	39		
68.1	68.5	60	1	431	782	431	81	50	297	1013	297	0	162	
			2	679	679	183	183		760	760	43	43		
72.6	73.0	85	1	501	879	501	123	52	354	1177	354	0	172	
			2	768	768	234	234		887	887	55	55		

12.2.169 Slewing section with 32.5 m Jib on UW 260.1 (5.0m x 6.79m)

Tower crane without climbing frame

- ☐ Stationary
☒ Mobile

Size across corners: 5.0 m x 6.79 m

12.2.170 Slewing section with 35 m Jib on UW 260.1 (5.0m x 6.79m)

Tower crane without climbing frame

- ☐ Stationary
☒ Mobile

Size across corners: 5.0 m x 6.79 m

12.2.173 Slewing section with 42.5 m Jib on UW 260.1 (5.0m x 6.79m)

Tower crane without climbing frame

☐ Stationary☐ Mobile

Size across corners: 5.0 m x 6.79 m

[illegible]

12.2.174 Slewing section with 45 m Jib on UW 260.1 (5.0m x 6.79m)

Tower crane without climbing frame

☐ Stationary☐ Mobile

Size across corners: 5.0 m x 6.79 m

[illegible]

12.2.175 Slewing section with 47.5 m Jib on UW 260.1 (5.0m x 6.79m)

Tower crane without climbing frame

- ☐ Stationary
☒ Mobile

Size across corners: 5.0 m x 6.79 m

12.2.176 Slewing section with 50 m Jib on UW 260.1 (5.0m x 6.79m)

Tower crane without climbing frame

- ☐ Stationary
 - ☒ Mobile

Size across corners: 5.0 m x 6.79 m

[illegible]

12.2.177 Slewing section with 52.5 m Jib on UW 260.1 (5.0m x 6.79m)

Tower crane without climbing frame

☐ Stationary☐ Mobile

Size across corners: 5.0 m x 6.79 m

[illegible]

12.2.178 Slewing section with 55 m Jib on UW 260.1 (5.0m x 6.79m)

Tower crane without climbing frame

☐ Stationary☐ Mobile

Size across corners: 5.0 m x 6.79 m

[illegible]

12.2.181 Slewing section with 62.5 m Jib on UW 260.1 (5.0m x 6.79m)

Tower crane without climbing frame

- ☐ Stationary
☒ Mobile

Size across corners: 5.0 m x 6.79 m

12.2.182 Slewing section with 65 m Jib on UW 260.1 (5.0m x 6.79m)

Tower crane without climbing frame

- ☐ Stationary
 - ☒ Mobile

Size across corners: 5.0 m x 6.79 m

12.2.183 Slewing section with 30 m Jib on UW 260.1 (6.0m x 6.0m)

Tower crane without climbing frame

- ☐ Stationary
☒ Mobile

Size across corners: 6.0 m x 6.0 m

12.2.184 Slewing section with 32.5 m Jib on UW 260.1 (6.0m x 6.0m)

Tower crane without climbing frame

- ☐ Stationary
☒ Mobile

Size across corners: 6.0 m x 6.0 m

12.2.185 Slewing section with 35 m Jib on UW 260.1 (6.0m x 6.0m)

Tower crane without climbing frame

- ☐ Stationary
☒ Mobile

Size across corners: 6.0 m x 6.0 m

[illegible]

12.2.186 Slewing section with 37.5 m Jib on UW 260.1 (6.0m x 6.0m)

Tower crane without climbing frame

- ☐ Stationary
☒ Mobile

Size across corners: 6.0 m x 6.0 m

[illegible]

12.2.187 Slewing section with 40 m Jib on UW 260.1 (6.0m x 6.0m)

Tower crane without climbing frame

- ☐ Stationary
☒ Mobile

Size across corners: 6.0 m x 6.0 m

12.2.188 Slewing section with 42.5 m Jib on UW 260.1 (6.0m x 6.0m)

Tower crane without climbing frame

- ☐ Stationary
☒ Mobile

Size across corners: 6.0 m x 6.0 m

12.2.189 Slewing section with 45 m Jib on UW 260.1 (6.0m x 6.0m)

Tower crane without climbing frame

- ☐ Stationary
☒ Mobile

Size across corners: 6.0 m x 6.0 m

12.2.190 Slewing section with 47.5 m Jib on UW 260.1 (6.0m x 6.0m)

Tower crane without climbing frame

- ☐ Stationary
 - ☒ Mobile

Size across corners: 6.0 m x 6.0 m

12.2.191 Slewing section with 50 m Jib on UW 260.1 (6.0m x 6.0m)

Tower crane without climbing frame

- ☐ Stationary
☒ Mobile

Size across corners: 6.0 m x 6.0 m

[illegible]

12.2.192 Slewing section with 52.5 m Jib on UW 260.1 (6.0m x 6.0m)

Tower crane without climbing frame

- ☐ Stationary
☒ Mobile

Size across corners: 6.0 m x 6.0 m

[illegible]

12.2.193 Slewing section with 55 m Jib on UW 260.1 (6.0m x 6.0m)

Tower crane without climbing frame

- ☐ Stationary
☒ Mobile

Size across corners: 6.0 m x 6.0 m

[illegible]

12.2.194 Slewing section with 57.5 m Jib on UW 260.1 (6.0m x 6.0m)

Tower crane without climbing frame

- ☐ Stationary
☒ Mobile

Size across corners: 6.0 m x 6.0 m

[illegible]

12.2.195 Slewing section with 60 m Jib on UW 260.1 (6.0m x 6.0m)

Tower crane without climbing frame

☐ Stationary☐ Mobile

Size across corners: 6.0 m x 6.0 m

12.2.196 Slewing section with 62.5 m Jib on UW 260.1 (6.0m x 6.0m)

Tower crane without climbing frame

☐ Stationary☐ Mobile

Size across corners: 6.0 m x 6.0 m

12.2.197 Slewing section with 65 m Jib on UW 260.1 (6.0m x 6.0m)

Tower crane without climbing frame

- ☐ Stationary
☒ Mobile

Size across corners: 6.0 m x 6.0 m

12.2.198 Slewing section with 30 m Jib on UW 260.2 (5.0m x 6.79m)

Tower crane without climbing frame

- ☐ Stationary
☒ Mobile

Size across corners: 5.0 m x 6.79 m

[illegible]

12.2.199 Slewing section with 32.5 m Jib on UW 260.2 (5.0m x 6.79m)

Tower crane without climbing frame

- ☐ Stationary
☒ Mobile

Size across corners: 5.0 m x 6.79 m

[illegible]

12.2.200 Slewing section with 35 m Jib on UW 260.2 (5.0m x 6.79m)

Tower crane without climbing frame

- ☐ Stationary
☒ Mobile

Size across corners: 5.0 m x 6.79 m

[illegible]

12.2.201 Slewing section with 37.5 m Jib on UW 260.2 (5.0m x 6.79m)

Tower crane without climbing frame

- ☐ Stationary
☒ Mobile

Size across corners: 5.0 m x 6.79 m

[illegible]

12.2.202 Slewing section with 40 m Jib on UW 260.2 (5.0m x 6.79m)

Tower crane without climbing frame

- ☐ Stationary
 - ☒ Mobile

Size across corners: 5.0 m x 6.79 m

[illegible]

12.2.203 Slewing section with 42.5 m Jib on UW 260.2 (5.0m x 6.79m)

Tower crane without climbing frame

- ☐ Stationary
☒ Mobile

Size across corners: 5.0 m x 6.79 m

12.2.204 Slewing section with 45 m Jib on UW 260.2 (5.0m x 6.79m)

Tower crane without climbing frame

- ☐ Stationary
 - ☒ Mobile

Size across corners: 5.0 m x 6.79 m

12.2.205 Slewing section with 47.5 m Jib on UW 260.2 (5.0m x 6.79m)

Tower crane without climbing frame

- ☐ Stationary
☒ Mobile

Size across corners: 5.0 m x 6.79 m

12.2.206 Slewing section with 50 m Jib on UW 260.2 (5.0m x 6.79m)

Tower crane without climbing frame

- ☐ Stationary
☒ Mobile

Size across corners: 5.0 m x 6.79 m

12.2.207 Slewing section with 52.5 m Jib on UW 260.2 (5.0m x 6.79m)

Tower crane without climbing frame

- ☐ Stationary
☒ Mobile

Size across corners: 5.0 m x 6.79 m

12.2.208 Slewing section with 55 m Jib on UW 260.2 (5.0m x 6.79m)

Tower crane without climbing frame

- ☐ Stationary
☒ Mobile

Size across corners: 5.0 m x 6.79 m

12.2.209 Slewing section with 57.5 m Jib on UW 260.2 (5.0m x 6.79m)

Tower crane without climbing frame

- ☐ Stationary
☒ Mobile

Size across corners: 5.0 m x 6.79 m

12.2.210 Slewing section with 60 m Jib on UW 260.2 (5.0m x 6.79m)

Tower crane without climbing frame

- ☐ Stationary
 - ☒ Mobile

Size across corners: 5.0 m x 6.79 m

12.2.211 Slewing section with 62.5 m Jib on UW 260.2 (5.0m x 6.79m)

Tower crane without climbing frame

- ☐ Stationary
☒ Mobile

Size across corners: 5.0 m x 6.79 m

12.2.212 Slewing section with 65 m Jib on UW 260.2 (5.0m x 6.79m)

Tower crane without climbing frame

- ☐ Stationary
 - ☒ Mobile

Size across corners: 5.0 m x 6.79 m

12.2.213 Slewing section with 30 m Jib on UW 260.2 (6.0m x 6.0m)

Tower crane without climbing frame

- ☐ Stationary
☒ Mobile

Size across corners: 6.0 m x 6.0 m

12.2.214 Slewing section with 32.5 m Jib on UW 260.2 (6.0m x 6.0m)

Tower crane without climbing frame

- ☐ Stationary
 - ☒ Mobile

Size across corners: 6.0 m x 6.0 m

12.2.215 Slewing section with 35 m Jib on UW 260.2 (6.0m x 6.0m)

Tower crane without climbing frame

- ☐ Stationary
☒ Mobile

Size across corners: 6.0 m x 6.0 m

12.2.216 Slewing section with 37.5 m Jib on UW 260.2 (6.0m x 6.0m)

Tower crane without climbing frame

- ☐ Stationary
 - ☒ Mobile

Size across corners: 6.0 m x 6.0 m

12.2.217 Slewing section with 40 m Jib on UW 260.2 (6.0m x 6.0m)

Tower crane without climbing frame

- ☐ Stationary
☒ Mobile

Size across corners: 6.0 m x 6.0 m

12.2.218 Slewing section with 42.5 m Jib on UW 260.2 (6.0m x 6.0m)

Tower crane without climbing frame

- ☐ Stationary
☒ Mobile

Size across corners: 6.0 m x 6.0 m

12.2.219 Slewing section with 45 m Jib on UW 260.2 (6.0m x 6.0m)

Tower crane without climbing frame

- ☐ Stationary
☒ Mobile

Size across corners: 6.0 m x 6.0 m

[illegible]

12.2.220 Slewing section with 47.5 m Jib on UW 260.2 (6.0m x 6.0m)

Tower crane without climbing frame

- ☐ Stationary
 - ☒ Mobile

Size across corners: 6.0 m x 6.0 m

[illegible]

12.2.221 Slewing section with 50 m Jib on UW 260.2 (6.0m x 6.0m)

Tower crane without climbing frame

- ☐ Stationary
☒ Mobile

Size across corners: 6.0 m x 6.0 m

[illegible]

12.2.222 Slewing section with 52.5 m Jib on UW 260.2 (6.0m x 6.0m)

Tower crane without climbing frame

- ☐ Stationary
 - ☒ Mobile

Size across corners: 6.0 m x 6.0 m

[illegible]

12.2.225 Slewing section with 60 m Jib on UW 260.2 (6.0m x 6.0m)

Tower crane without climbing frame

- ☐ Stationary
☒ Mobile

Size across corners: 6.0 m x 6.0 m

[illegible]

12.2.226 Slewing section with 62.5 m Jib on UW 260.2 (6.0m x 6.0m)

Tower crane without climbing frame

- ☐ Stationary
☒ Mobile

Size across corners: 6.0 m x 6.0 m

[illegible]

12.2.227 Slewing section with 65 m Jib on UW 260.2 (6.0m x 6.0m)

Tower crane without climbing frame

☐ Stationary☐ Mobile

Size across corners: 6.0 m x 6.0 m

[illegible]

12.2.228 Slewing section with 30 m Jib on UW 260.3 (5.0m x 6.79m)

Tower crane without climbing frame

☐ Stationary☐ Mobile

Size across corners: 5.0 m x 6.79 m

[illegible]

12.2.229 Slewing section with 32.5 m Jib on UW 260.3 (5.0m x 6.79m)

Tower crane without climbing frame

- ☐ Stationary
☒ Mobile

Size across corners: 5.0 m x 6.79 m

[illegible]

12.2.230 Slewing section with 35 m Jib on UW 260.3 (5.0m x 6.79m)

Tower crane without climbing frame

- ☐ Stationary
☒ Mobile

Size across corners: 5.0 m x 6.79 m

[illegible]

12.2.231 Slewing section with 37.5 m Jib on UW 260.3 (5.0m x 6.79m)

Tower crane without climbing frame

- ☐ Stationary
☒ Mobile

Size across corners: 5.0 m x 6.79 m

[illegible]

12.2.232 Slewing section with 40 m Jib on UW 260.3 (5.0m x 6.79m)

Tower crane without climbing frame

- ☐ Stationary
 - ☒ Mobile

Size across corners: 5.0 m x 6.79 m

[illegible]

12.2.233 Slewing section with 42.5 m Jib on UW 260.3 (5.0m x 6.79m)

Tower crane without climbing frame

- ☐ Stationary
☒ Mobile

Size across corners: 5.0 m x 6.79 m

[illegible]

12.2.234 Slewing section with 45 m Jib on UW 260.3 (5.0m x 6.79m)

Tower crane without climbing frame

- ☐ Stationary
☒ Mobile

Size across corners: 5.0 m x 6.79 m

[illegible]

12.2.235 Slewing section with 47.5 m Jib on UW 260.3 (5.0m x 6.79m)

Tower crane without climbing frame

- ☐ Stationary
☒ Mobile

Size across corners: 5.0 m x 6.79 m

12.2.236 Slewing section with 50 m Jib on UW 260.3 (5.0m x 6.79m)

Tower crane without climbing frame

- ☐ Stationary
 - ☒ Mobile

Size across corners: 5.0 m x 6.79 m

12.2.237 Slewing section with 52.5 m Jib on UW 260.3 (5.0m x 6.79m)

Tower crane without climbing frame

- ☐ Stationary
☒ Mobile

Size across corners: 5.0 m x 6.79 m

12.2.238 Slewing section with 55 m Jib on UW 260.3 (5.0m x 6.79m)

Tower crane without climbing frame

- ☐ Stationary
☒ Mobile

Size across corners: 5.0 m x 6.79 m

12.2.241 Slewing section with 62.5 m Jib on UW 260.3 (5.0m x 6.79m)

Tower crane without climbing frame

- ☐ Stationary
☒ Mobile

Size across corners: 5.0 m x 6.79 m

12.2.242 Slewing section with 65 m Jib on UW 260.3 (5.0m x 6.79m)

Tower crane without climbing frame

- ☐ Stationary
☒ Mobile

Size across corners: 5.0 m x 6.79 m

12.2.251 Slewing section with 50 m Jib on UW 260.3 (6.0m x 6.0m)

Tower crane without climbing frame

☐ Stationary

☒ Mobile

Size across corners: 6.0 m x 6.0 m

Hook height		Central ballast	Jib position	Crane in service					Horizontal load	Crane out of service					Horizontal load
Slewing torque: 280 kNm				Wind region: C25											
Corner loads				Corner loads											
				A	B	C	D		A	B	C	D			
[m]	[m]	[t]		[kN]	[kN]	[kN]	[kN]	[kN]	[kN]	[kN]	[kN]	[kN]	[kN]		
10.1	10.5	25	1	274	454	274	94	35	148	379	148	15	57		
			2	401	401	147	147		301	301	44	44			
14.6	15.0	25	1	279	474	279	83	37	153	386	153	15	64		
			2	417	417	140	140		308	308	46	46			
19.1	19.5	30	1	296	508	296	83	39	183	395	183	15	71		
			2	446	446	146	146		328	328	60	60			
23.6	24.0	30	1	300	531	300	70	40	187	405	187	15	78		
			2	463	463	137	137		336	336	61	61			
28.1	28.5	30	1	305	556	305	54	42	191	416	191	15	85		
			2	482	482	127	127		345	345	61	61			
32.6	33.0	30	1	309	582	309	36	44	193	429	193	15	93		
			2	502	502	116	116		373	373	185	185			
37.1	37.5	35	1	326	624	326	29	45	296	480	296	113	100		
			2	537	537	116	116		426	426	166	166			
41.6	42.0	35	1	323	662	323	15	47	301	542	301	60	108		
			2	560	560	102	102		471	471	131	131			
46.1	46.5	40	1	328	721	328	15	49	317	623	317	15	115		
			2	598	598	98	98		533	533	103	103			
50.6	51.0	45	1	330	785	330	15	50	280	765	280	15	123		
			2	637	637	93	93		600	600	70	70			
55.1	55.5	60	1	378	857	378	15	52	285	924	285	15	131		
			2	705	705	109	109		698	698	56	56			
59.6	60.0	85	1	477	933	477	20	54	337	1097	337	15	140		
			2	799	799	154	154		829	829	64	64			

12.2.252 Slewing section with 52.5 m Jib on UW 260.3 (6.0m x 6.0m)

Tower crane without climbing frame

☐ Stationary

☒ Mobile

Size across corners: 6.0 m x 6.0 m

Hook height		Central ballast	Jib position	Crane in service					Horizontal load	Crane out of service				Horizontal load
				Slewing torque: 280 kNm				Wind region: C25						
				Corner loads				Corner loads						
		[t]		A	B	C	D		A	B	C	D		
[m]	[m]			[kN]	[kN]	[kN]	[kN]	[kN]	[kN]	[kN]	[kN]	[kN]	[kN]	[kN]
10.1	10.5	25	1	252	459	252	45	36	148	379	148	15	57	
			2	399	399	106	106		301	301	44	44		
14.6	15.0	30	1	269	490	269	49	37	178	386	178	15	64	
			2	425	425	173	173		321	321	58	58		
19.1	19.5	30	1	274	509	274	39	39	183	395	183	15	71	
			2	442	442	165	165		328	328	60	60		
23.6	24.0	30	1	278	530	278	27	41	187	405	187	15	79	
			2	460	460	157	157		336	336	61	61		
28.1	28.5	30	1	281	553	281	15	42	190	417	190	15	86	
			2	479	479	147	147		345	345	61	61		
32.6	33.0	35	1	296	593	296	15	44	300	431	300	168	93	
			2	511	511	148	148		393	393	207	207		
37.1	37.5	35	1	283	636	283	15	46	304	487	304	121	101	
			2	533	533	136	136		434	434	175	175		
41.6	42.0	35	1	268	684	268	15	47	309	549	309	69	108	
			2	556	556	121	121		479	479	139	139		
46.1	46.5	40	1	276	736	276	15	49	326	631	326	21	116	
			2	594	594	118	118		541	541	111	111		
50.6	51.0	45	1	282	794	282	15	51	294	768	294	15	124	
			2	634	634	112	112		609	609	77	77		
55.1	55.5	60	1	334	858	334	15	52	298	929	298	15	132	
			2	702	702	128	128		708	708	62	62		
59.6	60.0	85	1	485	926	485	43	55	350	1104	350	15	141	
			2	797	797	173	173		840	840	69	69		

12.2.253 Slewing section with 55 m Jib on UW 260.3 (6.0m x 6.0m)

Tower crane without climbing frame

- ☐ Stationary
☒ Mobile

Size across corners: 6.0 m x 6.0 m

[illegible]

12.2.254 Slewing section with 57.5 m Jib on UW 260.3 (6.0m x 6.0m)

Tower crane without climbing frame

- ☐ Stationary
 - ☒ Mobile

Size across corners: 6.0 m x 6.0 m

[illegible]

12.2.255 Slewing section with 60 m Jib on UW 260.3 (6.0m x 6.0m)

Tower crane without climbing frame

☐ Stationary

☒ Mobile

Size across corners: 6.0 m x 6.0 m

Hook height		Central ballast	Jib position	Crane in service					Horizontal load	Crane out of service				Horizontal load
Slewing torque: 280 kNm				Wind region: C25										
				Corner loads				Corner loads						
[m]	[m]	[t]		A [kN]	B [kN]	C [kN]	D [kN]	[kN]	A [kN]	B [kN]	C [kN]	D [kN]	[kN]	
10.1	10.5	25	1	283	452	283	114	36	148	379	148	15	58	
			2	402	402	163	163		303	303	94	94		
14.6	15.0	30	1	300	485	300	115	38	178	387	178	15	65	
			2	430	430	169	169		322	322	108	108		
19.1	19.5	30	1	304	506	304	103	39	183	396	183	15	72	
			2	447	447	162	162		330	330	109	109		
23.6	24.0	30	1	309	530	309	88	41	187	406	187	15	79	
			2	465	465	153	153		340	340	218	218		
28.1	28.5	30	1	314	555	314	72	43	190	417	190	15	87	
			2	484	484	143	143		374	374	193	193		
32.6	33.0	35	1	331	594	331	67	44	301	475	301	127	94	
			2	517	517	144	144		424	424	178	178		
37.1	37.5	35	1	335	623	335	47	46	305	532	305	79	101	
			2	539	539	131	131		465	465	145	145		
41.6	42.0	35	1	340	655	340	25	48	310	595	310	24	109	
			2	562	562	117	117		511	511	108	108		
46.1	46.5	40	1	354	704	354	15	49	287	717	287	15	117	
			2	600	600	113	113		575	575	78	78		
50.6	51.0	50	1	380	770	380	15	51	273	865	273	15	125	
			2	653	653	119	119		657	657	56	56		
55.1	55.5	75	1	453	867	453	39	53	324	1029	324	15	133	
			2	746	746	161	161		782	782	65	65		
59.6	60.0	100	1	523	973	523	73	55	374	1208	374	15	142	
			2	841	841	205	205		915	915	71	71		

12.2.256 Slewing section with 62.5 m Jib on UW 260.3 (6.0m x 6.0m)

Tower crane without climbing frame

☐ Stationary

☒ Mobile

Size across corners: 6.0 m x 6.0 m

Hook height		Central ballast	Jib position	Crane in service					Horizontal load	Crane out of service				Horizontal load
				Slewing torque: 280 kNm				Wind region: C25						
				Corner loads				Corner loads						
[m]	[m]	[t]		A [kN]	B [kN]	C [kN]	D [kN]	[kN]	A [kN]	B [kN]	C [kN]	D [kN]	[kN]	
10.1	10.5	30	1	273	460	273	86	36	206	420	206	15	58	
			2	406	406	200	200		355	355	69	69		
14.6	15.0	30	1	278	478	278	77	38	211	428	211	15	65	
			2	422	422	194	194		362	362	70	70		
19.1	19.5	30	1	282	498	282	67	40	216	437	216	15	72	
			2	439	439	186	186		370	370	72	72		
23.6	24.0	35	1	299	531	299	68	41	238	455	238	21	80	
			2	469	469	190	190		391	391	85	85		
28.1	28.5	35	1	304	554	304	54	43	242	466	242	19	87	
			2	488	488	180	180		400	400	85	85		
32.6	33.0	35	1	339	579	339	98	45	309	482	309	135	94	
			2	508	508	169	169		431	431	186	186		
37.1	37.5	40	1	356	620	356	91	46	326	552	326	99	102	
			2	543	543	168	168		486	486	165	165		
41.6	42.0	40	1	360	652	360	69	48	330	616	330	44	110	
			2	566	566	154	154		532	532	128	128		
46.1	46.5	45	1	337	699	337	15	50	327	720	327	15	117	
			2	604	604	150	150		596	596	98	98		
50.6	51.0	50	1	342	758	342	15	51	287	869	287	15	125	
			2	644	644	144	144		666	666	62	62		
55.1	55.5	70	1	449	839	449	59	53	312	1035	312	15	133	
			2	725	725	173	173		780	780	58	58		
59.6	60.0	95	1	518	945	518	92	55	361	1217	361	15	143	
			2	820	820	217	217		913	913	64	64		

12.2.257 Slewing section with 65 m Jib on UW 260.3 (6.0m x 6.0m)

Tower crane without climbing frame

☐ Stationary

☒ Mobile

Size across corners: 6.0 m x 6.0 m

Hook height		Central ballast	Jib position	Crane in service					Horizontal load	Crane out of service				Horizontal load
				Slewing torque:				Wind region:						
				280 kNm				C25						
				Corner loads				Corner loads						
			A	B	C	D		A	B	C	D			
[m]	[m]	[t]	[kN]	[kN]	[kN]	[kN]	[kN]	[kN]	[kN]	[kN]	[kN]	[kN]	[kN]	
10.1	10.5	35	1	317	465	317	169	36	210	465	210	15	59	
			2	421	421	212	212		384	384	66	66		
14.6	15.0	35	1	321	485	321	157	38	215	473	215	15	66	
			2	437	437	205	205		392	392	68	68		
19.1	19.5	40	1	338	519	338	157	40	244	483	244	15	73	
			2	466	466	210	210		412	412	81	81		
23.6	24.0	40	1	343	543	343	143	41	248	494	248	15	80	
			2	484	484	201	201		421	421	82	82		
28.1	28.5	40	1	347	568	347	127	43	250	507	250	15	87	
			2	503	503	191	191		430	430	82	82		
32.6	33.0	45	1	364	607	364	121	45	334	537	334	132	95	
			2	536	536	192	192		477	477	191	191		
37.1	37.5	45	1	369	637	369	101	46	339	595	339	83	102	
			2	558	558	180	180		520	520	158	158		
41.6	42.0	50	1	386	681	386	91	48	356	672	356	40	110	
			2	594	594	178	178		580	580	132	132		
46.1	46.5	55	1	403	727	403	79	50	347	783	347	15	118	
			2	632	632	174	174		644	644	102	102		
50.6	51.0	55	1	407	765	407	50	51	280	934	280	15	125	
			2	660	660	155	155		702	702	53	53		
55.1	55.5	80	1	475	868	475	81	53	330	1104	330	15	133	
			2	753	753	196	196		829	829	60	60		
59.6	60.0	105	1	544	974	544	114	55	377	1287	377	15	143	
			2	848	848	240	240		964	964	64	64		

12.2.258 Slewing section with 30 m Jib on UW 480

Tower crane without climbing frame

☐ Stationary

☒ Mobile

Size across corners: 8.0 m x 8.0 m

Hook height		Central ballast	Jib position	Crane in service					Horizontal load	Crane out of service					Horizontal load
				Slewing torque: 280 kNm				Wind region: C25							
				Corner loads				Corner loads							
 [m]	 [m]	[t]		A [kN]	B [kN]	C [kN]	D [kN]		A [kN]	B [kN]	C [kN]	D [kN]			
15.1	15.5	0	1	237	395	237	79	39	159	303	159	24	69		
			2	348	348	125	125		260	260	63	63			
19.6	20.0	0	1	244	414	244	73	41	168	311	168	26	78		
			2	364	364	123	123		270	270	67	67			
24.1	24.5	0	1	248	432	248	65	43	173	319	173	27	85		
			2	378	378	119	119		277	277	69	69			
28.6	29.0	0	1	253	450	253	56	45	178	328	178	27	92		
			2	392	392	114	114		284	284	71	71			
33.1	33.5	0	1	258	470	258	45	47	182	337	182	27	99		
			2	407	407	108	108		292	292	73	73			
37.6	38.0	0	1	262	490	262	34	48	187	347	187	27	107		
			2	424	424	101	101		308	308	156	156			
42.1	42.5	0	1	263	517	263	24	50	237	384	237	89	114		
			2	441	441	93	93		341	341	132	132			
46.6	47.0	10	1	296	562	296	31	52	266	458	266	74	122		
			2	484	484	108	108		402	402	131	131			
51.1	51.5	15	1	313	600	313	27	53	283	524	283	42	130		
			2	516	516	111	111		454	454	113	113			
55.6	56.0	25	1	343	652	343	33	55	306	615	306	24	138		
			2	562	562	124	124		521	521	104	104			
60.1	60.5	35	1	372	707	372	37	57	305	734	305	24	145		
			2	609	609	135	135		593	593	91	91			
64.6	65.0	45	1	402	765	402	39	58	299	866	299	24	153		
			2	658	658	145	145		669	669	74	74			
69.1	69.5	65	1	459	850	459	68	60	339	1014	339	24	163		
			2	736	736	182	182		779	779	79	79			
73.6	74.0	85	1	516	938	516	94	63	372	1176	372	24	173		
			2	815	815	217	217		893	893	79	79			

12.2.259 Slewing section with 32.5 m Jib on UW 480

Tower crane without climbing frame

☐ Stationary

☒ Mobile

Size across corners: 8.0 m x 8.0 m

Hook height		Central ballast	Jib position	Crane in service				Horizontal load	Crane out of service				Horizontal load
				Slewing torque: 280 kNm					Wind region: C25				
				Corner loads					Corner loads				
				A	B	C	D		A	B	C	D	
[m]	[m]	[t]		[kN]	[kN]	[kN]	[kN]	[kN]	[kN]	[kN]	[kN]	[kN]	[kN]
15.1	15.5	0	1	245	397	245	92	40	159	304	159	24	69
			2	353	353	137	137		260	260	63	63	
19.6	20.0	0	1	252	417	252	87	42	168	312	168	25	78
			2	369	369	135	135		270	270	67	67	
24.1	24.5	0	1	256	434	256	78	44	173	320	173	26	85
			2	382	382	130	130		277	277	69	69	
28.6	29.0	0	1	261	453	261	69	45	178	328	178	27	92
			2	397	397	125	125		284	284	71	71	
33.1	33.5	0	1	265	473	265	58	47	182	337	182	27	100
			2	412	412	119	119		292	292	72	72	
37.6	38.0	0	1	220	496	220	24	49	187	347	187	27	107
			2	428	428	112	112		314	314	166	166	
42.1	42.5	0	1	213	528	213	24	50	245	389	245	100	115
			2	446	446	104	104		347	347	142	142	
46.6	47.0	5	1	230	562	230	24	52	262	451	262	72	122
			2	477	477	107	107		395	395	128	128	
51.1	51.5	15	1	321	604	321	38	54	291	530	291	53	130
			2	521	521	121	121		460	460	122	122	
55.6	56.0	25	1	351	657	351	44	55	321	614	321	28	138
			2	567	567	134	134		528	528	113	113	
60.1	60.5	35	1	380	712	380	48	57	323	731	323	24	146
			2	615	615	145	145		600	600	100	100	
64.6	65.0	45	1	410	771	410	49	59	315	864	315	24	154
			2	665	665	155	155		677	677	83	83	
69.1	69.5	60	1	454	844	454	65	61	330	1013	330	24	164
			2	730	730	179	179		774	774	75	75	
73.6	74.0	85	1	524	946	524	102	63	387	1178	387	24	174
			2	822	822	226	226		902	902	86	86	

12.2.260 Slewing section with 35 m Jib on UW 480

Tower crane without climbing frame

☐ Stationary

☒ Mobile

Size across corners: 8.0 m x 8.0 m

Hook height		Central ballast	Jib position	Crane in service					Horizontal load	Crane out of service					Horizontal load
				Slewing torque: 280 kNm				Wind region: C25							
				Corner loads				Corner loads							
				A	B	C	D	A		B	C	D			
[m]	[m]	[t]		[kN]	[kN]	[kN]	[kN]	[kN]	[kN]	[kN]	[kN]	[kN]	[kN]		
15.1	15.5	0	1	246	409	246	82	40	159	304	159	24	69		
			2	361	361	130	130		260	260	63	63			
19.6	20.0	0	1	253	429	253	77	42	168	312	168	25	78		
			2	377	377	128	128		270	270	67	67			
24.1	24.5	0	1	257	446	257	68	44	173	320	173	26	85		
			2	391	391	123	123		277	277	69	69			
28.6	29.0	0	1	262	465	262	58	45	178	328	178	27	93		
			2	405	405	118	118		284	284	71	71			
33.1	33.5	0	1	266	485	266	48	47	182	337	182	27	100		
			2	421	421	112	112		294	294	178	178			
37.6	38.0	0	1	271	506	271	35	49	241	359	241	123	107		
			2	437	437	104	104		324	324	157	157			
42.1	42.5	0	1	272	532	272	24	50	245	404	245	86	115		
			2	455	455	96	96		358	358	133	133			
46.6	47.0	0	1	262	572	262	24	52	250	454	250	46	123		
			2	473	473	86	86		394	394	106	106			
51.1	51.5	10	1	299	615	299	24	54	279	533	279	26	130		
			2	518	518	100	100		459	459	100	100			
55.6	56.0	20	1	334	663	334	24	55	285	642	285	24	138		
			2	565	565	113	113		527	527	91	91			
60.1	60.5	30	1	367	716	367	24	57	283	764	283	24	146		
			2	613	613	124	124		600	600	77	77			
64.6	65.0	45	1	411	785	411	36	59	300	898	300	24	154		
			2	676	676	145	145		689	689	72	72			
69.1	69.5	65	1	468	872	468	63	61	339	1048	339	24	164		
			2	754	754	182	182		800	800	76	76			
73.6	74.0	90	1	537	974	537	100	63	395	1214	395	24	174		
			2	846	846	228	228		928	928	87	87			

12.2.261 Slewing section with 37.5 m Jib on UW 480

Tower crane without climbing frame

☐ Stationary

☒ Mobile

Size across corners: 8.0 m x 8.0 m

Hook height		Central ballast	Jib position	Crane in service					Horizontal load	Crane out of service					Horizontal load
				Slewing torque: 280 kNm				Wind region: C25							
				Corner loads				Corner loads							
[m]	[m]	[t]		A [kN]	B [kN]	C [kN]	D [kN]	[kN]	A [kN]	B [kN]	C [kN]	D [kN]	[kN]		
15.1	15.5	0	1	247	413	247	81	40	159	304	159	24	70		
			2	364	364	129	129		260	260	63	63			
19.6	20.0	0	1	254	433	254	75	42	168	312	168	25	79		
			2	380	380	127	127		270	270	67	67			
24.1	24.5	0	1	258	450	258	66	44	173	320	173	26	86		
			2	394	394	122	122		277	277	69	69			
28.6	29.0	0	1	263	469	263	56	46	178	328	178	27	93		
			2	409	409	117	117		284	284	71	71			
33.1	33.5	0	1	267	489	267	45	47	182	337	182	27	100		
			2	424	424	110	110		301	301	173	173			
37.6	38.0	0	1	272	511	272	33	49	242	369	242	115	108		
			2	441	441	103	103		332	332	152	152			
42.1	42.5	0	1	271	539	271	24	51	247	415	247	78	115		
			2	458	458	95	95		365	365	128	128			
46.6	47.0	0	1	260	579	260	24	52	251	465	251	38	123		
			2	477	477	85	85		402	402	100	100			
51.1	51.5	10	1	297	623	297	24	54	273	552	273	24	131		
			2	522	522	99	99		467	467	94	94			
55.6	56.0	15	1	307	672	307	24	56	252	663	252	24	139		
			2	556	556	99	99		523	523	72	72			
60.1	60.5	30	1	365	725	365	24	57	274	786	274	24	147		
			2	617	617	122	122		609	609	71	71			
64.6	65.0	45	1	412	791	412	32	59	291	921	291	24	155		
			2	680	680	143	143		699	699	65	65			
69.1	69.5	70	1	481	891	481	72	61	354	1072	354	24	164		
			2	771	771	192	192		822	822	81	81			
73.6	74.0	90	1	538	980	538	96	63	385	1239	385	24	174		
			2	851	851	226	226		938	938	79	79			

12.2.262 Slewing section with 40 m Jib on UW 480

Tower crane without climbing frame

☐ Stationary

☒ Mobile

Size across corners: 8.0 m x 8.0 m

Hook height		Central ballast	Jib position	Crane in service					Horizontal load	Crane out of service					Horizontal load
				Slewing torque: 280 kNm						Wind region: C25					
				Corner loads						Corner loads					
				A	B	C	D	A		B	C	D			
[m]	[m]	[t]		[kN]	[kN]	[kN]	[kN]	[kN]	[kN]	[kN]	[kN]	[kN]	[kN]		
15.1	15.5	0	1	254	407	254	101	40	159	304	159	24	70		
			2	362	362	146	146		260	260	63	63			
19.6	20.0	0	1	261	427	261	95	42	168	312	168	25	79		
			2	378	378	144	144		270	270	67	67			
24.1	24.5	0	1	265	444	265	86	44	173	320	173	26	86		
			2	392	392	139	139		277	277	69	69			
28.6	29.0	0	1	270	463	270	77	46	178	328	178	27	93		
			2	407	407	133	133		284	284	71	71			
33.1	33.5	0	1	274	483	274	66	47	182	338	182	27	101		
			2	422	422	127	127		302	302	187	187			
37.6	38.0	0	1	279	505	279	53	49	249	367	249	131	108		
			2	439	439	119	119		333	333	166	166			
42.1	42.5	0	1	230	530	230	24	51	254	413	254	94	116		
			2	456	456	111	111		366	366	141	141			
46.6	47.0	0	1	221	565	221	24	53	258	463	258	54	123		
			2	475	475	101	101		403	403	113	113			
51.1	51.5	10	1	318	604	318	31	54	288	543	288	33	131		
			2	520	520	115	115		468	468	107	107			
55.6	56.0	20	1	347	658	347	37	56	299	646	299	24	139		
			2	567	567	128	128		537	537	97	97			
60.1	60.5	30	1	377	714	377	39	58	297	769	297	24	147		
			2	615	615	138	138		610	610	83	83			
64.6	65.0	40	1	406	773	406	39	59	288	906	288	24	155		
			2	666	666	147	147		688	688	65	65			
69.1	69.5	65	1	476	873	476	79	61	351	1058	351	24	165		
			2	757	757	195	195		811	811	80	80			
73.6	74.0	85	1	533	963	533	103	64	381	1226	381	24	175		
			2	837	837	229	229		928	928	78	78			

12.2.263 Slewing section with 42.5 m Jib on UW 480

Tower crane without climbing frame

☐ Stationary

☒ Mobile

Size across corners: 8.0 m x 8.0 m

Hook height		Central ballast	Jib position	Crane in service					Horizontal load	Crane out of service					Horizontal load
Slewing torque: 280 kNm				Wind region: C25											
Corner loads				Corner loads											
 [m]	 [m]	[t]		A [kN]	B [kN]	C [kN]	D [kN]	[kN]	A [kN]	B [kN]	C [kN]	D [kN]	[kN]		
15.1	15.5	0	1	255	416	255	94	40	159	304	159	24	70		
			2	369	369	141	141		260	260	63	63			
19.6	20.0	0	1	262	436	262	88	43	168	312	168	25	79		
			2	385	385	139	139		270	270	67	67			
24.1	24.5	0	1	267	454	267	79	44	173	320	173	26	86		
			2	399	399	134	134		277	277	69	69			
28.6	29.0	0	1	271	473	271	69	46	178	329	178	27	94		
			2	414	414	128	128		286	286	196	196			
33.1	33.5	0	1	276	493	276	58	48	246	343	246	149	101		
			2	429	429	122	122		314	314	177	177			
37.6	38.0	0	1	280	515	280	46	49	250	384	250	116	108		
			2	446	446	114	114		345	345	155	155			
42.1	42.5	0	1	285	538	285	31	51	255	430	255	79	116		
			2	464	464	106	106		379	379	131	131			
46.6	47.0	0	1	280	572	280	24	53	259	481	259	38	124		
			2	483	483	96	96		416	416	103	103			
51.1	51.5	5	1	292	617	292	24	54	256	569	256	24	132		
			2	516	516	97	97		469	469	84	84			
55.6	56.0	15	1	327	666	327	24	56	259	682	259	24	139		
			2	563	563	109	109		538	538	73	73			
60.1	60.5	25	1	359	720	359	24	58	255	807	255	24	147		
			2	611	611	119	119		612	612	59	59			
64.6	65.0	45	1	420	798	420	42	59	295	945	295	24	155		
			2	687	687	153	153		716	716	65	65			
69.1	69.5	70	1	490	898	490	81	62	357	1099	357	24	165		
			2	778	778	201	201		840	840	80	80			
73.6	74.0	90	1	547	989	547	105	64	387	1269	387	24	175		
			2	859	859	234	234		957	957	77	77			

12.2.264 Slewing section with 45 m Jib on UW 480

Tower crane without climbing frame

☐ Stationary

☒ Mobile

Size across corners: 8.0 m x 8.0 m

Hook height		Central ballast	Jib position	Crane in service					Horizontal load	Crane out of service				Horizontal load
				Slewing torque: 280 kNm				Wind region: C25						
				Corner loads				Corner loads						
				A	B	C	D	A		B	C	D		
[m]	[m]	[t]		[kN]	[kN]	[kN]	[kN]	[kN]	[kN]	[kN]	[kN]	[kN]	[kN]	
15.1	15.5	0	1	262	409	262	116	41	158	304	158	24	71	
			2	366	366	159	159		260	260	62	62		
19.6	20.0	0	1	270	429	270	110	43	168	312	168	25	80	
			2	382	382	157	157		270	270	67	67		
24.1	24.5	0	1	274	447	274	101	45	173	320	173	26	87	
			2	396	396	152	152		277	277	69	69		
28.6	29.0	0	1	279	466	279	91	46	178	329	178	26	94	
			2	411	411	146	146		289	289	208	208		
33.1	33.5	0	1	283	486	283	80	48	253	344	253	162	101	
			2	427	427	140	140		317	317	189	189		
37.6	38.0	0	1	288	508	288	68	50	258	386	258	129	109	
			2	443	443	132	132		348	348	167	167		
42.1	42.5	0	1	246	533	246	24	51	262	432	262	92	116	
			2	461	461	123	123		382	382	142	142		
46.6	47.0	0	1	237	569	237	24	53	267	483	267	51	124	
			2	480	480	113	113		420	420	114	114		
51.1	51.5	5	1	251	609	251	24	55	276	559	276	24	132	
			2	513	513	115	115		473	473	95	95		
55.6	56.0	15	1	288	653	288	24	56	278	673	278	24	140	
			2	560	560	127	127		543	543	84	84		
60.1	60.5	25	1	373	706	373	39	58	274	799	274	24	148	
			2	609	609	137	137		617	617	69	69		
64.6	65.0	45	1	428	791	428	64	60	314	938	314	24	156	
			2	685	685	170	170		721	721	75	75		
69.1	69.5	65	1	485	879	485	90	62	350	1094	350	24	166	
			2	763	763	206	206		833	833	77	77		
73.6	74.0	90	1	554	982	554	126	64	403	1265	403	24	176	
			2	857	857	252	252		963	963	85	85		

12.2.265 Slewing section with 47.5 m Jib on UW 480

Tower crane without climbing frame

☐ Stationary

☒ Mobile

Size across corners: 8.0 m x 8.0 m

Hook height		Central ballast	Jib position	Crane in service					Horizontal load	Crane out of service					Horizontal load
Slewing torque: 280 kNm				Wind region: C25											
Corner loads				Corner loads											
A	B			C	D		A	B		C	D				
		[t]		[kN]	[kN]	[kN]	[kN]	[kN]	[kN]	[kN]	[kN]	[kN]	[kN]	[kN]	
15.1	15.5	0	1	263	413	263	113	41	158	304	158	24	71		
			2	369	369	157	157		260	260	62	62			
19.6	20.0	0	1	270	433	270	106	43	168	312	168	25	80		
			2	385	385	154	154		270	270	67	67			
24.1	24.5	0	1	274	451	274	98	45	173	320	173	26	87		
			2	399	399	149	149		277	277	69	69			
28.6	29.0	0	1	279	470	279	88	46	178	329	178	26	94		
			2	414	414	144	144		297	297	201	201			
33.1	33.5	0	1	284	491	284	76	48	254	355	254	152	102		
			2	430	430	137	137		325	325	182	182			
37.6	38.0	0	1	288	513	288	64	50	258	397	258	119	109		
			2	447	447	129	129		356	356	160	160			
42.1	42.5	0	1	293	536	293	49	51	263	444	263	82	117		
			2	465	465	121	121		391	391	135	135			
46.6	47.0	0	1	297	561	297	33	53	267	495	267	40	124		
			2	484	484	111	111		428	428	106	106			
51.1	51.5	0	1	293	597	293	24	55	240	583	240	24	132		
			2	504	504	99	99		469	469	74	74			
55.6	56.0	10	1	327	647	327	24	56	242	697	242	24	140		
			2	551	551	111	111		539	539	63	63			
60.1	60.5	25	1	373	712	373	35	58	262	824	262	24	148		
			2	613	613	134	134		626	626	61	61			
64.6	65.0	45	1	428	797	428	59	60	301	965	301	24	156		
			2	689	689	167	167		730	730	65	65			
69.1	69.5	70	1	497	898	497	97	62	362	1121	362	24	166		
			2	780	780	215	215		855	855	80	80			
73.6	74.0	95	1	567	1001	567	133	64	415	1294	415	24	176		
			2	874	874	260	260		986	986	88	88			

12.2.266 Slewing section with 50 m Jib on UW 480

Tower crane without climbing frame

☐ Stationary

☒ Mobile

Size across corners: 8.0 m x 8.0 m

Hook height		Central ballast	Jib position	Crane in service					Horizontal load	Crane out of service					Horizontal load
				Slewing torque: 280 kNm				Wind region: C25							
				Corner loads				Corner loads							
				A	B	C	D	A		B	C	D			
[m]	[m]	[t]	[kN]	[kN]	[kN]	[kN]	[kN]	[kN]	[kN]	[kN]	[kN]	[kN]	[kN]		
15.1	15.5	0	1	263	413	263	114	41	158	305	158	24	71		
			2	369	369	157	157		260	260	62	62			
19.6	20.0	0	1	270	433	270	107	43	168	312	168	25	80		
			2	385	385	155	155		270	270	67	67			
24.1	24.5	0	1	275	451	275	99	45	173	320	173	26	87		
			2	399	399	150	150		278	278	212	212			
28.6	29.0	0	1	279	470	279	88	46	178	329	178	26	95		
			2	414	414	144	144		304	304	195	195			
33.1	33.5	0	1	284	491	284	77	48	254	365	254	143	102		
			2	430	430	138	138		332	332	176	176			
37.6	38.0	0	1	288	512	288	64	50	258	407	258	110	110		
			2	447	447	130	130		363	363	153	153			
42.1	42.5	0	1	293	536	293	50	51	263	454	263	72	117		
			2	465	465	121	121		398	398	128	128			
46.6	47.0	0	1	298	561	298	34	53	268	505	268	30	125		
			2	484	484	111	111		436	436	99	99			
51.1	51.5	0	1	294	597	294	24	55	230	604	230	24	133		
			2	504	504	100	100		477	477	67	67			
55.6	56.0	10	1	328	646	328	24	56	231	720	231	24	141		
			2	551	551	112	112		547	547	56	56			
60.1	60.5	30	1	386	725	386	48	58	276	847	276	24	148		
			2	625	625	147	147		647	647	65	65			
64.6	65.0	50	1	441	810	441	72	60	315	989	315	24	157		
			2	702	702	180	180		752	752	70	70			
69.1	69.5	70	1	498	898	498	98	62	350	1147	350	24	166		
			2	780	780	215	215		865	865	71	71			
73.6	74.0	95	1	567	1001	567	134	64	402	1321	402	24	176		
			2	874	874	261	261		996	996	79	79			

12.2.267 Slewing section with 52.5 m Jib on UW 480

Tower crane without climbing frame

☐ Stationary

☒ Mobile

Size across corners: 8.0 m x 8.0 m

Hook height		Central ballast	Jib position	Crane in service					Horizontal load	Crane out of service					Horizontal load
Slewing torque: 280 kNm				Wind region: C25											
Corner loads				Corner loads											
A	B			C	D	A	B	C		D					
[m]	[m]	[t]		[kN]	[kN]	[kN]	[kN]	[kN]	[kN]	[kN]	[kN]	[kN]	[kN]		
15.1	15.5	0	1	241	409	241	73	41	158	305	158	24	72		
			2	368	368	174	174		261	261	62	62			
19.6	20.0	0	1	278	429	278	128	43	168	312	168	25	81		
			2	384	384	172	172		270	270	67	67			
24.1	24.5	0	1	283	447	283	119	45	173	321	173	26	88		
			2	399	399	167	167		285	285	221	221			
28.6	29.0	0	1	287	466	287	109	47	257	333	257	182	95		
			2	414	414	161	161		311	311	204	204			
33.1	33.5	0	1	292	486	292	97	48	262	372	262	152	103		
			2	429	429	154	154		339	339	184	184			
37.6	38.0	0	1	296	508	296	84	50	266	414	266	118	110		
			2	446	446	146	146		371	371	162	162			
42.1	42.5	0	1	301	532	301	70	52	271	462	271	80	118		
			2	464	464	138	138		406	406	136	136			
46.6	47.0	0	1	257	564	257	24	53	275	514	275	37	126		
			2	483	483	128	128		444	444	107	107			
51.1	51.5	0	1	246	604	246	24	55	245	606	245	24	133		
			2	504	504	116	116		486	486	74	74			
55.6	56.0	10	1	282	649	282	24	57	246	723	246	24	141		
			2	551	551	128	128		556	556	63	63			
60.1	60.5	30	1	394	721	394	67	59	290	852	290	24	149		
			2	625	625	163	163		657	657	71	71			
64.6	65.0	50	1	449	806	449	91	60	327	996	327	24	157		
			2	702	702	196	196		762	762	75	75			
69.1	69.5	70	1	506	895	506	117	62	361	1156	361	24	167		
			2	781	781	231	231		876	876	76	76			
73.6	74.0	95	1	575	999	575	152	65	412	1334	412	24	177		
			2	875	875	276	276		1008	1008	82	82			

12.2.268 Slewing section with 55 m Jib on UW 480

Tower crane without climbing frame

☐ Stationary

☒ Mobile

Size across corners: 8.0 m x 8.0 m

Hook height		Central ballast	Jib position	Crane in service					Horizontal load	Crane out of service				Horizontal load
				Slewing torque: 280 kNm				Wind region: C25						
				Corner loads				Corner loads						
				A	B	C	D	A		B	C	D		
[m]	[m]	[t]		[kN]	[kN]	[kN]	[kN]	[kN]	[kN]	[kN]	[kN]	[kN]	[kN]	
15.1	15.5	0	1	272	419	272	125	41	158	305	158	24	72	
			2	376	376	168	168		264	264	111	111		
19.6	20.0	0	1	279	439	279	118	44	168	312	168	25	81	
			2	392	392	165	165		274	274	224	224		
24.1	24.5	0	1	283	458	283	109	45	173	321	173	26	88	
			2	407	407	160	160		297	297	210	210		
28.6	29.0	0	1	288	477	288	99	47	258	350	258	166	95	
			2	422	422	154	154		323	323	193	193		
33.1	33.5	0	1	293	498	293	87	49	263	389	263	136	103	
			2	438	438	147	147		352	352	173	173		
37.6	38.0	0	1	297	520	297	74	50	267	432	267	102	110	
			2	455	455	140	140		384	384	150	150		
42.1	42.5	0	1	302	544	302	60	52	272	480	272	63	118	
			2	473	473	130	130		419	419	124	124		
46.6	47.0	0	1	306	569	306	43	54	272	536	272	24	126	
			2	492	492	120	120		457	457	95	95		
51.1	51.5	5	1	323	610	323	37	55	253	643	253	24	133	
			2	526	526	121	121		512	512	75	75		
55.6	56.0	15	1	353	665	353	41	57	253	760	253	24	141	
			2	573	573	132	132		583	583	63	63		
60.1	60.5	35	1	407	747	407	67	59	297	891	297	24	149	
			2	648	648	167	167		684	684	71	71		
64.6	65.0	55	1	462	833	462	91	60	333	1037	333	24	157	
			2	724	724	199	199		790	790	74	74		
69.1	69.5	75	1	519	922	519	116	63	367	1198	367	24	167	
			2	804	804	234	234		904	904	74	74		
73.6	74.0	100	1	589	1027	589	150	65	417	1376	417	24	177	
			2	898	898	279	279		1037	1037	81	81		

12.2.269 Slewing section with 57.5 m Jib on UW 480

Tower crane without climbing frame

☐ Stationary

☒ Mobile

Size across corners: 8.0 m x 8.0 m

Hook height		Central ballast	Jib position	Crane in service					Horizontal load	Crane out of service					Horizontal load
Slewing torque: 280 kNm				Wind region: C25											
Corner loads				Corner loads											
		[t]		A	B	C	D	[kN]	A	B	C	D	[kN]		
[m]	[m]			[kN]	[kN]	[kN]	[kN]		[kN]	[kN]	[kN]	[kN]			
15.1	15.5	0	1	272	410	272	133	41	158	305	158	24	72		
			2	370	370	174	174		261	261	62	62			
19.6	20.0	0	1	279	431	279	127	44	168	312	168	25	81		
			2	386	386	171	171		274	274	224	224			
24.1	24.5	0	1	283	449	283	118	45	173	321	173	25	88		
			2	400	400	166	166		297	297	209	209			
28.6	29.0	0	1	288	468	288	107	47	258	351	258	165	96		
			2	415	415	160	160		323	323	192	192			
33.1	33.5	0	1	292	489	292	96	49	262	390	262	135	103		
			2	431	431	153	153		352	352	172	172			
37.6	38.0	0	1	297	511	297	83	50	267	433	267	101	111		
			2	448	448	146	146		384	384	149	149			
42.1	42.5	0	1	301	534	301	68	52	271	481	271	62	118		
			2	466	466	137	137		419	419	123	123			
46.6	47.0	0	1	306	560	306	52	54	270	539	270	24	126		
			2	485	485	127	127		458	458	94	94			
51.1	51.5	5	1	323	600	323	46	55	251	646	251	24	134		
			2	519	519	127	127		513	513	73	73			
55.6	56.0	15	1	353	654	353	51	57	251	764	251	24	142		
			2	566	566	139	139		584	584	61	61			
60.1	60.5	35	1	407	737	407	78	59	294	895	294	24	150		
			2	640	640	174	174		685	685	69	69			
64.6	65.0	55	1	462	822	462	101	60	330	1041	330	24	158		
			2	717	717	207	207		791	791	72	72			
69.1	69.5	75	1	519	911	519	127	63	364	1203	364	24	168		
			2	796	796	242	242		905	905	72	72			
73.6	74.0	100	1	588	1015	588	162	65	413	1382	413	24	178		
			2	890	890	287	287		1038	1038	78	78			

12.2.270 Slewing section with 60 m Jib on UW 480

Tower crane without climbing frame

☐ Stationary

☒ Mobile

Size across corners: 8.0 m x 8.0 m

Hook height		Central ballast	Jib position	Crane in service					Horizontal load	Crane out of service				Horizontal load
				Slewing torque: 280 kNm				Wind region: C25						
				Corner loads				Corner loads						
				A	B	C	D	A		B	C	D		
[m]	[m]	[t]		[kN]	[kN]	[kN]	[kN]	[kN]	[kN]	[kN]	[kN]	[kN]	[kN]	
15.1	15.5	0	1	272	413	272	130	41	158	305	158	24	72	
			2	372	372	172	172		268	268	106	106		
19.6	20.0	0	1	279	434	279	124	44	168	313	168	24	82	
			2	389	389	169	169		283	283	215	215		
24.1	24.5	0	1	284	452	284	115	45	254	329	254	178	89	
			2	403	403	164	164		307	307	200	200		
28.6	29.0	0	1	288	472	288	105	47	258	364	258	152	96	
			2	418	418	158	158		333	333	183	183		
33.1	33.5	0	1	293	492	293	93	49	263	404	263	122	104	
			2	434	434	151	151		362	362	163	163		
37.6	38.0	0	1	297	514	297	80	50	267	447	267	87	111	
			2	451	451	144	144		395	395	140	140		
42.1	42.5	0	1	302	538	302	65	52	272	495	272	48	119	
			2	469	469	135	135		430	430	114	114		
46.6	47.0	0	1	306	563	306	49	54	256	569	256	24	126	
			2	488	488	124	124		469	469	84	84		
51.1	51.5	5	1	323	603	323	43	55	236	677	236	24	134	
			2	521	521	125	125		524	524	63	63		
55.6	56.0	20	1	365	671	365	60	57	260	796	260	24	142	
			2	581	581	149	149		608	608	63	63		
60.1	60.5	40	1	420	753	420	86	59	303	929	303	24	150	
			2	656	656	184	184		710	710	70	70		
64.6	65.0	60	1	474	839	474	110	60	339	1076	339	24	158	
			2	732	732	217	217		816	816	73	73		
69.1	69.5	80	1	532	928	532	135	63	371	1239	371	24	168	
			2	812	812	251	251		931	931	72	72		
73.6	74.0	110	1	614	1045	614	183	65	445	1420	445	24	178	
			2	918	918	309	309		1077	1077	90	90		

12.2.271 Slewing section with 62.5 m Jib on UW 480

Tower crane without climbing frame

☐ Stationary

☒ Mobile

Size across corners: 8.0 m x 8.0 m

Hook height		Central ballast	Jib position	Crane in service					Horizontal load	Crane out of service					Horizontal load
				Slewing torque: 280 kNm				Wind region: C25							
				Corner loads				Corner loads							
[m]	[m]	[t]		A	B	C	D		A	B	C	D			
				[kN]	[kN]	[kN]	[kN]	[kN]		[kN]	[kN]	[kN]	[kN]	[kN]	
15.1	15.5	0	1	280	404	280	156	42	188	324	188	52	73		
			2	368	368	192	192		284	284	92	92			
19.6	20.0	0	1	287	425	287	149	44	195	335	195	56	82		
			2	384	384	190	190		294	294	97	97			
24.1	24.5	0	1	291	443	291	140	46	200	343	200	56	89		
			2	399	399	184	184		314	314	209	209			
28.6	29.0	0	1	296	462	296	130	47	266	372	266	160	96		
			2	414	414	178	178		341	341	191	191			
33.1	33.5	0	1	301	483	301	118	49	271	411	271	130	104		
			2	430	430	172	172		370	370	171	171			
37.6	38.0	0	1	305	505	305	105	51	275	455	275	95	111		
			2	446	446	164	164		402	402	148	148			
42.1	42.5	0	1	310	529	310	91	52	280	504	280	56	119		
			2	464	464	155	155		438	438	121	121			
46.6	47.0	0	1	314	554	314	74	54	271	570	271	24	127		
			2	484	484	145	145		477	477	91	91			
51.1	51.5	5	1	331	594	331	69	56	251	679	251	24	135		
			2	517	517	145	145		533	533	70	70			
55.6	56.0	15	1	361	649	361	73	57	250	800	250	24	143		
			2	564	564	157	157		605	605	57	57			
60.1	60.5	35	1	415	731	415	100	59	292	934	292	24	151		
			2	639	639	192	192		707	707	64	64			
64.6	65.0	60	1	482	829	482	135	61	351	1084	351	24	159		
			2	728	728	237	237		827	827	78	78			
69.1	69.5	80	1	539	918	539	161	63	382	1249	382	24	169		
			2	807	807	272	272		942	942	77	77			
73.6	74.0	105	1	609	1023	609	196	65	430	1432	430	24	179		
			2	901	901	317	317		1077	1077	81	81			

12.2.272 Slewing section with 65 m Jib on UW 480

Tower crane without climbing frame

☐ Stationary

☒ Mobile

Size across corners: 8.0 m x 8.0 m

Hook height		Central ballast	Jib position	Crane in service					Horizontal load	Crane out of service				Horizontal load
				Slewing torque: 280 kNm				Wind region: C25						
				Corner loads				Corner loads						
				A	B	C	D	A		B	C	D		
[m]	[m]	[t]		[kN]	[kN]	[kN]	[kN]	[kN]	[kN]	[kN]	[kN]	[kN]	[kN]	
15.1	15.5	0	1	281	406	281	155	42	189	342	189	36	73	
			2	370	370	192	192		297	297	81	81		
19.6	20.0	0	1	288	427	288	148	44	196	353	196	39	82	
			2	386	386	189	189		307	307	85	85		
24.1	24.5	0	1	292	446	292	139	46	201	361	201	40	90	
			2	401	401	184	184		330	330	195	195		
28.6	29.0	0	1	297	465	297	129	47	267	393	267	140	97	
			2	416	416	178	178		356	356	177	177		
33.1	33.5	0	1	301	486	301	117	49	271	434	271	109	104	
			2	432	432	171	171		386	386	157	157		
37.6	38.0	0	1	306	508	306	104	51	276	478	276	74	112	
			2	449	449	163	163		419	419	133	133		
42.1	42.5	0	1	310	532	310	89	52	280	527	280	34	119	
			2	467	467	154	154		455	455	106	106		
46.6	47.0	0	1	315	557	315	73	54	249	616	249	24	127	
			2	486	486	144	144		494	494	76	76		
51.1	51.5	5	1	332	597	332	67	56	228	727	228	24	135	
			2	520	520	144	144		550	550	54	54		
55.6	56.0	25	1	387	677	387	96	57	276	849	276	24	143	
			2	592	592	181	181		648	648	65	65		
60.1	60.5	45	1	441	760	441	122	59	317	986	317	24	151	
			2	666	666	216	216		751	751	71	71		
64.6	65.0	65	1	496	846	496	146	61	350	1138	350	24	159	
			2	743	743	248	248		859	859	72	72		
69.1	69.5	90	1	565	947	565	183	63	406	1305	406	24	169	
			2	835	835	295	295		988	988	82	82		
73.6	74.0	115	1	635	1052	635	218	65	452	1491	452	24	179	
			2	930	930	340	340		1123	1123	86	86		